Technical sheet:

DOZER BLADE - MANUAL (COMPACT MACHINES)



Technical characteristics

Customer benefits

- Orientation: mechanical or hydraulic (2 cylinders).
- · Bolt-on wear plate.

• For all material pushing applications.



DOZER BLADE-MANUAL (COMPACT MACHINES) Created on November 4, 2025 at 6:09 AM UTC

Weight		BLD 1080	BLD 1480	BLD 1800 (a)	BLD 1800 (b)	BLD 2000 (a)	BLD 2000 (b)
Overall weight (kg)		135	185	205	205	288	288
Weight and dimensions							
Overall height (mm)	h17	677	677	677	677	677	677
Width (mm)		1080	1480	1800	1800	2000	2000
Depth (mm)	р5	813	813	813	813	813	813

SOR	Machines compatibility	BLD 1080	BLD 1480	BLD 1800 (a)	BLD 1800 (b)	BLD 2000 (a)	BLD 2000 (b)
1050R	All-Tach®	N726032	N736036	N51502488	N757041	N51502489	N757042
1050RT	850R	Х				-	-
1350R NXT2	1050R		Χ				
1350RT	1050RT		X			-	
1640E	1350R NXT2		Χ				
1650R	1350RT		Χ			-	
1650RT	1640E	Х					
1950RT	1650R			Х		-	
1950RT	1650RT				Х		
1950RT	1950RT				Х		
1950RT	1950RT				Х		
2100V	1950RT				Х		
2300V	1950RT				Х		
Part Part	2100V				Х		
R105	2300V				Х		
R165	2750V					Х	
RT105 x - <td>R105</td> <td></td> <td>Х</td> <td></td> <td></td> <td></td> <td></td>	R105		Х				
RT135 x - - - - RT165 - - x - - RT195 - NEW - - x - - RT195 - NEW - - x - - V210 - - x - - V230 - - x - - V275 - - x - - 1900R OLD - - x - - 2200R OLD - - x - x 2700V NXT2 OLD - - - x - x - R260 OLD - - - - x - - x - R260 OLD - - - - - x - - - - - - - - - - - - - <td>R165</td> <td></td> <td></td> <td>Х</td> <td></td> <td>-</td> <td></td>	R165			Х		-	
RT165	RT105		Х				
RT195 - NEW	RT135		Х				
RT195 - NEW	RT165				Х		
RT195 - NEW	RT195 - NEW				Х	-	
V210 - - x - - V230 - - x - - V275 - - - x - 1900R OLD - - - x - - 2200R OLD - - - x - - - 2600R OLD - - - - x - - - 2700V NXT2 OLD -	RT195 - NEW				Х		
V230 - - X - - V275 - - - X - 1900R OLD - - - X - - 2200R OLD - - - X - - 2600R OLD - - - X - X 2700V NXT2 OLD - - - X - X R220 OLD - - - X - X R260 OLD - - - X - X	RT195 - NEW				Х	-	-
V275 - - - - x - 1900R OLD - <t< td=""><td>V210</td><td></td><td></td><td></td><td>Х</td><td></td><td></td></t<>	V210				Х		
1900R OLD	V230				Х	-	
2200R OLD	V275				-	Х	
2600R OLD X - X - X - 2700V NXT2 OLD X X X X X X X X X X - X X - X - X - X - X - X - X - X - X - X - X - X - X - X - X X -	1900R OLD				Х		
2700V NXT2 OLD X - X - R220 OLD X - X	2200R OLD		-	-	X	-	-
R220 OLD	2600R OLD				Х		Х
R260 OLD X - X	2700V NXT2 OLD		-	-	-	X	-
_	R220 OLD				Х		
V270 OLD	R260 OLD		-	-	X	-	Х
	V270 OLD					X	

TABLE SYMBOL							
×	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank		
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition		





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes