Technical sheet:

EXTENSIBLE JIB WITH WINCH



Technical characteristics

- Oil immersed negative brake.
- Safety: homologated swivel self locking hook.
- Safety: end of cable/hook upper position automatic movement stop.
- Manual extension (manual winch) with adjustable jib length.
- Adjustable length for an excellent polyvalence (extension: manual jib).

Customer benefits

- Suspended load handling solution for all type of building sites.
- Perfect for transporting and placing beams, frames and other light and bulky elements.
- Its telescopic boom allows to gain greater flexibility while keeping an important forward reach.
- Tubular structure designed for an optimal weight / rigidity ratio
- · Excellent adaptability.



Technical characteristics		JWE 7000 / 800 39M	PT 800		
Distance to center of gravity (mm)		1791	1791		
Working height (mm)	h21	41000	32000		
Capacities					
Capacity (kg)		800	800		
Capacity 2 (kg)		1000	1000		
Weight					
Overall weight (kg)		605	605		
Dimensions					
Maximum outreach (mm)		4525	4525		
Maximum outreach 2 (mm)		7183	7183		
Weight and dimensions					
Overall length (mm)	I1	4632	4632		
Width (mm)		870	870		
Cable length (mm)		49000	37000		
Working Parameters					
Required machine equipment		\$\$ 6°	88 SE		
Hook Speed (m/mn)		30	30		

Machines compatibility	JWE 7000 / 800 39M	PT 800		
Reference number E-RECO	52717860	921323		
MRT 1845 75	X	·		
MRT 1845 115	X			
MRT 2145 115	X			
MRT 2260	X			
MRT 2260 e	X			
MRT 2545 115	X			
MRT 2570	X			
MRT 2660	X			
MRT 2660 e	X			
MRT 3060	X			
MRT 3570	X			
MRT 3570 ES	X			
MRT-X 1845	X			
MRT-X 2145	X			
MRT-X 2150 Privilege Plus		Х		
MRT-X 2260	X			
MRT-X 2470 Privilege Plus		X		
MRT-X 2545	X			
MRT-X 2550 Privilege Plus		X		
MRT-X 2570	X			
MRT-X 2660	X			
MRT-X 3050 Privilege Plus		X		
MRT-X 3060	X			
MRT-X 3255 Privilege Plus		X		
MRT-X 3570	X	-		
MRT-X 3570 ES	X	·		
MRT 2150 Privilege Plus OLD		Х		
MRT 2470 Privilege Plus OLD		Х		
MRT 2550 Privilege Plus OLD		Х		
MRT 3050 Privilege Plus OLD		Х		
MRT 3255 Privilege Plus OLD				

TABLE SYMBOL						
X	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank	
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition	





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes