

Technical sheet :

EXTENSION JIB WITH WINCH



Technical characteristics

- Wide range of crane with winch from 600 kg / 1323 lb to 2000 kg / 4410 lb with a forward reach max. from 4 m / 13 ft to 2.5 m / 8 ft.
- Oil immersed negative brakes.
- Safety: homologated swivel self locking hook.
- Limit switch sensor (up and down).

[The 3D picture at the top of this page is the reference PT 1000 - 921326].

Customer benefits

- Handling solution for suspended loads for all type of building sites.
- Turn your telehandler into a crane.
- Perfect for transporting and placing beams, frames and other suspended loads.
- Improves the forward reach of the telehandler.
- Its winch allows to gain greater flexibility while keeping an important forward reach.
- Tubular structure designed for an optimal weight/rigidity ratio.

Technical characteristics	JW 1950 LB	JW 2500 / 2000 35M	JW 3000 / 1500 44M	JW 4100 / 600 68M	JW 4100 / 1000 34M	PT 600	PT 1000	PT 1500	PT 2000 (a)	PT 2000 (b)
Distance to center of gravity (in)	3' 9"	2' 11"	3' 2"	3' 10"	3' 10"	3' 8"	3' 8"	3'	2' 10"	2' 10"
Working height (in)	h21	88' 7"	78' 9"	114' 10"	124' 8"	88' 7"	124' 8"	88' 7"	114' 10"	78' 9"
Capacities										
Capacity (lb)	1949	4409	3307	1323	2205	1323	2205	3307	4409	4409
Weight										
Overall weight (lb)	842	882	811	207	659	613	659	816	858	882
Dimensions										
Maximum outreach (in)	11' 7"	6' 7"	8' 8"	12' 2"	11' 7"	13' 6"	13' 6"	8' 8"	6' 7"	6' 7"
Weight and dimensions										
Overall length (in)	I1	13' 6"	8' 3"	9' 10"	13' 6"	13' 6"	13' 6"	9' 6"	7' 10"	7' 10"
Cable loop		1 loop	1 loop	Direct	Direct	1 loop	Direct	1 loop	Direct	1 loop
Width (in)		2' 8"	2' 8"	2' 8"	2' 8"	2' 8"	2' 8"	2' 8"	2' 8"	2' 8"
Cable length (in)		183' 9"	229' 8"	121' 5"	131' 3"	183' 9"	131' 3"	183' 9"	121' 5"	160' 9"
Working Parameters										
Required machine equipment										
Hook Speed (m/mn)		44	24	48	94	44	94	44	48	24

Machines compatibility	JW 1950 LB	JW 2500 / 2000 35M	JW 3000 / 1500 44M	JW 4100 / 600 68M	JW 4100 / 1000 34M	PT 600	PT 1000	PT 1500	PT 2000 (a)	PT 2000 (b)
Reference number E-RECO	52718275	52717582	52717710	52719496	52719497	921325	921326	921330	921331	939392
MRT 1645 75	-	X	X	X	X	X	X	X	X	X
MRT 1645 115	-	X	X	X	X	X	X	X	X	X
MRT 1845 75	-	X	X	X	X	X	X	X	X	X
MRT 1845 115	-	X	X	X	X	X	X	X	X	X
MRT 2145 115	-	X	X	X	X	X	X	X	X	X
MRT 2260	X	X	X	X	X	X	X	X	X	X
MRT 2260 e	X	X	X	X	X	-	-	-	-	-
MRT 2545 115	-	X	X	X	X	X	X	X	X	X
MRT 2570	X	X	X	X	X	X	X	X	X	X
MRT 2660	X	X	X	X	X	X	X	X	X	X
MRT 2660 e	X	X	X	X	X	-	-	-	-	-
MRT 3060	X	X	X	X	X	X	X	X	X	X
MRT 3570	X	X	X	X	X	X	X	X	X	X
MRT 3570 ES	X	X	X	X	X	X	X	X	X	X
MRTX 1645	-	X	X	X	X	X	X	X	X	X
MRTX 1845	-	X	X	X	X	X	X	X	X	X
MRTX 2145	-	X	X	X	X	X	X	X	X	X
MRTX 2260	X	X	X	X	X	X	X	X	X	X
MRTX 2545	-	X	X	X	X	X	X	X	X	X
MRTX 2570	X	X	X	X	X	X	X	X	X	X
MRTX 2660	X	X	X	X	X	X	X	X	X	X
MRTX 3060	X	X	X	X	X	X	X	X	X	X
MRTX 3570	X	X	X	X	X	X	X	X	X	X
MRTX 3570 ES	X	X	X	X	X	X	X	X	X	X
MRT 1440 Easy T4 S2 400° <small>OLD</small>	-	-	-	-	-	X	X	X	-	-
MRT 1640 Easy T4 S2 360° <small>OLD</small>	-	-	-	-	-	X	X	X	-	-
MRT 1640 Easy T4 S2 400° <small>OLD</small>	-	-	-	-	-	X	X	X	-	-
MRT 1840 Easy T4 S1 360° <small>OLD</small>	-	-	-	-	-	-	X	-	-	-
MRT 1840 Easy T4 S1 400° <small>OLD</small>	-	-	-	-	-	-	X	-	-	-
MRT 1840 Easy T4 S2 360° <small>OLD</small>	-	-	-	-	-	X	X	X	-	-
MRT 1840 Easy T4 S2 400° <small>OLD</small>	-	-	-	-	-	X	X	X	-	-
MRT 2145 Easy T4 S2 360° <small>OLD</small>	-	-	-	-	-	X	X	X	-	-
MRT 2145 Easy T4 S2 400° <small>OLD</small>	-	-	-	-	-	X	X	X	-	-
MRT 2150 Privilege Plus <small>OLD</small>	-	-	-	-	-	X	X	X	-	-
MRT 2470 Privilege Plus <small>OLD</small>	-	-	-	-	-	X	-	X	-	X
MRT 2545 Easy T4 S2 360° <small>OLD</small>	-	-	-	-	-	X	X	X	-	X
MRT 2545 Easy T4 S2 400° <small>OLD</small>	-	-	-	-	-	X	X	X	-	X
MRT 2550 Privilege Plus <small>OLD</small>	-	-	-	-	-	X	X	X	-	X
MRT 3050 Privilege Plus <small>OLD</small>	-	-	-	-	-	X	X	X	-	X
MRT 3255 Privilege Plus <small>OLD</small>	-	-	-	-	-	X	-	X	-	X
MRTX 1840 Easy 360° <small>OLD</small>	-	-	-	-	-	X	X	X	-	-
MRTX 1840 Easy 400° <small>OLD</small>	-	-	-	-	-	X	X	X	-	-
MRTX 2145 Easy 360° <small>OLD</small>	-	-	-	-	-	X	X	X	-	-
MRTX 2145 Easy 400° <small>OLD</small>	-	-	-	-	-	X	X	X	-	-
MRTX 2150 Privilege Plus <small>OLD</small>	-	-	-	-	-	X	X	X	-	-
MRTX 2470 Privilege Plus <small>OLD</small>	-	-	-	-	-	X	-	X	-	X
MRTX 2545 Easy 360° <small>OLD</small>	-	-	-	-	-	X	X	X	-	X
MRTX 2545 Easy 400° <small>OLD</small>	-	-	-	-	-	X	X	X	-	X
MRTX 2550 Privilege Plus <small>OLD</small>	-	-	-	-	-	X	X	X	-	X
MRTX 3050 Privilege Plus <small>OLD</small>	-	-	-	-	-	X	X	X	-	X
MRTX 3255 Privilege Plus <small>OLD</small>	-	-	-	-	-	X	-	X	-	X

TABLE SYMBOL	No predisposition required	Hydraulic line	Return piping to hydraulic oil tank

TABLE SYMBOL

	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition
--	-------------------------	--	-------------------------	--	---



MANITOU HANDLING YOUR WORLD

Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes