Technical sheet :

EXTENSION JIB WITH WINCH

Technical characteristics

- Wide range of crane with winch from 600 kg (1323 lb) to 2000 kg (4409 lb) with a forward reach max. from 4 m (13.1 ft) to 2.5 m (8.2 ft).
- Oil immersed negative brakes.
- Safety: homologated swivel self-locking hook.
- Limit switch sensor (up and down).

[The 3D picture at the top of this page is the reference PT 1000 - 921326].

Customer benefits

- Handling solution for suspended loads for all type of building sites.
- Turn your telehandler into a crane.
- Perfect for transporting and placing beams, frames and other suspended loads.
- Improves the forward reach of the telehandler.
- Its winch allows to gain greater flexibility while keeping an important forward reach.
- Tubular structure designed for an optimal weight/rigidity ratio.

		JW 1950 LBS	JW 2100/3000 62M	JW 2500/2000 35M	JW 3000/1500 43M	JW 3000/1500 71M	JW 4100/1000 34M	JW 4100/1950 55M
Reference number		52718275	52816510	52717582	52717710	52810359	52719497	52807264
Working height (mm)	h21	27	62	24	35	71	27	55
Capacity (kg)		1950	3000	2000	1500	1500	1000	885
Overall weight (kg)		382	615	400	368	379	299	420
Height (mm)		1564	1211	888	893	-	1540	1546
Length (mm)		4107	2255	2516	2990	2887	4107	3879
Max. outreach (mm)		3542	2093	2008	2633	2633	3542	3550
Cable		1 loop	Direct	1 loop	Direct	Direct	1 loop	1 loop
Width (mm)		810	815	815	815	815	810	940
Required machine equipment								
Hook Speed (m/mn)		44	-	24	35	-	44	-
E-RECO		Yes	Yes	Yes	Yes	Yes	Yes	Yes
Connection system		Manitou	Manitou	Manitou	Manitou	Manitou	Manitou	Manitou

Machines compatibility							
MRT 2260	X	-	X	X	-	X	-
MRT 2260 e	X	-	-	X	-	X	-
MRT 2570	X	-	X	X	-	X	-
MRT 2660	X	-	X	X	-	X	-
MRT 2660 e	X	-	X	X	-	X	-
MRT 3060	X	-	X	X	-	X	-
MRT 3570	X	-	X	X	-	X	-
MRT 3570 ES	X	-	X	X	-	X	-
MRT 4080	-	X	-	-	X	-	X
MRT-X 2260	X	-	-	X	-	X	-
MRT-X 2570	X	-	X	X	-	X	-
MRT-X 2660	X	-	X	X	-	X	-
MRT-X 3060	X	-	X	X	-	X	-
MRT-X 3570	X	-	X	X	-	X	-
MRT-X 3570 ES	X	-	X	X	-	X	-
MRT-X 4080	-	X	-	-	X	-	X

		JW 4100/600 68M	PT 600	PT 1000	PT 1500	PT 2000	PT 2000
Reference number		52719496	921325	921326	921330	921331	939392
Working height (mm)	h21	38	38	27	35	24	24
Capacity (kg)		600	600	1000	1500	2000	2000
Overall weight (kg)		354	278	348	370	389	400
Height (mm)		1540	1540	1564	1350	1564	1564
Length (mm)		4107	4104	3949	2887	2388	2387
Max. outreach (mm)		3703	4104	3542	2633	2008	2008
Cable		Direct	Direct	1 loop	Direct	1 loop	1 loop
Width (mm)		810	815	815	815	815	815
Required machine equipment							
Hook Speed (m/mn)		94	94	44	48	24	24
E-RECO		Yes	Yes	Yes	Yes	Yes	Yes
Connection system		Manitou	Manitou	Manitou	Manitou	Manitou	Manitou

Machines compatibility						
MRT 1845 75	-	X	X	X	X	-
MRT 1845 115	-	X	X	X	X	-
MRT 2145 115	-	X	X	X	X	-
MRT 2260	X	-	-	-	-	-
MRT 2260 e	X	-	-	-	-	-
MRT 2545 115	-	X	X	X	-	X
MRT 2570	X	-	-	-	-	-
MRT 2660	X	-	-	-	-	-
MRT 2660 e	X	-	-	-	-	-
MRT 3060	X	-	-	-	-	-
MRT 3570	X	-	-	-	-	-
MRT 3570 ES	X	-	-	-	-	-
MRT-X 1845	-	X	X	X	X	-
MRT-X 2145	-	X	X	X	X	-
MRT-X 2260	X	-	-	-	-	-
MRT-X 2545	-	X	X	X	-	X
MRT-X 2570	X	-	-	-	-	-
MRT-X 2660	X	-	-	-	-	-
MRT-X 3060	X	-	-	-	-	-
MRT-X 3570	X	-	-	-	-	-
MRT-X 3570 ES	X	-	-	-	-	-
MRT 1645 75 OLD	-	X	X	X	X	-
MRT 1645 115 OLD	-	X	X	X	X	-
MRT-X 1645 OLD	-	X	X	X	X	-

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition

Head Office
B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com

This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.
MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes