

技術シート：

FAST OPENING PLATFORM



諸元

- Capacity 365/1000/700 kg / 805/2205/1544 lb including 3 people.
- Unfolded working width 4,4 m / 14 ft
- Slewing platform +/- 90° on both sides.
- Legally approved for 3 persons.
- Accessible from 3 sides (2x Side + 1 front).
- version "D": right access with side door.
- version "DD": front and right access with side door.
- Overload sensor.
- Fork sleeves: 238 mm x 100 mm / 9 in x 4 in.

[The 3D picture at the top of this page is the reference P 4400/700 S EXT D - 52869500].

お客様のメリット

- Flexibility on aerial working situations.
- User-friendly opening system, complete opening/closing within 50 seconds.
- Heavy duty, galvanized structure for an improved longevity.
- Non-slip metal floor.
- Expandable sides are independent.
- Fork sleeves for yard handling.

諸元		P 4400 / 365 S EXT D	P 4400 / 365 S EXT DD	P 4400 / 700 S EXT D	P 4400 / 850 S EXT D	P 4400 / 1000 S EXT D	PSE 4400 / 365	PSE 4400 / 365 (MRT)	PSE 4400 / 365 D (MRT)	PSE 4400 / 365 DD (MRT)	PSE 4400 / 700 D (MRT)
人員を含む容量 (kg)		365	365	700	850	1000	365	365	365	365	700
人員数		3	3	3	3	3	3	3	3	3	3
重心位置までの距離 (mm)		1297	1187	1187	1187	1187	1187	1297	1297	1383	1187
重量											
重量 (kg)		670	690	1030	1030	1030	650	670	670	690	1030
仕様											
全高 (mm)	h17	1300	1312	1312	2429824000	1312	1300	1300	1300	1312	1312
全長 (mm)	l1	2430	2261	2261	2335	2261	2430	2430	2430	2261	2261
最小幅 (mm)		2282	2282	2282	2282	2282	2281	2281	2282	2282	2282
最大幅 (mm)		4838	4348	4348	4387	4348	4388	4388	4388	4348	4348
深さ (mm)	p5	1150	1150	1150	1150	1150	1150	1150	1150	1150	1150
ワーキング パラメーター											
機械設備											
回転 1 (°)		-	90	-	90	90	90	90	90	90	90
回転 2 (°)		-	90	-	90	90	90	90	90	90	90

マシンの互換性	P 4400 / 365 S EXT D	P 4400 / 365 S EXT DD	P 4400 / 700 S EXT D	P 4400 / 850 S EXT D	P 4400 / 1000 S EXT D	PSE 4400 / 365	PSE 4400 / 365 (MRT)	PSE 4400 / 365 D (MRT)	PSE 4400 / 365 DD (MRT)	PSE 4400 / 700 D (MRT)
参照番号	52869498	52869501	52869500	52915865	52869499	-	-	-	-	-
MT 1335 HA 75D ST5	X	X	X	-	-	-	-	-	-	-
MT 1335 HA 100D ST5	X	X	X	-	-	-	-	-	-	-
MT 1440 A	X	X	X	X	X	-	-	-	-	-
MT 1440 HA	X	X	X	X	X	-	-	-	-	-
MT 1840 A	X	X	X	X	-	-	-	-	-	-
MT 1840 HA	X	X	X	X	-	-	-	-	-	-
MT-X 1440 A	X	X	X	X	X	-	-	-	-	-
MT-X 1840 A	X	X	X	X	-	-	-	-	-	-
MT 1440 A ST5 OLD	X	X	X	X	X	-	-	-	-	-
MT 1440 HA ST5 OLD	X	X	X	X	X	-	-	-	-	-
MT 1840 A ST5 S1 OLD	X	X	X	X	-	-	-	-	-	-
MT 1840 HA ST5 S1 OLD	X	X	X	X	-	-	-	-	-	-
MT-X 1440 A OLD	X	X	X	X	X	-	-	-	-	-
MT-X 1840 A OLD	X	X	X	X	-	-	-	-	-	-
参照番号 E-RECO	-	-	-	-	-	914500	52719248	52686224	52719250	52719251
MRT 1645 75	-	-	-	-	-	-	X	X	X	X
MRT 1645 115	-	-	-	-	-	-	X	X	X	X
MRT 1845 75	-	-	-	-	-	-	X	X	X	X
MRT 1845 115	-	-	-	-	-	-	X	X	X	X
MRT 2145 115	-	-	-	-	-	-	X	X	X	X
MRT 2260	-	-	-	-	-	-	X	X	X	X
MRT 2260 e	-	-	-	-	-	-	X	X	X	X
MRT 2545 115	-	-	-	-	-	-	X	X	X	X
MRT 2570	-	-	-	-	-	-	X	X	X	X
MRT 2660	-	-	-	-	-	-	X	X	X	X
MRT 2660 e	-	-	-	-	-	-	X	X	X	X
MRT 3060	-	-	-	-	-	-	X	X	X	X
MRT 3570	-	-	-	-	-	-	X	X	X	X
MRT 3570 ES	-	-	-	-	-	-	X	X	X	X
MRT 4080	-	-	-	-	-	-	X	X	X	X
MRT-X 1645	-	-	-	-	-	-	X	X	X	X
MRT-X 1845	-	-	-	-	-	-	X	X	X	X
MRT-X 2145	-	-	-	-	-	-	X	X	X	X
MRT-X 2260	-	-	-	-	-	-	X	X	X	X
MRT-X 2545	-	-	-	-	-	-	X	X	X	X
MRT-X 2570	-	-	-	-	-	-	X	X	X	X
MRT-X 2660	-	-	-	-	-	-	X	X	X	X
MRT-X 3060	-	-	-	-	-	-	X	X	X	X
MRT-X 3570	-	-	-	-	-	-	X	X	X	X
MRT-X 3570 ES	-	-	-	-	-	-	X	X	X	X
MRT-X 4080	-	-	-	-	-	-	X	X	X	X
MHT 790 OLD	-	-	-	-	-	X	-	-	-	-
MRT 1440 Easy 3B S2 400° OLD	-	-	-	-	-	X	-	-	-	-
MRT 1440 Easy T4 S1 400° OLD	-	-	-	-	-	X	-	-	-	-
MRT 1440 Easy T4 S2 400° OLD	-	-	-	-	-	X	-	-	-	-
MRT 1640 Easy 3B S2 360° OLD	-	-	-	-	-	X	-	-	-	-
MRT 1640 Easy 3B S2 400° OLD	-	-	-	-	-	X	-	-	-	-
MRT 1640 Easy T4 S1 360° OLD	-	-	-	-	-	X	-	-	-	-
MRT 1640 Easy T4 S1 400° OLD	-	-	-	-	-	X	-	-	-	-
MRT 1640 Easy T4 S2 360° OLD	-	-	-	-	-	X	-	-	-	-
MRT 1640 Easy T4 S2 400° OLD	-	-	-	-	-	X	-	-	-	-
MRT 1840 Easy 3B S2 360° OLD	-	-	-	-	-	X	-	-	-	-
MRT 1840 Easy 3B S2 400° OLD	-	-	-	-	-	X	-	-	-	-
MRT 1840 Easy T4 S1 360° OLD	-	-	-	-	-	X	-	-	-	-
MRT 1840 Easy T4 S1 400° OLD	-	-	-	-	-	X	-	-	-	-
MRT 1840 Easy T4 S2 360° OLD	-	-	-	-	-	X	-	-	-	-
MRT 1840 Easy T4 S2 400° OLD	-	-	-	-	-	X	-	-	-	-
MRT 2145 Easy 3B S2 360° OLD	-	-	-	-	-	X	-	-	-	-

マシンの互換性	P 4400 / 365 S EXT D	P 4400 / 365 S EXT DD	P 4400 / 700 S EXT D	P 4400 / 850 S EXT D	P 4400 / 1000 S EXT D	PSE 4400 / 365	PSE 4400 / 365 (MRT)	PSE 4400 / 365 D (MRT)	PSE 4400 / 365 DD (MRT)	PSE 4400 / 700 D (MRT)
MRT 2145 Easy 3B S2 400° OLD	-	-	-	-	-	X	-	-	-	-
MRT 2145 Easy T4 S1 360° OLD	-	-	-	-	-	X	-	-	-	-
MRT 2145 Easy T4 S1 400° OLD	-	-	-	-	-	X	-	-	-	-
MRT 2145 Easy T4 S2 360° OLD	-	-	-	-	-	X	-	-	-	-
MRT 2145 Easy T4 S2 400° OLD	-	-	-	-	-	X	-	-	-	-
MRT 2150 Privilege Plus OLD	-	-	-	-	-	X	-	-	-	-
MRT 2470 Privilege Plus OLD	-	-	-	-	-	X	-	-	-	-
MRT 2545 Easy 3B S2 360° OLD	-	-	-	-	-	X	-	-	-	-
MRT 2545 Easy 3B S2 400° OLD	-	-	-	-	-	X	-	-	-	-
MRT 2545 Easy T4 S1 360° OLD	-	-	-	-	-	X	-	-	-	-
MRT 2545 Easy T4 S1 400° OLD	-	-	-	-	-	X	-	-	-	-
MRT 2545 Easy T4 S2 360° OLD	-	-	-	-	-	X	-	-	-	-
MRT 2545 Easy T4 S2 400° OLD	-	-	-	-	-	X	-	-	-	-
MRT 2550 Privilege Plus OLD	-	-	-	-	-	X	-	-	-	-
MRT 3050 Privilege Plus OLD	-	-	-	-	-	X	-	-	-	-
MRT 3255 Privilege Plus OLD	-	-	-	-	-	X	-	-	-	-
MRT-X 1840 Easy 360° OLD	-	-	-	-	-	X	-	-	-	-
MRT-X 1840 Easy 400° OLD	-	-	-	-	-	X	-	-	-	-
MRT-X 2145 Easy 360° OLD	-	-	-	-	-	X	-	-	-	-
MRT-X 2145 Easy 400° OLD	-	-	-	-	-	X	-	-	-	-
MRT-X 2150 Privilege Plus OLD	-	-	-	-	-	X	-	-	-	-
MRT-X 2470 Privilege Plus OLD	-	-	-	-	-	X	-	-	-	-
MRT-X 2545 Easy 360° OLD	-	-	-	-	-	X	-	-	-	-
MRT-X 2545 Easy 400° OLD	-	-	-	-	-	X	-	-	-	-
MRT-X 2550 Privilege Plus OLD	-	-	-	-	-	X	-	-	-	-
MRT-X 3050 Privilege Plus OLD	-	-	-	-	-	X	-	-	-	-
MRT-X 3255 Privilege Plus OLD	-	-	-	-	-	X	-	-	-	-
参照番号 E-RECO 2	-	-	-	-	-	939241	52719665	-	-	52719668
MRT 1645 75	-	-	-	-	-	-	X	-	-	X
MRT 1645 115	-	-	-	-	-	-	X	-	-	X
MRT 1845 75	-	-	-	-	-	-	X	-	-	X
MRT 1845 115	-	-	-	-	-	-	X	-	-	X
MRT 2145 115	-	-	-	-	-	-	X	-	-	X
MRT 2260	-	-	-	-	-	-	X	-	-	X
MRT 2260 e	-	-	-	-	-	-	X	-	-	X
MRT 2545 115	-	-	-	-	-	-	X	-	-	X
MRT 2570	-	-	-	-	-	-	X	-	-	X
MRT 2660	-	-	-	-	-	-	X	-	-	X
MRT 2660 e	-	-	-	-	-	-	X	-	-	X
MRT 3060	-	-	-	-	-	-	X	-	-	X
MRT 3570	-	-	-	-	-	-	X	-	-	X
MRT 3570 ES	-	-	-	-	-	-	X	-	-	X
MRT-X 1645	-	-	-	-	-	-	X	-	-	X
MRT-X 1845	-	-	-	-	-	-	X	-	-	X
MRT-X 2145	-	-	-	-	-	-	X	-	-	X
MRT-X 2260	-	-	-	-	-	-	X	-	-	X
MRT-X 2545	-	-	-	-	-	-	X	-	-	X
MRT-X 2570	-	-	-	-	-	-	X	-	-	X
MRT-X 2660	-	-	-	-	-	-	X	-	-	X
MRT-X 3060	-	-	-	-	-	-	X	-	-	X
MRT-X 3570	-	-	-	-	-	-	X	-	-	X
MRT-X 3570 ES	-	-	-	-	-	-	X	-	-	X
MHT 10130 OLD	-	-	-	-	-	X	-	-	-	-
MHT 10180 OLD	-	-	-	-	-	X	-	-	-	-
MHT 10230 OLD	-	-	-	-	-	X	-	-	-	-

諸元		PSE 4400 / 1000 D (MHT)	PSE 4400 / 1000 D (MRT)	コース 4400 / 365 (MHT)
人員を含む容量 (kg)		1000	1000	365
人員数		3	3	3
重心位置までの距離 (mm)		1187	1187	1187
重量				
重量 (kg)		-	1030	675
仕様				
全高 (mm)	h17	1030	1312	1300
全長 (mm)	l1	2261	2261	2430
最小幅 (mm)		2282	2282	2281
最大幅 (mm)		4348	4348	4388
深さ (mm)	p5	1150	1150	1150
ワーキング パラメーター				
機械設備				
回転 1 (°)		90	90	90
回転 2 (°)		90	90	90

マシンの互換性	PSE 4400 / 1000 D (MHT)	PSE 4400 / 1000 D (MRT)	コース 4400 / 365 (MHT)
参照番号	-	-	-
参照番号 E-RECO	5272783	52619610	5272782
MHT 10135 ST5	X	-	X
MHT 10160 ST5	X	-	X
MHT 10200 ST5	X	-	X
MHT 11250 Mining ST5	X	-	X
MHT 11250 ST5	X	-	X
MHT-X 10135 ST3A	X	-	X
MHT-X 10160 ST3A	X	-	X
MHT-X 10200 ST3A	X	-	X
MHT-X 11250 Mining	X	-	X
MHT-X 11250 ST3A	X	-	X
MRT 1645 75	-	X	-
MRT 1645 115	-	X	-
MRT 1845 75	-	X	-
MRT 1845 115	-	X	-
MRT 2145 115	-	X	-
MRT 2260	-	X	-
MRT 2260 e	-	X	-
MRT 2545 115	-	X	-
MRT 2570	-	X	-
MRT 2660	-	X	-
MRT 2660 e	-	X	-
MRT 3060	-	X	-
MRT 3570	-	X	-
MRT 3570 ES	-	X	-
MRT 4080	-	X	-
MRT-X 1645	-	X	-
MRT-X 1845	-	X	-
MRT-X 2145	-	X	-
MRT-X 2260	-	X	-
MRT-X 2545	-	X	-
MRT-X 2570	-	X	-
MRT-X 2660	-	X	-
MRT-X 3060	-	X	-
MRT-X 3570	-	X	-
MRT-X 3570 ES	-	X	-
MRT-X 4080	-	X	-
参照番号 E-RECO 2	52747068	52719669	52747071
MHT 10135 ST5	X	-	X
MHT 10160 ST5	X	-	X
MHT 10200 ST5	X	-	X
MHT 11250 Mining ST5	X	-	X
MHT 11250 ST5	X	-	X
MHT-X 10135 ST3A	X	-	X
MHT-X 10160 ST3A	X	-	X
MHT-X 10200 ST3A	X	-	X
MHT-X 11250 Mining	X	-	X
MHT-X 11250 ST3A	X	-	X
MRT 1645 75	-	X	-
MRT 1645 115	-	X	-
MRT 1845 75	-	X	-
MRT 1845 115	-	X	-
MRT 2145 115	-	X	-
MRT 2260	-	X	-
MRT 2260 e	-	X	-
MRT 2545 115	-	X	-
MRT 2570	-	X	-
MRT 2660	-	X	-

マシンの互換性	PSE 4400 / 1000 D (MHT)	PSE 4400 / 1000 D (MRT)	コース 4400 / 365 (MHT)
MRT 2660 e	-	X	-
MRT 3060	-	X	-
MRT 3570	-	X	-
MRT 3570 ES	-	X	-
MRT-X 1645	-	X	-
MRT-X 1845	-	X	-
MRT-X 2145	-	X	-
MRT-X 2260	-	X	-
MRT-X 2545	-	X	-
MRT-X 2570	-	X	-
MRT-X 2660	-	X	-
MRT-X 3060	-	X	-
MRT-X 3570	-	X	-
MRT-X 3570 ES	-	X	-

記号の表					
	前処理が不要		油圧ライン		タンクへの油圧リターン
	電気要素		プラットフォーム要素		タイヤクランプ、シリンダークランプ要素



本社ビル

B.P. 249 - 430 rue de l'Aubinière オービニエール通り
44150 Ancenis Cedex - France

電話 +33 (0)2 40 09 10 11 - ファックス +33 (0)2 40 09 10 97

www.manitou.com



本書では、マニトウ製品の構成バージョンやオプションについて説明していますが、機器によって異なる場合があります。このパンフレットで紹介されている機器は、バージョンによってシリーズの一部であったり、オプションであったり、あるいは利用できない場合があります。Manitouは、いつでも予告なしに、記載・表現されている仕様を変更する権利を有します。提供された仕様はメーカーを拘束するものではありません。詳細につきましては、マニトウの代理店にお問い合わせください。本資料は、契約上の拘束力を有するものではありません。製品の提示は、契約上の拘束力はありません。仕様のリストは無尽蔵です。ロゴおよび会社のビジュアル・アイデンティティはManitouが所有しており、許可なく使用することはできません。すべての権利はマニトウに帰属します。このパンフレットに掲載されている写真や図は、相談や情報提供を目的としています。

MANITOU BF SA - 取締役会を有する有限会社・株式資本。39 668 399 ユーロ - 857 802 508 RCS Nantes