Technical sheet :

# FIXED PLATFORM

## Technical characteristics

- Capacity 200 kg (441 lb) or 365 kg (805 lb).
- Platform fixed.
- Legally approved up to 3 people (platform capacity includes up to 3 people).
- Overload (200 kg (4401 lb) or 365 kg (805 lb)) and presence sensor.
- Painted platform.
- Non-slip metal floor.
- Fork sleeves: 238 mm (9.4 in) x 100 mm (3.9 in).

[The 3D picture at the top of this page is the reference NAC 2M - 788782].

## Customer benefits

- Uncompromised safety for all your people lifting applications.
- Simple and high-performing platform, providing a cost-effective solution.
- Maximum protection ensured by a continuous handrail around the entire platform.
- Dual side access for increased flexibility and convenience on site.
- Equipped with integrated fork sleeves for easy handling around the yard.

| | | P 2200/365 FX | PF 1200/200 | PF 2000/365 | PF 2000/365 | PF 2000/365 |
|---|---|---|---|---|---|---|
| Reference number | | 52869493 | 52719244 | 52719245 | 52747069 | 52719658 |
| Capacity including people (kg) | | 365 | 200 | 365 | 365 | 365 |
| Number of people | | 3 | 2 | 3 | 3 | 3 |
| Overall weight (kg) | | 412 | 165 | 393 | 414 | 409 |
| Height (mm) | | 1649 | 1240 | 1631 | 1631 | 1629 |
| Length (mm) | | 1812 | 1173 | 1812 | 1755 | 1812 |
| Width (mm) | | 2190 | 1391 | 2190 | 2190 | 2190 |
| Depth (mm) | p5 | 1150 | 740 | 1150 | 1150 | 1150 |
| Required machine equipment | | | | | | |
| Extendable | | No | No | No | No | No |
| Rotation capability | | Fixed | Fixed | Fixed | Fixed | Fixed |
| E-RECO | | No | Yes | Yes | Yes | Yes |
| Connection system | | Manitou | Manitou | Manitou | Manitou | Manitou |

| Machines compatibility | | | | | |
|---|---|---|---|---|---|
| MHT 790 Mining ST5 | - | - | X | - | X |
| MHT 790 ST5 | - | - | X | - | X |
| MHT 10135 ST5 | - | - | - | X | - |
| MHT 10160 ST5 | - | - | - | X | - |
| MHT 10200 ST5 | - | - | - | X | - |
| MHT 11250 Mining ST5 | - | - | - | X | - |
| MHT 11250 ST5 | - | - | - | X | - |
| MHT-X 790 Mining ST3A | - | - | X | - | X |
| MHT-X 790 ST3A | - | - | X | - | X |
| MHT-X 10135 ST3A | - | - | - | X | - |
| MHT-X 10160 ST3A | - | - | - | X | - |
| MHT-X 10200 ST3A | - | - | - | X | - |
| MHT-X 11250 Mining | - | - | - | X | - |
| MHT-X 11250 ST3A | - | - | - | X | - |
| MRT 1845 75 | - | X | X | - | X |
| MRT 1845 115 | - | X | X | - | X |
| MRT 2145 115 | - | X | X | - | X |
| MRT 2260 | - | X | X | - | X |
| MRT 2260 e | - | X | X | - | X |
| MRT 2545 115 | - | X | X | - | X |
| MRT 2570 | - | X | X | - | X |
| MRT 2660 | - | X | X | - | X |
| MRT 2660 e | - | X | X | - | X |
| MRT 3060 | - | X | X | - | X |
| MRT 3570 | - | X | X | - | X |
| MRT 3570 ES | - | X | X | - | X |
| MRT-X 1845 | - | X | X | - | X |
| MRT-X 2145 | - | X | X | - | X |
| MRT-X 2260 | - | X | X | - | X |
| MRT-X 2545 | - | X | X | - | X |
| MRT-X 2570 | - | X | X | - | X |
| MRT-X 2660 | - | X | X | - | X |
| MRT-X 3060 | - | X | X | - | X |
| MRT-X 3570 | - | X | X | - | X |
| MRT-X 3570 ES | - | X | X | - | X |
| MT 1335 HA 75D ST5 | X | - | - | - | - |
| MT 1335 HA 100D ST5 | X | - | - | - | - |
| MRT 1645 75 OLD | - | X | X | - | X |
| MRT 1645 115 OLD | - | X | X | - | X |
| MRT-X 1645 OLD | - | X | X | - | X |

| TABLE SYMBOL | | | | | |
|---|---|---|---|---|---|
| | No predisposition required | | Hydraulic line | | Return piping to hydraulic oil tank |
| | Electric predisposition | | Platform predisposition | | Tyre handler, cylinder handler predisposition |

**Head Office**
B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com

This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.
MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes