Technical sheet:

MOWER (COMPACT MACHINES)



Technical characteristics

- Cut grass up and small branches.
- · Equipped with hammers.
- Front protection chains.
- Floating deck.

[The 3D picture at the top of this page is the reference MV 1500 - 52728002].

Customer benefits

- Must-have attachment for parks and gardens maintenance.
- Efficient work, cuts grass and small branches in one shot.
- Equipped with a floating deck to work on rough terrain with ease.
- Equipped with chains on the front to minimize projections.



Weight		MF 1600 SK	MF 1900 SK	MV 1500
Overall weight (kg)		480	530	268
Weight and dimensions				
Overall height (mm)	h17	940	940	633
Overall length (mm)	11	1230	1230	999
Width (mm)		1818	2122	1664
Working Parameters				
Required machine equipment		88 gc		₽₽ 9 c
Side shift		No	No	No
Working width (mm)		1608	1912	1530
Minimum hydraulic requirements (I/min)		75	75	42
Maximum hydraulic requirements (I/min)		125	125	120
Number of blade		24	28	24
Maximum cutting diameter (mm)		40	40	30
Maximum cutting height (mm)		300	300	300
Blade type		Hammer blade	Hammer blade	Hammer blade
Other Data for Attachments				
E-RECO		No	No	No
Connection system		Universal Quick-attach	Universal Quick-attach	

Machines compatibility	MF 1600 SK	MF 1900 SK	MV 1500
All-Tach®	52845078	52845079	52728002
4 point Carriage	-	-	52741076
Euro Carriage	-	-	52741075
2100V	X		
2100VT	X	•	
2300V		X	
2300VT	-	X	-
2750V		X	
2750VT	-	X	-
GCT 3-14			X
GCT 3-14	-	<u> </u>	X
GCT 3-14 +			X
GCT 3-14+	-	<u> </u>	X
ULM 412 H			X
ULM 412 H	-	<u> </u>	X
ULM 415 H			X
ULM 415 H	-	<u> </u>	X
V210	X		
V230		X	-
V275		X	
VT210	X	•	
VT230		X	
VT275		Х	

TABLE SYMBOL								
X	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank			
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition			





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes