

技術シート：

# MOWER (COMPACT MACHINES)



## 諸元

- Cut grass up and small branches.
- Equipped with hammers.
- Front protection chains.
- Floating deck.

[The 3D picture at the top of this page is the reference MV 1500 - 52728002].

## お客様のメリット

- Must-have attachment for parks and gardens maintenance.
- Efficient work, cuts grass and small branches in one shot.
- Equipped with a floating deck to work on rough terrain with ease.
- Equipped with chains on the front to minimize projections.

重量		MF 1600 SK	MF 1900 SK	MV 1500
重量 (kg)		480	530	268
仕様				
全高 (mm)	h17	940	940	633
全長 (mm)	l1	1230	1230	999
幅 (mm)		1818	2122	1664
ワーキングパラメーター				
機械設備				
サイドシフト		いいえ	いいえ	いいえ
作業幅 (mm)		1608	1912	1530
最低油圧要件 (l/min)		75	75	42
最大油圧要件 (l/min)		125	125	120
ブレード数		24	28	24
最大切断径 (mm)		40	40	30
最大切断高さ (mm)		300	300	300
ブレードタイプ		Hammer blade	Hammer blade	Hammer blade
アタッチメント用他 データ				
E-RECO		いいえ	いいえ	いいえ
接続システム		ユニバーサル・クイック・アタッチメント	ユニバーサル・クイック・アタッチメント	-

マシンの互換性	MF 1600 SK	MF 1900 SK	MV 1500
All-Tach@	52845078	52845079	52728002
4点キャリッジ	-	-	52741076
欧州キャリッジ	-	-	52741075
2100V	X	-	-
2100VT	X	-	-
2300V	-	X	-
2300VT	-	X	-
2750V	-	X	-
2750VT	-	X	-
GCT 3-14	-	-	X
GCT 3-14	-	-	X
GCT 3-14+	-	-	X
GCT 3-14+	-	-	X
ULM 412 H	-	-	X
ULM 412 H	-	-	X
ULM 415 H	-	-	X
ULM 415 H	-	-	X
V210	X	-	-
V230	-	X	-
V275	-	X	-
VT210	X	-	-
VT230	-	X	-
VT275	-	X	-

記号の表					
	前処理が不要		油圧ライン		タンクへの油圧リターン
	電気要素		プラットフォーム要素		タイヤクランプ、シリンダークランプ要素



本社ビル

B.P. 249 - 430 rue de l'Aubinière オービニエール通り  
44150 Ancenis Cedex - France

電話 +33 (0)2 40 09 10 11 - ファックス +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



本書では、マニトウ製品の構成バージョンやオプションについて説明していますが、機器によって異なる場合があります。このパンフレットで紹介されている機器は、バージョンによってシリーズの一部であったり、オプションであったり、あるいは利用できない場合があります。Manitouは、いつでも予告なしに、記載・表現されている仕様を変更する権利を有します。提供された仕様はメーカーを拘束するものではありません。詳細につきましては、マニトウの代理店にお問い合わせください。本資料は、契約上の拘束力を有するものではありません。製品の提示は、契約上の拘束力はありません。仕様のリストは無尽蔵です。ロゴおよび会社のビジュアル・アイデンティティはManitouが所有しており、許可なく使用することはできません。すべての権利はマニトウに帰属します。このパンフレットに掲載されている写真や図は、相談や情報提供を目的としています。

MANITOU BF SA - 取締役会を有する有限会社・株式資本。39 668 399 ユーロ - 857 802 508 RCS Nantes