Technical sheet:

## FLOATING FORK CARRIAGE WITH SIDE SHIFT (MRT)



## **Customer benefits**

- Floating fork carriage with hydraulic side shift for an efficient load placement.
- Load backrest for a higher load stability.

## **Technical characteristics**

- Hydraulic line required to allow fork movement form the cab.
- Pin type forks.
- Bolt-on load backrest for a better longevity.

[The 3D picture at the top of this page is the reference TFF 1030 TDL  $5\,T$  - 924864].



		1 20A 1102 1 01111 2 A 11111 2 1 2 2 2 1 1 1 (11112 ) oleated on may 2, 202 1 at 3.02.0 1 mm or o
Technical characteristics		TFF 1030 TDL 5 T
Distance to center of gravity (mm)		367
Capacities		
Capacity (kg)		5000
Weight		
Overall weight (kg)		625
Weight and dimensions		
Overall height (mm)	h17	1481
Overall length (mm)	l1	1672
Width (mm)		1128
Working Parameters		
Machine Equipment		<b>号</b> 导
Side shift (mm)		100
Fork spread minimum (mm)	b5	410
Fork spread maximum (mm)	b5	1028
Available fork dimensions		
125 x 50 x 1200		924864

March to a comment that	
Machines compatibility	TFF 1030 TDL 5 T
MRT 1645 75	x
MRT 1645 115	x
MRT 1845 75	X
MRT 1845 115	x
MRT 2145 115	х
MRT 2260	х
MRT 2260 e	x
MRT 2545 115	х
MRT 2570	х
MRT 2660	х
MRT 2660 e	х
MRT 3060	х
MRT 3570	х
MRT 3570 ES	х
MRT-X 1645	x
MRT-X 1845	x
MRT-X 2145	x
MRT-X 2260	х
MRT-X 2545	х
MRT-X 2570	х
MRT-X 2660	x
MRT-X 3060	x
MRT-X 3570	x
MRT-X 3570 ES	х

TABLE SYMBOL	ABLE SYMBOL						
X	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank		
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition		





## **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes