

Technical sheet :

# **FLOATING FORKS CARRIAGE (MLT - MT)**

---



---

## **Customer benefits**

- Solution adapted to uneven ground: floating forks + leveling.

## **Technical characteristics**

- Load backrest standard.







- Fork leveling.

[The 3D picture at the top of this page is the reference TFF 35 MT (a) - 654093].

 **ATTACHMENTS**

| Capacities                 |    | TFF 35 MT (UK) | TFF 75 MT |
|----------------------------|----|----------------|-----------|
| Capacity (kg)              |    | 3500           | 7500      |
| Weight and dimensions      |    |                |           |
| Width (mm)                 |    | 1140           | 1495      |
| Working Parameters         |    |                |           |
| Required machine equipment |    | ✕              | ✕         |
| Maximum forks spread (mm)  | b5 | 1040           | 1430      |
| Available fork dimensions  |    |                |           |
| 100 x 50 x 1200            |    | 788793         |           |
| 200 x 60 x 1200            |    |                | 528083    |
| 200 x 60 x 1500            |    |                | 578154    |

| Machines compatibility         | TFF 35 MT (UK) | TFF 75 MT |
|--------------------------------|----------------|-----------|
| Reference number               | -              | 504280    |
| MLT 850-145 V+                 | -              | X         |
| MLT 961-160 V+ L               | -              | X         |
| MLFX 850-145 V+                | -              | X         |
| MLFX 961-160 V+ L              | -              | X         |
| MT 733 Easy <b>OLD</b>         | X              | -         |
| MT 933 Easy <b>OLD</b>         | X              | -         |
| MT 1033 easy <b>OLD</b>        | X              | -         |
| MT 1135 easy ST5 <b>OLD</b>    | X              | -         |
| MT 1135 H easy ST5 <b>OLD</b>  | X              | -         |
| MT 1135 HA Easy ST5 <b>OLD</b> | X              | -         |
| MT 1135 ST5 <b>OLD</b>         | X              | -         |
| MT 1335 <b>OLD</b>             | X              | -         |
| MT 1335 easy ST5 <b>OLD</b>    | X              | -         |
| MT 1335 H easy ST5 <b>OLD</b>  | X              | -         |
| MT 1335 HA easy ST5 <b>OLD</b> | X              | -         |
| MT-FX 733 <b>OLD</b>           | X              | -         |
| MT-FX 1033 <b>OLD</b>          | X              | -         |

| TABLE SYMBOL  |                            |   |                         |   |   |
|---|----------------------------|---|-------------------------|---|---|
|  | No predisposition required |  | Hydraulic line          |  | Return piping to hydraulic oil tank           |
|  | Electric predisposition    |  | Platform predisposition |  | Tyre handler, cylinder handler predisposition |



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes