

Ficha técnica :

# FORESTRY AND STONE MULCHER





## Beneficios para el cliente

- **Versatility:** forestry mulcher capable of crushing stones.
  - Land clearing and soil preparation.
  - Shredding heavy vegetation / overgrowth.
  - Forest road creation & maintenance.
- **Performance:**
  - Adjustable hood to facilitate mulching capacity in thick vegetation in the open position and to refine the mulching and limit forward projections in the closed position.
  - Adjustable brush guard to guide and facilitate the penetration of vegetation into the mulcher.
  - Equipped with inner cover knives, increasing productivity.
- **Security :** Protection chains at the rear to limit projections.
- **Maintenance :** Easy and quick teeth replacement.







## Características técnicas

- 60 cm<sup>3</sup> variable displacement hydraulic piston motor.
- Transmission via 4 XPB V-belts.
- Working pressure control gauge. It indicates if the rotor is blocked (P=210 bars) and to regulate its forward speed if necessary.
- Anti-wear steel shredding chamber with 3 rows of inner cover knives.
- Rotor equipped with quick attach fixed hammers.
- Hydraulic block with pressure relief valve and 12V diverter valve.
- Adjustable skids.
- Hydraulically adjustable hood with 2 rows of inner cover knives.
- Manual adjustment of the brush guard (4 positions).

[The 3D picture at the top of this page is the reference M 1950 SK - 52845080]

| Weight                                 |     | M 1800 SK   | M 1950 SK   |
|--|-----|---|---|
| Peso (kg)                              |     | 820   | 880   |
| Peso y dimensión                       |     |   |   |
| Altura total (mm)                      | h17 | 1149  | 1149  |
| Longitud total (mm)                    | l1  | 1025  | 1025  |
| Anchura (mm)                           |     | 1775  | 1955  |
| Parámetros de trabajo                  |     |   |   |
| Equipamiento de máquina                |     |  |  |
| Hood type                              |     | Hydraulic   | Hydraulic   |
| Brush guard                            |     | manual  | manual  |
| Working width (mm)                     |     | 1500  | 1680  |
| Minimum hydraulic requirements (l/min) |     | 60  | 60  |
| Maximum hydraulic requirements (l/min) |     | 130   | 130   |
| Number of blade                        |     | 32  | 36  |
| Maximum tree diameter (mm)             |     | 150   | 150   |
| Blade type                             |     | Forestry and stone  | Forestry and stone  |
| Otros datos para accesorios            |     |   |   |
| Connection system                      |     | Universal Quick-attach  | Universal Quick-attach  |
| E-RECO                                 |     | No  | No  |

| Compatibilidad de la máquina | M 1800 SK | M 1950 SK |
|------------------------------|-----------|-----------|
| All-Tach®                    | 52830830  | 52845080  |
| 1650R                        | X         | -         |
| 1650RT                       | X         | -         |
| 2100V                        | -         | X         |
| 2100VT                       | -         | X         |
| 2300V                        | -         | X         |
| 2300VT                       | -         | X         |
| 2750V                        | -         | X         |
| 2750VT                       | -         | X         |
| R165                         | X         | -         |
| RT165                        | X         | -         |
| V210                         | -         | X         |
| V230                         | -         | X         |
| V275                         | -         | X         |
| VT210                        | -         | X         |
| VT230                        | -         | X         |
| VT275                        | -         | X         |

| TABLA DE SÍMBOLOS   |                               |   |                                 |   |  |
|---|-------------------------------|---|---------------------------------|---|--|
|  | No se requiere predisposición |  | Línea hidráulica                |  | Retomo al depósito de aceite hidráulico                |
|  | Predisposición eléctrica      |  | Predisposición de la plataforma |  | Predisposición manipulador de neumáticos, de cilindros |



**Oficina Central**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - Francia

Tel.: 00 33 (0)2 40 09 10 11 - Fax: 00 33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



Esta publicación describe las versiones y posibilidades de configuración de los productos Manitou que puedan diferir en equipamiento. Los equipamientos presentados en este folleto pueden ser de serie, opcionales o no estar disponibles en algunas versiones. Manitou se reserva el derecho, en cualquier momento y sin previo aviso, de modificar las especificaciones descritas y representadas. Las especificaciones aportadas no comprometen al fabricante. Para más información, póngase en contacto con su concesionario Manitou. Documento no contractual. Presentación de los productos no contractual. Lista de especificaciones no exhaustiva. Los logos y la identidad visual de la empresa son propiedad de Manitou y no pueden ser utilizados sin autorización. Todos los derechos reservados. Las fotos y los esquemas contenidos en este folleto se ofrecen para consulta y a título indicativo solamente.

Manitou BF SA - Sociedad anónima con Consejo de Administración - Capital social: 39 668 399 euros - 857 802 508 RCS Nantes