Technical sheet:

## **FORK BALE COTTON**



## **Customer benefits**

- Simple and efficient solution for handling cotton bales.
- Handling up to 1 cotton bale (equivalent to 2-3 t / 4410-6615 lb).
- Optimized upholding thanks to its 5 tines.
- Safe transport: tines not bolted on the carriage and placed in a dedicated space.

## **Technical characteristics**

- Capacity of 5000 kg / 11025 lb.
- 2 tines, Ø 50 mm / 2 in, working length 2000 mm / 79 in.
- 3 tines, Ø 50 mm / 2 in, working length 2300 mm / 91 in.
- Removable tines (easy to change, to ship and to store during the off season).

[The 3D picture at the top of this page is the reference FBC 5/5000-52775361].



Technical characteristics         FBC 5 / 5000           Distance to center of gravity (mm)         535           Capacities         Capacity (kg)         5000           Weight         Overall weight (kg)         388           Weight and dimensions         Overall height (mm)         h17         1072           Overall length (mm)         11         2477           Width (mm)         1516           Working Parameters         Required machine equipment         Teeth / Fingers         2 / 3           Tines length (mm)         2 / 3			
Capacities         5000           Weight         5000           Overall weight (kg)         388           Weight and dimensions         1072           Overall height (mm)         11         2477           Width (mm)         1516           Working Parameters         Required machine equipment         X           Teeth / Fingers         2/3	Technical characteristics		FBC 5 / 5000
Capacity (kg)         5000           Weight         0           Overall weight (kg)         388           Weight and dimensions         0           Overall height (mm)         h17         1072           Overall length (mm)         11         2477           Width (mm)         1516           Working Parameters         8           Required machine equipment         X           Teeth / Fingers         2 / 3	Distance to center of gravity (mm)		535
Weight         0verall weight (kg)         388           Weight and dimensions         0verall height (mm)         1072           Overall length (mm)         11         2477           Width (mm)         1516           Working Parameters         Verail length (mm)         2470           Fequired machine equipment         2470           Teeth / Fingers         2/3	Capacities		
Overall weight (kg)         388           Weight and dimensions         0           Overall height (mm)         h17         1072           Overall length (mm)         11         2477           Width (mm)         1516           Working Parameters         Required machine equipment         X           Teeth / Fingers         2/3	Capacity (kg)		5000
Weight and dimensions         1072           Overall height (mm)         117         2477           Width (mm)         1516           Working Parameters         Required machine equipment         X/3           Teeth / Fingers         2/3	Weight		
Overall height (mm)         h17         1072           Overall length (mm)         11         2477           Width (mm)         1516           Working Parameters         Fequired machine equipment         X           Teeth / Fingers         2/3	Overall weight (kg)		388
Overall length (mm)         I1         2477           Width (mm)         1516           Working Parameters	Weight and dimensions		
Width (mm) 1516  Working Parameters  Required machine equipment	Overall height (mm)	h17	1072
Working Parameters  Required machine equipment  Teeth / Fingers  2/3	Overall length (mm)	l1	2477
Required machine equipment  Teeth / Fingers 2/3	Width (mm)		1516
Teeth / Fingers 2/3	Working Parameters		
	Required machine equipment		X
Tines length (mm) 2000	Teeth / Fingers		2/3
	Tines length (mm)		2000

Machines compatibility	FBC 5 / 5000		
Reference number	52775361		
MLT 850-145 V+	х		
MLT 937-115	х		
MLT 961-160 V+ L	х		
MLT-X 850-145 V+	x		
MLT-X 961-160 V+ L	х		

TABLE SYMBOL							
×	No predisposition required	88	Hydraulic line		Retum piping to hydraulic oil tank		
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition		





## **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes