

Technical sheet :

# FORK BALE COTTON



## Technical characteristics

- Capacity of 5000 kg / 11025 lb.
- 2 tines, Ø 50 mm / 2 in, working length 2000 mm / 79 in.
- 3 tines, Ø 50 mm / 2 in, working length 2300 mm / 91 in.
- Removable tines (easy to change, to ship and to store during the off season).







[The 3D picture at the top of this page is the reference FBC 5 / 5000 - 52775361].

## Customer benefits

- Simple and efficient solution for handling cotton bales.
- Handling up to 1 cotton bale (equivalent to 2-3 t / 4410-6615 lb).
- Optimized upholding thanks to its 5 tines.
- Safe transport: tines not bolted on the carriage and placed in a dedicated space.

Technical characteristics		FBC 5 / 5000	
Distance to center of gravity (mm)		535	
Capacities			
Capacity (kg)		5000	
Weight			
Overall weight (kg)		388	
Weight and dimensions			
Overall height (mm)	h17	1072	
Overall length (mm)	l1	2477	
Width (mm)		1516	
Working Parameters			
Required machine equipment		✕	
Teeth / Fingers		2 / 3	
Times length (mm)		2000	

Machines compatibility		FBC 5 / 5000	
Reference number		52775361	
MLT 635-130 PS+ (S2)		X	
MLT 635-140 V+ (S2)		X	
MLT 738-130 PS+ (S1)		X	
MLT 742-130 PS+ (S1)		X	
MLT 742-140 V+ (S1)		X	
MLT 850-145 V+		X	
MLT 937-115 (S1)		X	
MLT 961-160 V+ L		X	
MLTX 738-130 PS+ (S1)		X	
MLTX 850-145 V+		X	
MLTX 961-160 V+ L		X	

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes