

Technical sheet :

# GENERAL PURPOSE BUCKET ESSENTIAL



## Technical characteristics

- Capacity: 400 L / 14 ft<sup>3</sup> up to 1000L / 35 ft<sup>3</sup>.
- For material density up to 2100 kg/m<sup>3</sup> / 131 lb/ft<sup>3</sup>.
- Simplified structure with straight sides.
- Integrated level indicator.
- No side strengthener.

[The 3D picture at the top of this page is the reference BGP 2000 / 800 Essential - 52688160].







## Customer benefits

- A bucket for all construction applications.
- Dedicated to heavy bulk: sand, earth, stones, gravels, etc.
- Tested at the R&D Center on high demanding applications.
- Designed and validated by Manitou.

Technical characteristics		BGP 1500 / 400 Essential	BGP 1850 / 750 Essential	BGP 2000 / 800 Essential	BGP 2300 / 900 Essential	BGP 2450 / 1000 Essential
Distance to center of gravity (mm)		417	422	425	429	434
<b>Capacities</b>						
Capacity (kg)		827	1550	1684	1955	2089
Heaped capacity (l)		394	738	802	931	995
Struck capacity (l)		311	574	622	718	766
<b>Weight</b>						
Overall weight (kg)		161	326	345	379	397
<b>Weight and dimensions</b>						
Overall height (mm)	h17	625	786	786	786	786
Overall length (mm)	l1	812	975	925	975	925
Width (mm)		1500	1850	2000	2300	2450
Depth (mm)	p5	627	817	817	817	817
<b>Working Parameters</b>						
Required machine equipment		×	×	×	×	×

Machines compatibility		BGP 1500 / 400 Essential	BGP 1850 / 750 Essential	BGP 2000 / 800 Essential	BGP 2300 / 900 Essential	BGP 2450 / 1000 Essential
Reference number		-	52690766	52688160	52690756	52658055
All-Tach®		52702290	-	-	-	-
4 point Carriage		52723638	-	-	-	-
Euro Carriage		52723639	-	-	-	-
AL530		X	-	-	-	-
GCT 3-14		X	-	-	-	-
GCT 3-14 +		X	-	-	-	-
MLA 5-50 H		X	-	-	-	-
MLT 630-115 (S1)		-	-	X	-	-
MLT 630-115 (S2)		-	-	X	-	-
MLT 630-115 V (S1)		-	-	X	-	-
MLT 630-115 V (S2)		-	-	X	-	-
MLT 630-115 V CP (S1)		-	-	X	-	-
MLT 630-115 V CP (S2)		-	-	X	-	-
MLT 635-130 PS+ (S1)		-	-	-	-	X
MLT 635-130 PS+ (S2)		-	-	-	X	X
MLT 635-140 V+ (S1)		-	-	-	-	X
MLT 635-140 V+ (S2)		-	-	-	X	X
MLT 730-115 V (S1)		-	-	X	-	-
MLT 730-115 V (S2)		-	-	X	-	-
MLT 730-115 V CP (S1)		-	-	X	-	-
MLT 730-115 V CP (S2)		-	-	X	-	-
MLT 733-115		-	-	-	-	X
MLT 733-115 (S2)		-	-	-	-	X
MLT 733-115 LSU (S1)		-	-	-	-	X
MLT 737-130 PS+ (S1)		-	-	-	-	X
MLT 738-130 PS+ (S1)		-	-	-	-	X
MLT 741-130 PS+ (S1)		-	-	-	-	X
MLT 741-140 V+ (S1)		-	-	-	-	X
MLT 742-140 V+ (S1)		-	-	-	-	X
MLT 841-145 PS+		-	-	-	-	X
MLT 937-115 (S1)		-	-	-	-	X
MLT 940-140 V+ (S1)		-	-	-	-	X
MLT 1041-145 PS+L		-	-	-	-	X
MLFX 732		-	-	-	-	X
MLFX 735 T LSU		-	-	-	-	X
MLFX 735 T LSU (70 KW)		-	-	-	-	X
MLFX 738-130 PS+ (S1)		-	-	-	-	X
MLFX 741 T LSU		-	-	-	-	X
MLFX 841 - 145 PS+		-	-	-	-	X
MLFX 1035 LT LSU		-	-	-	-	X
MLFX 1041-145 PS+L		-	-	-	-	X
MT 625 e		-	X	-	-	-
MT 625 H		-	X	-	-	-
MT 625 H Comfort		-	X	-	-	-
MT 730 H		-	-	X	-	-
MT 735 75D ST5		-	-	X	X	X
MT 930 H		-	-	X	-	-
MT 935 75D ST5		-	-	X	X	X
MT 1135 75 D		-	-	X	X	X
MT 1135		-	-	-	X	-
MT 1135 H 100D		-	-	X	X	X
MT 1335 75D ST5		-	-	X	X	X
MT 1335 100D ST5		-	-	X	X	X
MT 1335 H 75D ST5		-	-	X	X	X
MT 1335 H 100D ST5		-	-	X	X	X
MT 1335 HA 75D ST5		-	-	X	X	X
MT 1335 HA 100D ST5		-	-	X	X	X
MT 1440		-	-	-	X	X
MT 1440 e		-	-	X	X	X
MT 1440 easy ST5		-	-	X	X	X
MT 1440 ST5		-	-	X	X	X
MT 1840		-	-	-	X	-

Machines compatibility	BGP 1500 / 400 Essential	BGP 1850 / 750 Essential	BGP 2000 / 800 Essential	BGP 2300 / 900 Essential	BGP 2450 / 1000 Essential
MT 1840 e	-	-	X	X	X
MT 1840 easy ST5	-	-	X	X	X
MT 1840 ST5	-	-	X	X	X
MT-X 735	-	-	X	-	X
MT-X 1135	-	-	X	-	X
MT-X 1440	-	-	X	X	X
MT-X 1840	-	-	X	X	X
ULM 412 H	X	-	-	-	-
ULM 412 H	X	-	-	-	-
ULM 415 H	X	-	-	-	-
ULM 415 H	X	-	-	-	-
MLT 630-105 ST4 <b>OLD</b>	-	-	X	-	-
MLT 630-105 V CP ST4 <b>OLD</b>	-	-	X	-	-
MLT 630-105 V ST4 <b>OLD</b>	-	-	X	-	-
MLT 635-140 V+ ST4 <b>OLD</b>	-	-	-	-	X
MLT 730-115 V CP ST4 <b>OLD</b>	-	-	X	-	-
MLT 730-115 V ST4 <b>OLD</b>	-	-	X	-	-
MLT 733-115 ST4 <b>OLD</b>	-	-	-	-	X
MLT 737-130 PS+ ST4 <b>OLD</b>	-	-	-	-	X
MLT 741-140 V+ ST4 <b>OLD</b>	-	-	-	-	X
MLT 940-140 V+ ST4 <b>OLD</b>	-	-	-	-	X
MLT-X 737-130 PS+ (S2) <b>OLD</b>	-	-	-	-	X
MT 625 HA <b>OLD</b>	-	X	-	-	-
MT 733 Easy <b>OLD</b>	-	-	X	X	X
MT 930 HA <b>OLD</b>	-	-	X	-	-
MT 933 Easy <b>OLD</b>	-	-	X	X	X
MT 1033 easy <b>OLD</b>	-	-	X	X	X
MT 1135 easy ST5 <b>OLD</b>	-	-	X	X	X
MT 1135 H easy ST5 <b>OLD</b>	-	-	X	X	X
MT 1135 HA Easy ST5 <b>OLD</b>	-	-	X	X	X
MT 1135 ST5 <b>OLD</b>	-	-	X	X	X
MT 1335 <b>OLD</b>	-	-	X	X	X
MT 1335 easy ST5 <b>OLD</b>	-	-	X	X	X
MT 1335 H easy ST5 <b>OLD</b>	-	-	X	X	X
MT 1335 HA easy ST5 <b>OLD</b>	-	-	X	X	X
MT 1335 ST5 <b>OLD</b>	-	-	X	X	X
MT 1440 A ST4 <b>OLD</b>	-	-	X	X	-
MT 1440 A ST5 <b>OLD</b>	-	-	X	X	X
MT 1440 HA ST4 <b>OLD</b>	-	-	X	X	-
MT 1440 HA ST5 <b>OLD</b>	-	-	X	X	X
MT 1840 A ST5 S1 <b>OLD</b>	-	-	X	X	X
MT 1840 A STG4 <b>OLD</b>	-	-	X	X	-
MT 1840 HA ST4 <b>OLD</b>	-	-	X	X	X
MT 1840 HA ST5 S1 <b>OLD</b>	-	-	X	X	X
MT-X 733 <b>OLD</b>	-	-	X	X	X
MT-X 733 Mining <b>OLD</b>	-	-	-	X	-
MT-X 1033 <b>OLD</b>	-	-	X	X	X
MT-X 1033 Mining <b>OLD</b>	-	-	-	X	-
MT-X 1033 A Mining <b>OLD</b>	-	-	-	X	-
MT-X 1440 A <b>OLD</b>	-	-	X	X	X
MT-X 1840 A <b>OLD</b>	-	-	X	X	X

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



 **MANITOU**  
**HANDLING YOUR WORLD**

**Head Office**

B.P. 249 - 430 rue de l'Aubinière  
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes