

Technical sheet :

GENERAL PURPOSE BUCKET (MRT)



Technical characteristics

- Bucket dedicated to the handling of all heavy materials (< 2100 kg/m³ / 131 lb/ft³).
- Available with an optional bolt-on wear plate to operate on concrete/ asphalt floor.
- Note: rotating telehandlers are not designed for intensive loading applications or for digging applications.

Customer benefits

- Perfect for the handling of sand, gravels etc.
- Designed to suit to MRT's specific boom head position.

Technical characteristics		CBR 1000 / 2450 (a)	CBR 1000 / 2450 (b)
Distance to center of gravity (mm)		500	-
Capacities			
Capacity (kg)		2100	2100
Heaped capacity (l)		1000	1000
Weight			
Overall weight (kg)		415	441
Weight and dimensions			
Overall height (mm)	h17	802	820
Overall length (mm)	l1	890	922
Width (mm)		2450	2450
Working Parameters			
Required machine equipment		✗	✗
Other Data for Attachments			
Bolted wearplate (LDR)		-	Standard

Machines compatibility		CBR 1000 / 2450 (a)	CBR 1000 / 2450 (b)
Reference number E-RECO		921282	923967
MRT 1645 75		X	X
MRT 1645 115		X	X
MRT 1845 75		X	X
MRT 1845 115		X	X
MRT 2145 115		X	X
MRT 2260		X	X
MRT 2260 e		X	X
MRT 2545 115		X	X
MRT 2570		X	X
MRT 2660		X	X
MRT 2660 e		X	X
MRT 3060		X	X
MRT 3570		X	X
MRT 3570 ES		X	X
MRT-X 1645		X	X
MRT-X 1845		X	X
MRT-X 2145		X	X
MRT-X 2260		X	X
MRT-X 2545		X	X
MRT-X 2570		X	X
MRT-X 2660		X	X
MRT-X 3060		X	X
MRT-X 3570		X	X
MRT-X 3570 ES		X	X

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes