

Ficha técnica :

# GENERAL PURPOSE BUCKET (MRT)



## Customer benefits







- Perfect for the handling of sand, gravels etc.
- Designed to suit to MRT's specific boom head position.

## Technical characteristics

- Bucket dedicated to the handling of all heavy materials (< 2100 kg/m<sup>3</sup> / 131 lb/ft<sup>3</sup>).
- Available with an optional bolt-on wear plate to operate on concrete/ asphalt floor.
- Note: rotating telehandlers are not designed for intensive loading applications or for digging applications.

| Technical characteristics          |     | CBR 1000 / 2450 (a) | CBR 1000 / 2450 (b) |
|------------------------------------|-----|---------------------|---------------------|
| Distance to center of gravity (mm) |     | 500                 | -                   |
| <b>Capacities</b>                  |     |                     |                     |
| Capacity (kg)                      |     | 2100                | 2100                |
| Heaped capacity (l)                |     | 1000                | 1000                |
| <b>Weight</b>                      |     |                     |                     |
| Overall weight (kg)                |     | 415                 | 441                 |
| <b>Weight and dimensions</b>       |     |                     |                     |
| Overall height (mm)                | h17 | 802                 | 820                 |
| Overall length (mm)                | l1  | 890                 | 922                 |
| Width (mm)                         |     | 2450                | 2450                |
| <b>Working Parameters</b>          |     |                     |                     |
| Machine Equipment                  |     | ×                   | ×                   |
| <b>Other Data for Attachments</b>  |     |                     |                     |
| Bolted wearplate (LDR)             |     | -                   | Standard            |

| Compatibilidad de la máquina |  | CBR 1000 / 2450 (a) | CBR 1000 / 2450 (b) |
|------------------------------|--|---------------------|---------------------|
| Reference number E-RECO      |  | 921282              | 923967              |
| MRT 1645 75                  |  | X                   | X                   |
| MRT 1645 115                 |  | X                   | X                   |
| MRT 1845 75                  |  | X                   | X                   |
| MRT 1845 115                 |  | X                   | X                   |
| MRT 2145 115                 |  | X                   | X                   |
| MRT 2260                     |  | X                   | X                   |
| MRT 2260 e                   |  | X                   | X                   |
| MRT 2545 115                 |  | X                   | X                   |
| MRT 2570                     |  | X                   | X                   |
| MRT 2660                     |  | X                   | X                   |
| MRT 2660 e                   |  | X                   | X                   |
| MRT 3060                     |  | X                   | X                   |
| MRT 3570                     |  | X                   | X                   |
| MRT 3570 ES                  |  | X                   | X                   |
| MRT-X 1645                   |  | X                   | X                   |
| MRT-X 1845                   |  | X                   | X                   |
| MRT-X 2145                   |  | X                   | X                   |
| MRT-X 2260                   |  | X                   | X                   |
| MRT-X 2545                   |  | X                   | X                   |
| MRT-X 2570                   |  | X                   | X                   |
| MRT-X 2660                   |  | X                   | X                   |
| MRT-X 3060                   |  | X                   | X                   |
| MRT-X 3570                   |  | X                   | X                   |
| MRT-X 3570 ES                |  | X                   | X                   |

| TABLA DE SÍMBOLOS   |                               |   |                                 |   |  |
|---|-------------------------------|---|---------------------------------|---|--|
|  | No se requiere predisposición |  | Línea hidráulica                |  | Retorno al depósito de aceite hidráulico               |
|  | Predisposición eléctrica      |  | Predisposición de la plataforma |  | Predisposición manipulador de neumáticos, de cilindros |



**Oficina Central**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - Francia

Tel.: 00 33 (0)2 40 09 10 11 - Fax: 00 33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



Esta publicación describe las versiones y posibilidades de configuración de los productos Manitou que puedan diferir en equipamiento. Los equipamientos presentados en este folleto pueden ser de serie, opcionales o no estar disponibles en algunas versiones. Manitou se reserva el derecho, en cualquier momento y sin previo aviso, de modificar las especificaciones descritas y representadas. Las especificaciones aportadas no comprometen al fabricante. Para más información, póngase en contacto con su concesionario Manitou. Documento no contractual. Presentación de los productos no contractual. Lista de especificaciones no exhaustiva. Los logos y la identidad visual de la empresa son propiedad de Manitou y no pueden ser utilizados sin autorización. Todos los derechos reservados. Las fotos y los esquemas contenidos en este folleto se ofrecen para consulta y a título indicativo solamente.

Manitou BF SA - Sociedad anónima con Consejo de Administración - Capital social: 39 668 399 euros - 857 802 508 RCS Nantes