

技術シート：

GRADER BLADE WITH SIDE SHIFT



諸元

- 3 hydraulic functions to allow great precision on a job site: rotation right/left, side shift, horizontal tilting.
- All movements are proportional for greatest precision.
- Robust design with central shock absorber to resist to the stress received during the leveling work and to maintain good forward speed.
- Front wheels are completely free and pivoting 360° to provide additional stability.
- Can be combined with all laser systems of any brand, both 2D and 3D for more precision.
- The grader blades are already set up to accommodate the two poles for the receivers.





[The 3D picture at the top of this page is the reference BLG 2400 SK - 52832868]

お客様のメリット

- Dedicated to moving and grading surfaces (such as dirt, gravel, sand and any other material) with precision.
- Designed to be used by asphalt, landscaping, and concrete flatwork contractors.
- Ideal for grading roads, parkings lots, sports facilities, and squares.

重量		BLG 2100 SK	BLG 2400 SK
重量 (kg)		765	781
仕様			
全高 (mm)	h17	1441	1441
全長 (mm)	l1	2426	2426
幅 (mm)		2133	2400
ワーキングパラメーター			
機械設備			
角度のあるパス (mm)		1720	1924
傾き +/- (°)		30	30
サイドシフト		はい	はい
サイドシフトタイプ		油圧	油圧
最大アウトリーチ・サイドシフト (mm)		400	400
左アングル (°)		35	35
アングル・ライト (°)		35	35
最低油圧要件 (l/min)		20	20
最大油圧要件 (l/min)		80	80
アタッチメント用他 データ			
E-RECO		いいえ	いいえ
接続システム		ユニバーサル・クイック・アタッチメント	ユニバーサル・クイック・アタッチメント

マシンの互換性	BLG 2100 SK	BLG 2400 SK
All-Tach®	52832867	52832868
2100V	X	-
2100VT	X	-
2300V	-	X
2300VT	-	X
2750V	-	X
2750VT	-	X
V210	X	-
V230	-	X
V275	-	X
VT210	X	-
VT230	-	X
VT275	-	X

記号の表					
	前処理が不要		油圧ライン		タンクへの油圧リターン
	電気要素		プラットフォーム要素		タイヤクランプ、シリンダークランプ要素



本社ビル

B.P. 249 - 430 rue de l'Aubinière オービニエール通り
44150 Ancenis Cedex - France

電話 +33 (0)2 40 09 10 11 - ファックス +33 (0)2 40 09 10 97

www.manitou.com



本書では、マニトウ製品の構成バージョンやオプションについて説明していますが、機器によって異なる場合があります。このパンフレットで紹介されている機器は、バージョンによってシリーズの一部であったり、オプションであったり、あるいは利用できない場合があります。Manitouは、いつでも予告なしに、記載・表現されている仕様を変更する権利を有します。提供された仕様はメーカーを拘束するものではありません。詳細につきましては、マニトウの代理店にお問い合わせください。本資料は、契約上の拘束力を有するものではありません。製品の提示は、契約上の拘束力はありません。仕様のリストは無尽蔵です。ロゴおよび会社のビジュアル・アイデンティティはManitouが所有しており、許可なく使用することはできません。すべての権利はマニトウに帰属します。このパンフレットに掲載されている写真や図は、相談や情報提供を目的としています。

MANITOU BF SA - 取締役会を有する有限会社・株式資本。39 668 399 ユーロ - 857 802 508 RCS Nantes