Technical sheet:

## **GRAIN PUSHER**



## **Technical characteristics**

- Heavy duty design with round surfaces to prevent grain trapping.
- Polyurethane cutting edge to protect surfaces that could be damaged by the attachment.

[The 3D picture at the top of this page is the reference BLGP 2320 / 3900 - 52812920].

## **Customer benefits**

- Must have attachment to push the grain.
- · Facility space saving.
- Time saving for the operator.



Weight		BLGP 2320 / 3900
Overall weight (kg)		439
Weight and dimensions		
Overall height (mm)	h17	946
Overall length (mm)	l1	3942
Width (mm)		2320
Working Parameters		
Required machine equipment		X

Machines compatibility	BLGP 2320 / 3900
Reference number	52812920
MLT 630-115 (S2)	x
MLT 630-115 V (S2)	x
MLT 630-115 V CP (S2)	x
MLT 635-130 PS+ (S1)	x
MLT 635-130 PS+ (S2)	x
MLT 635-140 V+ (S1)	x
MLT 635-140 V+ (S2)	x
MLT 730-115 V (S2)	x
MLT 730-115 V CP (S2)	x
MLT 733-115	x
MLT 733-115 (S2)	X
MLT 733-115 LSU (S1)	х
MLT 737-130 PS+ (S1)	х
MLT 738-130 PS+ (S1)	X
MLT 741-130 PS+ (S1)	х
MLT 741-140 V+ (S1)	X
MLT 742-130 PS+ (S1)	х
MLT 742-140 V+ (S1)	X
MLT 841-145 PS+	х
MLT 850-145 V+	X
MLT 937-115 (S1)	X
MLT-X 732	х
MLT-X 735 T LSU	х
MLT-X 735 T LSU (70 KW)	х
MLT-X 738-130 PS+ (S1)	X
MLT-X 841 - 145 PS+	х
MLT-X 850-145 V+	х
MLT 635-130 PS+ ST4 <b>OLD</b>	X
MLT 635-140 V+ ST4 <b>OLD</b>	X
MLT 733-115 LSU ST4 <b>OLD</b>	X
MLT 733-115 ST4 <b>OLD</b>	х
MLT 737-130 PS+ ST4 <b>OLD</b>	Х
MLT-X 737-130 PS+ <b>OLD</b>	X
MLT-X 737-130 PS+ (S2) OLD	х
MLT-X 741-140 V+ S1 OLD	X

TABLE SYMBOL								
×	No predisposition required	88	Hydraulic line		Retum piping to hydraulic oil tank			
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition			





## **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes