

Technical sheet :

# HEAVY DUTY FRAME MOUNTED HOOK

---



## Customer benefits

- Efficient and heavy duty suspended load solution.
- Directly hitched on carriage for secured application.
- Very compact attachment that preserves machine stability.

## Technical characteristics

- Suspended load capacity up to 25000 kg / 55125 lb.
- Safety: Homologated swivel self locking hook.

[The 3D picture at the top of this page is the reference PC 9 T - 939970].

 **ATTACHMENTS**

| Technical characteristics          |     | JH 16000 | JH 20000 | PC 9 T | PC 13 T | PC 18 T | PC 25 T |
|------------------------------------|-----|----------|----------|--------|---------|---------|---------|
| Distance to center of gravity (mm) |     | 385      | 401      | 186    | 391     | 398     | 398     |
| Capacities                         |     |          |          |        |         |         |         |
| Capacity (kg)                      |     | 16000    | 20000    | 9000   | 13000   | 18000   | 25000   |
| Weight                             |     |          |          |        |         |         |         |
| Overall weight (kg)                |     | 340      | 355      | 129    | 305     | 340     | 460     |
| Dimensions                         |     |          |          |        |         |         |         |
| Max. outreach (mm)                 |     | 700      | 700      | 260    | 700     | 700     | 700     |
| Weight and dimensions              |     |          |          |        |         |         |         |
| Overall height (mm)                | h17 | 1068     | 1208     | 960    | 1055    | 1208    | 1258    |
| Overall length (mm)                | l1  | 943      | 943      | 425    | 945     | 943     | 985     |
| Width (mm)                         |     | 830      | 830      | 815    | 800     | 830     | 850     |
| Working Parameters                 |     |          |          |        |         |         |         |
| Machine Equipment                  |     | ×        | ×        | ×      | ×       | ×       | ×       |

| Machines compatibility               | JH 16000 | JH 20000 | PC 9 T | PC 13 T  | PC 18 T  | PC 25 T  |
|--------------------------------------|----------|----------|--------|----------|----------|----------|
| Reference number E-RECO              | 52702450 | 52702460 | 939970 | 53008009 | 53011879 | 53008289 |
| MHT 790 Mining ST5                   | -        | -        | X      | -        | -        | -        |
| MHT 790 ST5                          | -        | -        | X      | -        | -        | -        |
| MHT 10135 ST5                        | X        | -        | -      | -        | -        | -        |
| MHT 10160 ST5                        | X        | -        | -      | -        | -        | -        |
| MHT 10200 ST5                        | -        | X        | -      | -        | -        | -        |
| MHT 11250 Mining ST5                 | -        | -        | -      | -        | -        | X        |
| MHT 11250 ST5                        | -        | -        | -      | -        | -        | X        |
| MHT 12330                            | -        | -        | -      | -        | -        | X        |
| MHT-X 790 Mining ST3A                | -        | -        | X      | -        | -        | -        |
| MHT-X 790 ST3A                       | -        | -        | X      | -        | -        | -        |
| MHT-X 10135 ST3A                     | X        | -        | -      | -        | -        | -        |
| MHT-X 10160 ST3A                     | X        | -        | -      | -        | -        | -        |
| MHT-X 10200 ST3A                     | -        | X        | -      | -        | -        | -        |
| MHT-X 11250 Mining                   | -        | -        | -      | -        | -        | X        |
| MHT-X 11250 ST3A                     | -        | -        | -      | -        | -        | X        |
| MHT-X 12330                          | -        | -        | -      | -        | -        | X        |
| MRT 2260                             | -        | -        | X      | -        | -        | -        |
| MRT 2260 e                           | -        | -        | X      | -        | -        | -        |
| MRT 2570                             | -        | -        | X      | -        | -        | -        |
| MRT 2660                             | -        | -        | X      | -        | -        | -        |
| MRT 2660 e                           | -        | -        | X      | -        | -        | -        |
| MRT 3060                             | -        | -        | X      | -        | -        | -        |
| MRT 3570                             | -        | -        | X      | -        | -        | -        |
| MRT 3570 ES                          | -        | -        | X      | -        | -        | -        |
| MRT-X 2260                           | -        | -        | X      | -        | -        | -        |
| MRT-X 2570                           | -        | -        | X      | -        | -        | -        |
| MRT-X 2660                           | -        | -        | X      | -        | -        | -        |
| MRT-X 3060                           | -        | -        | X      | -        | -        | -        |
| MRT-X 3570                           | -        | -        | X      | -        | -        | -        |
| MRT-X 3570 ES                        | -        | -        | X      | -        | -        | -        |
| MHT 790 <b>OLD</b>                   | -        | -        | X      | -        | -        | -        |
| MHT 10130 <b>OLD</b>                 | -        | -        | -      | X        | -        | -        |
| MHT 10180 <b>OLD</b>                 | -        | -        | -      | -        | X        | -        |
| MHT 10230 <b>OLD</b>                 | -        | -        | -      | -        | -        | X        |
| MHT-X 790 <b>OLD</b>                 | -        | -        | X      | -        | -        | -        |
| MHT-X 790 Mining <b>OLD</b>          | -        | -        | X      | -        | -        | -        |
| MRT 2470 Privilege Plus <b>OLD</b>   | -        | -        | X      | -        | -        | -        |
| MRT-X 2470 Privilege Plus <b>OLD</b> | -        | -        | X      | -        | -        | -        |

| TABLE SYMBOL  |                            |   |                         |   |   |
|---|----------------------------|---|-------------------------|---|---|
|  | No predisposition required |  | Hydraulic line          |  | Return piping to hydraulic oil tank           |
|  | Electric predisposition    |  | Platform predisposition |  | Tyre handler, cylinder handler predisposition |



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes