Technical sheet:

## HEAVY DUTY FRAME MOUNTED HOOK



## **Technical characteristics**

- Suspended load capacity up to 25000 kg / 55125 lb.
- · Safety: Homologated swivel self locking hook.

[The 3D picture at the top of this page is the reference PC 9 T - 939970].

## **Customer benefits**

- Efficient and heavy duty suspended load solution.
- Directly hitched on carriage for secured application.
- Very compact attachment that preserves machine stability.



Technical characteristics		JH 16000	JH 20000	JH 36000	PC 9 T	PC 13 T	PC 18 T	PC 25 T
Distance to center of gravity (mm)		385	401	455	186	391	398	398
Capacities								
Capacity (kg)		16000	20000	36000	9000	13000	18000	25000
Weight								
Overall weight (kg)		340	355	970	129	305	340	460
Dimensions								
Maximum outreach (mm)		700	700	905	260	700	700	700
Weight and dimensions								
Overall height (mm)	h17	1068	1208	1468	960	1055	1208	1258
Overall length (mm)	I1	943	943	1817	425	945	943	985
Width (mm)		830	830	1170	815	800	830	850
Working Parameters								
Required machine equipment		X	X	×	X	X	X	X

Machines compatibility	JH 16000	JH 20000	JH 36000	PC 9 T	PC 13 T	PC 18 T	PC 25 T
Reference number E-RECO	52702450	52702460	52623274	939970	53008009	53011879	53008289
MHT 790	-			Х	-		-
MHT 790 Mining ST5				х			
MHT 790 ST5	-			Х	-		
MHT 10130					Х		-
MHT 10135 ST5	Х						
MHT 10160 ST5	Х						-
MHT 10180	-			-	-	Х	-
MHT 10200 ST5		Х					-
MHT 10230	-			-	-		X
MHT 11250 Mining ST5							X
MHT 11250 ST5					-		Х
MHT 12330			Х		-		Х
MHT-X 790 Mining ST3A				Х			
MHT-X 790 ST3A				Х			
MHT-X 10135 ST3A	Х						
MHT-X 10160 ST3A	Х						-
MHT-X 10200 ST3A	-	X		-	-		-
MHT-X 11250 Mining					-		Х
MHT-X 11250 ST3A					-		Х
MHT-X 12330			Х		-		Х
MRT 2260				Х	-		
MRT 2260 e				Х	-		-
MRT 2570				Х	-		
MRT 2660				Х	-		-
MRT 2660 e				Х	-		
MRT 3060				Х	-		-
MRT 3570				Х	-		
MRT 3570 ES				Х	-		-
MRT-X 2260	-			Х	-		-
MRT-X 2470 Privilege Plus				Х			-
MRT-X 2570	-			Х	-		-
MRT-X 2660				Х			-
MRT-X 3060				Х			-
MRT-X 3570				Х	-		-
MRT-X 3570 ES				Х	-		-
MHT-X 790 OLD	-		-	Х	-		-
MHT-X 790 Mining OLD				X			
MRT 2470 Privilege Plus OLD	-	-		Х	-	-	-

TABLE SYMBOL				
×	No predisposition required	88	Hydraulic line	Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition	Tyre handler, cylinder handler predisposition





## **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes