Technical sheet:

HIGH PRESSURE CLEANER



Technical characteristics

- Tank capacity of 600 L / 21 ft3.
- Hydraulic powered water pump.
- Pressure regulation from 10 bars / 145 psi to 200 bars / 2901 psi.
- · Manometer on standard.
- Nozzle spray with a 40 m / 131 ft hose.

[The 3D picture at the top of this page is the reference VHPC 600 - 790335].

Customer benefits

- Powerful and efficient cleaning.
- 45 min of autonomy at 200 bar / 2901 psi.
- Suitable for all types of cleaning applications and maintenances works.
- · Easy to hitch with a standard forks.



Weight		VHPC 600
Overall weight (kg)		240
Weight and dimensions		
Overall height (mm)	h17	1500
Overall length (mm)	I1	1200
Width (mm)		1450
Cable length (mm)		40000
Working Parameters		
Required machine equipment		₽₽ ₹ <u>6</u>

Reference number	Machines compatibility	VHPC 600
MLT 655-130 PS+ (S2) MLT 655-140 V+ (S1) X MLT 735-140 V+ (S1) X MLT 735-130 PS+ (S1) X MLT 735-130 PS+ (S1) X MLT 742-130 PS+ (S1) X MLT 742-130 PS+ (S1) X MLT 742-130 PS+ (S1) X MLT 940-140 V+ (S1) X MLT 940-140 V+ (S2) X MLT 1041-145 PS-1 X MLT 1041-145 PS-1 X MLEX 735-75 H X MLEX 735-75 LSU MLE	Reference number	790335
MLT 635-140 V+ (S1)	MLT 635-130 PS+ (S1)	χ
MLT 635-140 V+ (SZ) MLT 782-130 PS+ (S1) X MLT 782-130 PS+ (S1) X MLT 782-140 V+ (S1) X MLT 841-145 PS+ X MLT 840-140 V+ (S2) X MLT 961-160 V+ L MLT 961-160 V+ L MLT 842-145 PS+ X MLT 841-145 PS+ X MLT 841-145 PS+ X MLT 841-145 PS+ X MLT 961-160 V+ L MLT 841-145 PS+ X MLT 841-160 V+ MLT 841-1	MLT 635-130 PS+ (S2)	χ
MLT 738-130 PSr (S1) MLT 742-100 PSr (S1) X MLT 841-145 PSr MLT 841-145 PSr MLT 940-140 Vr (S2) X MLT 950-150 Vr L MLT 940-140 Vr ST X MLT 950-150 Vr L MLT 940-140 Vr ST X MLT 950-150 Vr L MLT 950	MLT 635-140 V+ (S1)	Х
MLT 742-140 Ps (S1)	MLT 635-140 V+ (S2)	Х
MLT 742-140 V+ (S1) MLT 841-145 PS+ X MLT 940-140 V+ (S2) X MLT 940-140 V+ (S2) X MLT 961-160 V+ L X MLT 851-150 Y+ X MLT 1041-145 PS+ L X MLT 735 T L SU X MLT X 381 30 PS+ (S1) X MLT X 381 1-145 PS+ X MLT X 381 30 PS+ (S1) X MLT X 381 1-145 PS+ X MLT 380 1-160 V+ L X MLT 380 1-160 V+ L X MLT 380 1-160 V+ L X MLT 380 1-160 V+ ST4 0 ID MLT 380 1-105 Y ST4 0 ID MLT 380 1-105 Y ST4 0 ID MLT 380 1-105 Y ST4 0 ID MLT 730 1-15 Y ST4 0 ID MLT 737 1-15 Y ST4 0 ID M	MLT 738-130 PS+ (S1)	X
MLT 841-145 PS+ MLT 860-145 V+ MLT 961-160 V+ L MLT 1011-145 PS+L MLT 801-160 V+ L MLT 801-160 V+ L MLT 801-160 V+ L MLT 801-160 V+ ST4 0LD MLT 630-105 V C PST4 0LD MLT 630-105 V C PST4 0LD MLT 630-105 V C PST4 0LD MLT 730-115 V C PST4 0LD MLT 730-115 V C PST4 0LD MLT 730-115 V C PST4 0LD MLT 737-130 PS+ ST4 0LD MLT 737-130 PS+ ST4 0LD MLT 737-130 PS+ ST4 0LD MLT 90-140 V+	MLT 742-130 PS+ (S1)	Х
MLT 850-145 V+ MLT 940-140 V+ (52) MLT 940-140 V+ (52) MLT 940-140 V+ (52) MLT WE	MLT 742-140 V+ (S1)	X
MIT 940-140 V+ (\$2) MIT 961-160 V+ L X MIT 1041-145 P8+L X MITX 257-57 H X MITX 735-T LSU X MITX 735-T SU X MITX 850-145 V+ X MITX 850-145 V+ X MITX 850-145 V+ X MITX 1041-145 P8+L X MITX 1041-145 P8+L X MIT 630-105 V CP ST4 CID X MIT 630-105 V CP ST4 CID X MIT 730-115 V CP ST4 CID X MIT 730-115 V ST4 CID X MIT 730-115 V ST4 CID X MIT 731-130 P8+ ST4 CID X MIT 731-140 V+ ST4 CID X MIT 731-140 V+ ST4 CID X MIT 730-15 P8+ T4 CID X MIT 730-15 P8+ CID X MIT 730-15 P8+ CID X MIT 1040-145 P8+L CID X MIT 1040-145 P8+L CID X MITX 940-140 V+ ST4 CID X MITX 940-140	MLT 841-145 PS+	Х
MLT 961-160 V+ L MLT 1011-145 PS+L MLTX 1025-75 H MLTX 738-130 PS+ (S1) MLTX 738-130 PS+ (S1) MLTX 731 T LSU MLTX 731 T LSU X MLTX 741 T LSU X MLTX 850-145 V+ X MLTX 850-145 V+ X MLTX 850-145 V+ X MLTX 961-160 V+ L X MLTX 961-160 V+ L X MLTX 961-160 V+ L X MLTX 961-160 V+ C X MLT 630-105 V CP ST4 QLD X MLT 630-105 V CP ST4 QLD X MLT 630-105 V CP ST4 QLD X MLT 730-115 V CP ST4 QLD X MLT 730-115 V ST4 QLD X MLT 731-140 V+ ST4 QLD X MLT 940-140 V+ ST4 QLD X MLT 940-140 V+ ST4 QLD X MLT 940-140 V+ ST4 QLD X MLTX 737-130 PS+ QLD X MLTX 740-140 V+ ST4 QLD X MLTX 740-140 V+	MLT 850-145 V+	Х
MLT 1041-145 PS+L	MLT 940-140 V+ (S2)	Х
MIEX 625-75 H x MIEX 735 T LSU x MIEX 738-130 PS+ (SI) x MIEX 741 T LSU x MIEX 841 - 145 PS+ x MIEX 850-145 V+ x MIEX 961-160 V+ L x MIEX 1041-145 PS+L x MIEX 630-105 V C P ST4 0LD x MIE 630-105 V C P ST4 0LD x MIE 630-105 V ST4 0LD x MIEX 730-115 V ST4 0LD x MIEX 840-140 PS+ ST4 0LD x MIEX 840-140 PS+ 0LD x MIEX 737-130 PS+ 0LD x MIEX 737-130 PS+ 0LD x MIEX 737-130 PS+ 0LD x MIEX 741-140 V+ ST4 0LD	MLT 961-160 V+ L	Х
MLTX 735 T LSU	MLT 1041-145 PS+L	Х
MLFX 738-130 PS+ (S1) X MLFX 841 - 145 PS+ X MLFX 850-145 V+ X MLFX 961-160 V+ L X MLFX 961-160 V ST4 QLD X MLF 630-105 ST4 QLD X MLF 630-105 V CP ST4 QLD X MLF 630-105 V ST4 QLD X MLF 730-115 V CP ST4 QLD X MLF 730-115 V ST4 QLD X MLF 730-130 PS+ ST4 QLD X MLF 340-145 PS+ QLD X MLF 340-140 V + ST4 QLD X MLF 340-140 PS+ QLD X MLF 747-130 PS+ QLD X MLF 340-140 PS+ QLD X MLF 747-130 PS+ QLD X MLF 747-140 V + ST4 QLD X MLF 747-140 V + ST4 QLD X MLF 747-140 V + ST4 QLD X	MLT-X 625-75 H	Х
MLFX 741 T LSU	MLT-X 735 T LSU	Х
MLFX 841 - 145 PS+ X MLFX 850-145 V+ X MLFX 961-160 V+ L X MLFX 1041-145 PS+L X MLT 630-105 ST4 0LD X MLT 630-105 V ST4 0LD X MLT 630-105 V ST4 0LD X MLT 730-115 V CP ST4 0LD X MLT 730-115 V CP ST4 0LD X MLT 730-115 V ST4 0LD X MLT 737-130 PS+ ST4 0LD X MLT 741-140 V+ ST4 0LD X MLT 940-145 PS+ 1 0LD X MLT 940-140 V+ ST4 0LD X MLT 401-145 PS+ 1 0LD X MLT 140-145 PS+ 2 0LD X MLT X41-140 V+ ST4 0LD X MLT X41-140 V+ ST4 0LD X	MLT-X 738-130 PS+ (S1)	Х
MLTX 850-145 V+ L X MLTX 961-160 V+ L X MLTX 1041-145 PS+L X MLT 630-105 ST4 (0LD X MLT 630-105 ST4 (0LD X MLT 630-105 V ST4 (0LD X MLT 630-105 V ST4 (0LD X MLT 630-105 V ST4 (0LD X MLT 730-115 V CP ST4 (0LD X MLT 730-115 V CP ST4 (0LD X MLT 730-115 V CP ST4 (0LD X MLT 730-115 V ST4 (0LD X MLT 730-115 V ST4 (0LD X MLT 730-115 V ST4 (0LD X MLT 741-140 V+ ST4 (0LD X MLT 741-140 V+ ST4 (0LD X MLT 741-140 V+ ST4 (0LD X MLT 940-140 PS+ 0LD X MLT 940-140 PS+ 0LD X MLT 1450-145 PS+ L 0LD X MLTX 741-140 V+ ST4 (0LD X MLTX 741-140 V+ ST4	MLT-X 741 T LSU	Х
MLTX 1041-145 PS+L	MLT-X 841 - 145 PS+	Х
MLT 1041-145 PS+L	MLT-X 850-145 V+	Х
MLT 630-105 ST4 OLD	MLT-X 961-160 V+ L	Х
MLT 630-105 V CP ST4 OLD MLT 630-105 V ST4 OLD MLT 635-140 V+ ST4 OLD MLT 730-115 V CP ST4 OLD MLT 730-115 V ST4 OLD MLT 731-130 PS+ ST4 OLD MLT 741-140 V+ ST4 OLD MLT 741-140 V+ ST4 OLD MLT 840-145 PS+ OLD MLT 940-140 V+ ST4 OLD MLT 1040-145 PS+ L OLD MLT 737-130 PS+ OLD MLT 741-140 V+ ST4 OLD MLT 840-145 PS+ L OLD MLT 940-140 V+ ST4 OLD MLT 940-140 V+ ST4 OLD MLT X 737-130 PS+ OLD MLT X 737-130 PS+ OLD X MLTX X 840-140 PS+ OLD X MLTX X 840-140 PS+ OLD X	MLT-X 1041-145 PS+L	Х
MLT 630-105 V ST4 OLD	MLT 630-105 ST4 OLD	Х
MLT 730-115 V CP ST4 OLD MLT 730-115 V ST4 OLD X MLT 737-130 PS+ ST4 OLD X MLT 741-140 V+ ST4 OLD X MLT 840-145 PS+ OLD X MLT 940-140 V+ ST4 OLD X MLT 1040-145 PS+ L OLD X MLT 737-130 PS+ OLD X MLT 4040-140 V+ ST4 OLD X	MLT 630-105 V CP ST4 OLD	Х
MLT 730-115 V CP ST4 OLD	MLT 630-105 V ST4 OLD	Х
MLT 730-115 V ST4 OLD	MLT 635-140 V+ ST4	Х
MLT 737-130 PS+ ST4 OLD	MLT 730-115 V CP ST4 OLD	Х
MLT 741-140 V+ ST4 OLD	MLT 730-115 V ST4 OLD	Х
MLT 840-145 PS+ OLD	MLT 737-130 PS+ ST4 OLD	Х
MLT 940-140 V+ ST4 OLD	MLT 741-140 V+ ST4 OLD	Х
MLT 1040-145 PS+ L OLD	MLT 840-145 PS+ OLD	Х
MLFX 737-130 PS+ OLD X MLFX 741-140 V+ S1 OLD X MLFX 840-140 PS+ OLD X	MLT 940-140 V+ ST4	Х
MLT-X 741-140 V+ S1 OLD X MLT-X 840-140 PS+ OLD X	MLT 1040-145 PS+ L OLD	Х
MLFX 840-140 PS+ OLD X	MLT-X 737-130 PS+ OLD	Х
	MLT-X 741-140 V+ S1 OLD	Х
MLT-X 1040-140 PS+ L OLD X	MLT-X 840-140 PS+ OLD	Х
	MLT-X 1040-140 PS+ L OLD	Х

TABLE SYMBOL							
×	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank		
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition		





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes