Technical sheet:

HIGH PRESSURE CLEANER



Technical characteristics

- Tank capacity of 600 L / 21 ft3.
- Hydraulic powered water pump.
- Pressure regulation from 10 bars / 145 psi to 200 bars / 2901 psi.
- Manometer on standard.
- Nozzle spray with a 40 m / 131 ft hose.

[The 3D picture at the top of this page is the reference VHPC 600 - 790335].

Customer benefits

- Powerful and efficient cleaning.
- 45 min of autonomy at 200 bar / 2901 psi.
- Suitable for all types of cleaning applications and maintenances works.
- · Easy to hitch with a standard forks.



| Weight | | VHPC 600 |
|----------------------------|-----|---------------|
| Overall weight (kg) | | 240 |
| Weight and dimensions | | |
| Overall height (mm) | h17 | 1500 |
| Overall length (mm) | I1 | 1200 |
| Width (mm) | | 1450 |
| Cable length (mm) | | 40000 |
| Working Parameters | | |
| Required machine equipment | | ₽₽ ₽ <u>₽</u> |

| Reference number Nooss Nat | Machines compatibility | VHPC 600 |
|--|---------------------------------|----------|
| MLT 835-140 V+ (S2) MLT 742-130 PS+ (S1) X MLT 742-130 V+ (S2) X MLT 742-140 V+ (S2) X MLT 841-145 PS+ X MLT 841-145 PS+ X MLT 941-140 V+ (S2) X MLT 941-140 V+ (S2) X MLT 1041-145 PS+L X MLT 1041-145 PS+L X MLT 1041-145 PS+L X MLT X451-145 PS+ X MLT X451-145 PS+L X MLT X451-145 PS+L X MLT X451-145 PS+L X MLT X451-155 PS+L X MLT 351-150 V+L X MLT 351-150 V+L X MLT 351-150 V+L X MLT 351-150 V+ST4 010 X MLT 351 | Reference number | 790335 |
| MLT 738-130 P8+ (S1) MLT 742-130 P8+ (S1) X MLT 742-130 P8+ (S1) X MLT 841-145 P8+ X MLT 850-145 V+ X MLT 940-140 V+ (S2) X MLT 940-140 V+ (S1) X MLT 738-130 P8+ (S1) X MLT 738-130 P8+ (S1) X MLT 738-130 P8+ (S1) X MLTX 738-130 P8+ (S1) X MLTX 850-160 V+ L X MLTX 850-160 V+ L X MLTX 850-160 V+ L X MLTX 940-140 F8+ (S1) X MLTX 950-160 V+ L X MLTX 950-160 V+ S1 (D10 X MLT 630-105 V CP ST4 (D10 X MLT 635-108 P8+ (S1) (D10 X MLT 635-108 P8+ (S1) (D10 X MLT 635-108 P8+ (S1) (D10 X MLT 730-115 V S14 (D10 MLT 73 | MLT 635-130 PS+ (S2) | Х |
| MLT 742-130 Ps (S1) | MLT 635-140 V+ (S2) | χ |
| MLT 742-140 V+ (S1) MLT 361-145 PS+ X MLT 961-160 V+ L X MLT 961-160 V+ L X MLT 265-160 V+ L X MLT 2738 I S L S L S L S L S L S L S L S L S L S | MLT 738-130 PS+ (S1) | Х |
| MLT 841-145 PS+ MLT 860-145 V+ MLT 961-160 V+ L MLT 1011-145 PS+L MLT 1011-145 PS+L MLT 1011-145 PS+L MLT X011-145 PS+ MLT X011-145 PS+ MLT X011-145 PS+L MLT X011-145 PS+L MLT X011-145 PS+L MLT X011-15 PS+L MLT | MLT 742-130 PS+ (S1) | Х |
| MIT 850-145 V+ | MLT 742-140 V+ (S1) | X |
| MIT 940-140 V+ (S2) MIT 940-140 V+ (S2) MIT 940-140 V+ (S2) X MIT 1041-145 PS+L X MIEX 2575 H X MIEX 258 1-30 PS+ (S1) MIEX 341-145 PS+ MIEX 361-160 V+ L X MIEX 361-160 V+ ST4 0II0 X MIEX 373-180 PS+ ST4 0II0 X MIEX 373-180 PS+ ST4 0II0 X MIEX 373-180 PS+ 0II0 X MIEX 373-180 PS+ 0II0 X MIEX 361-160 V+ ST4 0II0 X MIEX 373-180 PS+ 0II0 X MIEX 361-140 V+ ST4 0II0 X MIEX 373-180 PS+ 0II0 X MIEX 373-180 PS+ 0II0 X MIEX 373-180 PS+ 0II0 X MIEX 361-140 V+ ST4 0II0 X | MLT 841-145 PS+ | Х |
| MLT 961-160 V+ L MLT 1041-145 PS+L X MLTX 262-75 H X MLTX 738-130 PS+ (S1) X MLTX 738-130 PS+ (S1) X MLTX 747 H T LSU X MLTX 850-145 V+ X MLTX 850-145 V+ X MLTX 801-145 PS+L X MLTX 801-105 ST4 (0LD X MLT 630-105 V ST4 (0LD X MLT 635-130 PS+ (S1) (0LD X MLT 635-140 V+ (S1) (0LD X MLT 730-115 V CP ST4 (0LD X MLT 730-145 PS+ (0LD X MLT 730-145 PS+ (0LD X MLT 730-145 PS+ (0LD X MLT 1040-145 PS+ (0LD X MLTX 310-145 PS+ (0LD X MLTX 1040-145 PS+ (0LD X MLTX 1040-140 PS+ (0LD X | MLT 850-145 V+ | X |
| MLT 1041-145 PS+L MLTX 265-75 H X MLTX 735 T LSU X MLTX 735 T LSU X MLTX 731 T LSU X MLTX 841 - 145 PS+ X MLTX 851-160 V+ L X MLTX 861-160 V+ L X MLTX 801-105 V C P ST4 | MLT 940-140 V+ (S2) | Х |
| MLEX 625-75 H MLEX 735 T LSU X MLEX 735-130 PS+ (S1) X MLEX 841 - 145 PS+ X MLEX 850-145 V+ MLEX 850-145 V+ MLEX 961-160 V+ L MLEX 961-160 V+ L MLEX 961-160 V+ C MLEX 961-160 V+ ST4 OLD X MLEX 961-150 V+ ST4 OLD X MLEX 961-160 V+ ST4 OLD | MLT 961-160 V+ L | Х |
| MIEX 735 T LSU | MLT 1041-145 PS+L | Х |
| MLEX 738-130 PS+ (S1) MLEX 841- 145 PS+ MLEX 850-145 V+ MLEX 851-140 V+ | MLT-X 625-75 H | Х |
| MLEX 741 T LSU | MLT-X 735 T LSU | Х |
| MLFX 850-145 V+ X MLFX 961-160 V+ L X MLFX 961-160 V+ L X MLFX 1041-145 PS+L X MLT 630-105 V OF ST4 0LD X MLT 630-105 V ST4 0LD X MLT 635-130 PS+ (ST) 0LD X MLT 635-140 V+ (ST) 0LD X MLT 635-140 V+ ST4 0LD X MLT 730-115 V ST4 0LD X MLT 730-115 V ST4 0LD X MLT 730-115 V ST4 0LD X MLT 741-140 V+ ST4 0LD X MLT 741-140 V+ ST4 0LD X MLT 940-140 V+ ST4 0LD X MLT 940-140 V+ ST4 0LD X MLT 940-140 V+ ST4 0LD X MLT 1040-145 PS+ 0LD X MLT 741-140 V+ ST4 0LD X MLT 740-140 V+ ST4 0LD X MLT 740-140 V+ ST4 0LD X | MLT-X 738-130 PS+ (S1) | Х |
| MLFX 850-145 V+ | MLT-X 741 T LSU | Х |
| MLFX 951-160 V+ L MLFX 1041-145 PS+L X MLT 630-105 ST4 0LD MLT 630-105 V ST4 0LD X MLT 635-130 PS+ (S1) 0LD X MLT 635-140 V+ ST4 0LD X MLT 730-115 V CP ST4 0LD X MLT 730-115 V ST4 0LD X MLT 730-115 V ST4 0LD X MLT 730-115 V ST4 0LD X MLT 730-130 PS+ ST4 0LD X MLT 741-140 V+ ST4 0LD X MLT 740-140 V+ ST4 0LD X MLT 940-140 V+ ST4 0LD X MLT 940-140 V+ ST4 0LD X MLT 940-140 V+ ST4 0LD X MLT 741-140 V+ ST4 0LD X | MLT-X 841 - 145 PS+ | Х |
| MLT X 1041-145 PS+L | MLT-X 850-145 V+ | Х |
| MLT 630-105 ST4 OLD MLT 630-105 V ST4 OLD MLT 635-130 PS+ (S1) OLD MLT 635-140 V+ (S1) OLD MLT 635-140 V+ ST4 OLD MLT 730-115 V CP ST4 OLD MLT 730-115 V ST4 OLD MLT 731-140 V+ ST4 OLD MLT 741-140 V+ ST4 OLD MLT 741-140 V+ ST4 OLD MLT 741-140 V+ ST4 OLD MLT 940-145 PS+ ULD MLT 940-140 V+ ST4 OLD MLT 940-1 | MLT-X 961-160 V+ L | Х |
| MLT 630-105 V CP ST4 OLD MLT 630-105 V ST4 OLD X MLT 635-130 PS+ (S1) OLD X MLT 635-140 V+ (S1) OLD X MLT 730-115 V CP ST4 OLD X MLT 730-115 V CP ST4 OLD X MLT 737-130 PS+ ST4 OLD X MLT 741-140 V+ ST4 OLD X MLT 741-140 V+ ST4 OLD X MLT 737-130 PS+ DLD X MLT 747-140 V+ ST4 OLD X MLT 741-140 V+ ST4 OLD X MLT 741-140 V+ ST4 OLD X MLT 741-140 V+ ST4 OLD X MLT X47-140 V+ ST4 OLD X MLT X41-140 V+ ST4 OLD X | MLT-X 1041-145 PS+L | Х |
| MLT 630-105 V ST4 OLD | MLT 630-105 ST4 OLD | Х |
| MLT 635-130 PS+ (S1) OLD MLT 635-140 V+ (S1) OLD X MLT 730-115 V CP ST4 OLD X MLT 730-115 V ST4 OLD X MLT 737-130 PS+ ST4 OLD X MLT 741-140 V+ ST4 OLD X MLT 741-140 V+ ST4 OLD X MLT 940-140 V+ ST4 OLD X MLT 940-140 V+ ST4 OLD X MLT 741-140 V+ ST4 OLD X MLT 940-140 V+ ST4 OLD X MLT 401-145 PS+ L OLD X MLT 401-140 V+ S1 OLD X MLT 401-140 V+ S1 OLD X MLT 401-140 V+ S1 OLD | MLT 630-105 V CP ST4 OLD | Х |
| MLT 635-140 V+ (S1) OLD X MLT 730-115 V CP ST4 OLD X MLT 730-115 V ST4 OLD X MLT 737-130 PS+ ST4 OLD X MLT 741-140 V+ ST4 OLD X MLT 741-140 V+ ST4 OLD X MLT 940-140 V+ ST4 OLD X MLT 940-140 V+ ST4 OLD X MLT 1040-145 PS+ L OLD X MLT 404-145 PS+ L OLD X MLT 404-140 PS+ OLD X MLT 404-140 PS+ OLD | MLT 630-105 V ST4 OLD | Х |
| MLT 730-115 V CP ST4 OLD | MLT 635-130 PS+ (S1) OLD | Х |
| MLT 730-115 V CP ST4 OLD | MLT 635-140 V+ (S1) OLD | Х |
| MLT 730-115 V ST4 OLD | MLT 635-140 V+ ST4 OLD | Х |
| MLT 737-130 PS+ ST4 OLD | MLT 730-115 V CP ST4 OLD | Х |
| MLT 741-140 V+ ST4 OLD | MLT 730-115 V ST4 OLD | Х |
| MLT 840-145 PS+ OLD | MLT 737-130 PS+ ST4 OLD | Х |
| MLT 940-140 V+ ST4 OLD | MLT 741-140 V+ ST4 OLD | Х |
| MLT 1040-145 PS+ L OLD | MLT 840-145 PS+ OLD | Х |
| MLT-X 737-130 PS+ OLD | MLT 940-140 V+ ST4 OLD | Х |
| MLT-X 741-140 V+ S1 OLD X MLT-X 840-140 PS+ OLD X | MLT 1040-145 PS+ L OLD | Х |
| MLT-X 840-140 PS+ OLD X | MLT-X 737-130 PS+ OLD | Х |
| _ | MLT-X 741-140 V+ S1 OLD | Х |
| MLT-X 1040-140 PS+ L OLD X | MLT-X 840-140 PS+ OLD | Х |
| | MLT-X 1040-140 PS+ L OLD | Х |

| TABLE SYMBOL | | | | | | | | |
|--------------|----------------------------|----|-------------------------|--|---|--|--|--|
| \times | No predisposition required | 88 | Hydraulic line | | Return piping to hydraulic oil tank | | | |
| | Electric predisposition | | Platform predisposition | | Tyre handler, cylinder handler predisposition | | | |





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes