Technical sheet:

HIGH PRESSURE CLEANER



Customer benefits

- Powerful and efficient cleaning.
- 45 min of autonomy at 200 bars.
- Suitable for all types of cleaning applications and maintenances works.
- Easy to hitch with a standard forks.

Technical characteristics

- Tank capacity of 600 l.
- Hydraulic powered water pump.
- Pressure regulation from 10 to 200 bars.
- Manometer on standard.
- Nozzle spray with a 40 m hose.

[The 3D picture at the top of this page is the reference VHPC 600 - 790335].



Capacities		VHPC 600				
Heaped capacity (I)		600				
Weight						
Overall weight (kg)		240				
Weight and dimensions						
Overall height (mm)	h17	1500				
Overall length (mm)	I1	1200				
Width (mm)		1450				
Cable length (mm)		40000				
Working Parameters						
Machine Equipment						

Machines compatibility	VHPC 600
Reference number	790335
MLT 635-130 PS+	x
MLT 635-140 V+	х
MLT 841-145 PS+	х
MLT 850-145 V+	х
MLT 961-160 V+ L	х
MLT 1041-145 PS+L	х
MLT-X 625-75 H	х
MLT-X 735 T LSU	х
MLT-X 741 T LSU	x
MLT-X 841 - 145 PS+	x
MLT-X 850-145 V+	х
MLT-X 961-160 V+ L	x
MLT-X 1041-145 PS+L	x
MLT 630-105 ST4 OLD	x
MLT 630-105 V CP ST4 OLD	Х
MLT 630-105 V ST4 OLD	x
MLT 635-140 V+ ST4 OLD	Х
MLT 730-115 V CP ST4 OLD	x
MLT 730-115 V ST4 OLD	Х
MLT 737-130 PS+ ST4 OLD	x
MLT 741-140 V+ ST4 OLD	Х
MLT 840-145 PS+ OLD	x
MLT 940-140 V+ ST4 OLD	Х
MLT 1040-145 PS+ L OLD	x
MLT-X 737-130 PS+ OLD	х
MLT-X 741-140 V+ S1 OLD	x
MLT-X 840-140 PS+ OLD	х
MLT-X 1040-140 PS+ L OLD	X

TABLE SYMBOL							
X	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank		
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition		





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes