

Technical sheet :

HIGH TIP BUCKET (COMPACT MACHINES)



Technical characteristics

- For materials with a density <math>< 1,8 \text{ t/m}^3 / 112 \text{ lb/ft}^3</math>.

Customer benefits

- Noticeably increases the machine's lifting height (+ 800 mm / 31 in or more).
- Improves the efficiency of truck/container loading applications.

Capacities		BHS 1525 / 550	
Capacity (kg)			990
Heaped capacity (l)			550
Weight			
Overall weight (kg)			340
Weight and dimensions			
Overall height (mm)	h17		643
Width (mm)			1525
Depth (mm)	p5		970
Working Parameters			
Required machine equipment			

Machines compatibility		BHS 1525 / 550	
All-Tach®		N004050	
AL650			X
MLA 6-65 H-Z			X
AL750 OLD			X
MLA 4-50 H OLD			X

TABLE SYMBOL

	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes