HIGH TIP BUCKET (COMPACT MACHINES)

BUCKETS





Customer benefits

Technical characteristics

- Noticeably increases the machine's lifting height (+ 800 mm / 31 in or more).
- Improves the efficiency of truck/container loading applications.
- For materials with a density < 1,8 t/m³ / 112 lb/ft³.

MANITOU ATTACHMENTS

Capacities		BHS 1525 / 550
Capacity (lb)		2183
Heaped capacity (US gal)		145
Weight		
Overall weight (lb)		750
Weight and dimensions		
Overall height (in)	h17	2'1"
Width (in)		5
Depth (in)	р5	3' 2"
Working Parameters		
Machine Equipment		88

Machines compatibility	BHS 1525 / 550		
All-Tach®	N004050		
AL650	x		
AL750	x		
MLA 6-65 H-Z	x		
MLA 4-50 H OLD	х		

TABLE SYMBOL								
×	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank			
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition			





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend