

HIGH TIP BUCKET (COMPACT MACHINES)

ブラケット



GEHL®


お客様のメリット

- Noticeably increases the machine's lifting height (+ 800mm or more).
- Improves the efficiency of truck/container loading applications.




諸元

- For materials with a density < 1,8t/m³.

MANITOU GROUP ATTACHMENTS

キャパシティ		BHS 1525 / 550	
諸元 (kg)			990
ドーム容量 (l)			550
重量			
重量 (kg)			340
仕様			
全高 (mm)	h17		643
幅 (mm)			1525
深さ (mm)	p5		970
ワーキング パラメーター			
機械設備			
フレキシブルチューブ			いいえ

マシンの互換性		BHS 1525 / 550	
All-Tach®			N004050
AL650			X
AL750			X
MLA 6-65 H-Z			X
MLA 4-50 H OLD			X

記号の表					
	前処理が不要		油圧ライン		タンクへの油圧リターン
	電気要素		プラットフォーム要素		タイヤクランプ、シリンダークランプ要素



GEHL®

Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend