Technical sheet :

## HIGH TIP BUCKET (COMPACT MACHINES)



## **Customer benefits**

## Technical characteristics

Noticeably increases the machine's lifting height (+ 800mm or more).
Improves the efficiency of truck/container loading applications.

- For materials with a density <  $1,8t/m^3$ .



## HIGH TIP BUCKET (COMPACT MACHINES) Created on May 5, 2024 at 9:40:37 AM UTC

Capacities		BHS 1525 / 550
Capacity (Ib)		2183
Heaped capacity (US gal)		145
Weight		
Overall weight (lb)		750
Weight and dimensions		
Overall height (in)	h17	2 1*
Width (in)		5
Depth (in)	р5	3 2*
Working Parameters		
Machine Equipment		

Machines compatibility	BHS 1525 / 550		
All-Tach®	N004050		
AL650	x		
AL750	x		
MLA 6-65 H-Z	x		
MLA 4-50 H OLD	x		

TABLE SYMBOL								
$\times$	No predisposition required	₽₽	Hydraulic line		Retum piping to hydraulic oil tank			
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition			





This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes