

# HYDRAULIC HAMMER (COMPACT MACHINES) EARTH DRILLING AND DIGGING SOLUTIONS

---



## GEHL®

### Customer benefits

---








- Turns your machine into a real demolition unit.
- Silent version standard.

### Technical characteristics







---

- High resistance, frame and hydraulics.
- High impact frequency and stroke power.

**MANITOU GROUP ATTACHMENTS**

Weight		H 88	H 90	H 160	H 162	H 236	H 240	H 330	H 570
Overall weight (kg)		88	88	162	162	236	236	330	568
Weight and dimensions									
Overall height (mm)	h17	773	773	932	932	1016	1016	1112	1288
Diameter minimum (mm)		47.90	47.90	53.70	53.70	-	67.50	77.50	81.50
Working Parameters									
Machine Equipment						-			

Machines compatibility	H 88	H 90	H 160	H 162	H 236	H 240	H 330	H 570
All-Tach® Narrow	N5 15 02209	-	-	N5 15 02210	-	-	-	-
All-Tach®	-	N5 15 02209	N5 15 02210	-	N5 15 02211	N5 15 02211	N5 15 02212	N5 15 02214
1050R	X	X	X	X	-	-	-	-
1050RT	X	-	-	X	-	-	-	-
1350R NXT2	X	X	X	X	-	-	-	-
1350RT	X	-	-	X	-	-	-	-
1640 E	X	-	-	-	-	-	-	-
1650R	-	-	X	X	-	X	-	-
1650RT	-	-	-	X	-	X	-	-
1850RT	-	-	-	-	-	X	X	-
1900R	-	-	X	X	-	X	-	-
1950RT	-	-	-	X	-	X	-	-
1950RT	-	-	-	X	-	X	-	-
1950RT	-	-	-	X	-	X	-	-
1950RT	-	-	-	X	-	X	-	-
2150RT	-	-	-	-	-	X	X	-
2200R	-	-	-	-	-	X	X	-
2600R	-	-	-	-	-	X	X	-
2700V NXT2	-	-	-	-	-	X	X	-
3300V NXT2	-	-	-	-	-	X	X	-
4200V	-	-	-	-	-	-	X	X
R105	X	-	-	X	-	-	-	-
R165	-	-	X	X	-	X	-	-
R220	-	-	-	-	-	X	X	-
R260	-	-	-	-	-	X	X	-
RT105	X	-	-	X	-	-	-	-
RT135	X	-	-	X	-	-	-	-
RT165	-	-	-	X	-	X	-	-
RT185	-	-	-	-	-	X	X	-
RT195 - NEW	-	-	-	X	-	X	-	-
RT195 - NEW	-	-	-	X	-	X	-	-
RT195 - NEW	-	-	-	X	-	X	-	-
RT215	-	-	-	-	-	X	X	-
V330 GEN:2	-	-	-	-	-	X	X	-
V330 GEN:2	-	-	-	-	-	X	X	-
MLA 3-35 H <b>OLD</b>	X	-	-	X	-	-	-	-
MLA 4-50 H <b>OLD</b>	X	-	-	X	-	-	-	-
V270 <b>OLD</b>	-	-	-	-	-	X	X	-

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



# GEHL®

Siège Social  
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095  
Tel: (262) 334-9461 - Fax: (262) 338-7517  
[www.gehl.com](http://www.gehl.com)



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend