

**MARTELO HIDRAULICO
(MAQUINAS COMPACTAS)**

SOLUÇÕES DE PERFURAÇÃO E ESCAVAÇÃO



GEHL®








Benefícios para o cliente

- Transforme a sua máquina numa verdadeira unidade de demolição.
- Versão silenciosa de série.







Características técnicas

- Alta resistência, estrutura e sistema hidráulico.
- Alta frequência de impacto e potência de funcionamento.

MANITOU GROUP ATTACHMENTS

Weight		H 88	H 90	H 160	H 162	H 236	H 240	H 330	H 570
Peso (kg)		88	88	162	162	236	236	330	568
Peso e dimensões									
Altura total (mm)	h17	773	773	932	932	1016	1016	1112	1288
Diâmetro mínimo (mm)		47.90	47.90	53.70	53.70	-	67.50	77.50	81.50
Parâmetros de trabalho									
Equipamento da máquina						-			

Máquina de compatibilidades	H 88	H 90	H 160	H 162	H 236	H 240	H 330	H 570
All-Tach® estreito	N5 15 02209	-	-	N5 15 02210	-	-	-	-
All-Tach®	-	N5 15 02209	N5 15 02210	-	N5 15 02211	N5 15 02211	N5 15 02212	N5 15 02214
1050R	X	X	X	X	-	-	-	-
1050RT	X	-	-	X	-	-	-	-
1350R NXT2	X	X	X	X	-	-	-	-
1350RT	X	-	-	X	-	-	-	-
1640 E	X	-	-	-	-	-	-	-
1650R	-	-	X	X	-	X	-	-
1650RT	-	-	-	X	-	X	-	-
1850RT	-	-	-	-	-	X	X	-
1900R	-	-	X	X	-	X	-	-
1950RT	-	-	-	X	-	X	-	-
1950RT	-	-	-	X	-	X	-	-
1950RT	-	-	-	X	-	X	-	-
1950RT	-	-	-	X	-	X	-	-
2150RT	-	-	-	-	-	X	X	-
2200R	-	-	-	-	-	X	X	-
2600R	-	-	-	-	-	X	X	-
2700V NXT2	-	-	-	-	-	X	X	-
3300V NXT2	-	-	-	-	-	X	X	-
4200V	-	-	-	-	-	-	X	X
R105	X	-	-	X	-	-	-	-
R165	-	-	X	X	-	X	-	-
R220	-	-	-	-	-	X	X	-
R260	-	-	-	-	-	X	X	-
RT105	X	-	-	X	-	-	-	-
RT135	X	-	-	X	-	-	-	-
RT165	-	-	-	X	-	X	-	-
RT185	-	-	-	-	-	X	X	-
RT195 - NEW	-	-	-	X	-	X	-	-
RT195 - NEW	-	-	-	X	-	X	-	-
RT195 - NEW	-	-	-	X	-	X	-	-
RT215	-	-	-	-	-	X	X	-
V330 GEN:2	-	-	-	-	-	X	X	-
V330 GEN:2	-	-	-	-	-	X	X	-
MLA 3-35 H OLD	X	-	-	X	-	-	-	-
MLA 4-50 H OLD	X	-	-	X	-	-	-	-
V270 OLD	-	-	-	-	-	X	X	-

TABELA DE SÍMBOLOS					
	Não é necessária predisposição		Linha hidráulica		Retorno hidráulico ao reservatório
	Predisposição eléctrica		Predisposição da plataforma		Predisposição manipulador de pneus, do manipulador de cilindros



GEHL®

Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend