

LIGHT MATERIAL BUCKET (COMPACT MACHINES)

BUCKETS



GEHL®

Customer benefits

- Wide range of bucket capacities.
- High capacities for efficient loading applications

Technical characteristics

- Suited for bulk materials with a density $< 1 \text{ t/m}^3 / 62 \text{ lb/ft}^3$.
- 400 HB cutting edge for more resistance.

MANITOU
GROUP ATTACHMENTS

| Capacities | | BLM 920 / 240 | BLM 920 / 430 | BLM 1080 / 290 | BLM 1080 / 510 | BLM 1200 / 580 | BLM 1220 / 330 | BLM 1300 / 630 (a) | BLM 1300 / 630 (b) | BLM 1300 / 630 (c) | BLM 1380 / 430 |
|-----------------------|-----|---------------|---------------|----------------|----------------|----------------|----------------|--------------------|--------------------|--------------------|----------------|
| Capacity (kg) | | 240 | 430 | 290 | 510 | 580 | 330 | 630 | 630 | 630 | 430 |
| Heaped capacity (l) | | 240 | 430 | 290 | 510 | 580 | 330 | 630 | 630 | 630 | 430 |
| Weight | | | | | | | | | | | |
| Overall weight (kg) | | 62 | 169 | 67 | 173 | 184 | - | 196 | 203 | 205 | 140 |
| Weight and dimensions | | | | | | | | | | | |
| Overall height (mm) | h17 | 490 | 775 | 490 | 775 | 775 | 490 | 775 | 775 | 795 | 600 |
| Width (mm) | | 920 | 920 | 1080 | 1080 | 1200 | 1220 | 1300 | 1300 | 1300 | 1380 |
| Depth (mm) | p5 | 819 | 1025 | 819 | 1025 | 1025 | 819 | 1025 | 988 | 957 | 890 |
| Working Parameters | | | | | | | | | | | |
| Machine Equipment | | × | × | × | × | × | × | × | × | × | × |
| Flexible tube | | - | - | - | - | - | - | - | - | - | - |

| Machines compatibility | BLM 920 / 240 | BLM 920 / 430 | BLM 1080 / 290 | BLM 1080 / 510 | BLM 1200 / 580 | BLM 1220 / 330 | BLM 1300 / 630 (a) | BLM 1300 / 630 (b) | BLM 1300 / 630 (c) | BLM 1380 / 430 |
|------------------------|---------------|---------------|----------------|----------------|----------------|----------------|--------------------|--------------------|--------------------|----------------|
| All-Tach® Narrow | - | N004021 | - | N004022 | N004023 | - | N004024 | - | - | - |
| All-Tach® | N726009 | - | N726010 | - | - | N726011 | - | N004088 | N004092 | N736013 |
| 4 point Carriage | - | N003021 | - | N003022 | N003023 | - | N003024 | N003088 | N003092 | - |
| Euro Carriage | - | - | - | N51502113 | N51502114 | - | N51502115 | N51502160 | N51502185 | - |
| 1050R | - | - | - | - | - | X | - | - | - | X |
| 1050RT | - | - | - | - | - | X | - | - | - | X |
| 1350R NXT2 | - | - | - | - | - | X | - | - | - | X |
| 1350RT | - | - | - | - | - | X | - | - | - | X |
| 1640 E | X | - | X | - | - | - | - | - | - | - |
| AL230 | - | - | - | X | X | - | X | - | - | - |
| AL320 | - | - | - | X | X | - | X | - | - | - |
| AL330 | - | - | - | X | X | - | X | - | - | - |
| AL420 | - | - | - | X | X | - | X | X | - | - |
| AL430 | - | - | - | X | X | - | X | X | - | - |
| AL530 | - | - | - | - | - | - | - | - | X | - |
| AL550 | - | - | - | - | - | - | - | - | X | - |
| MLA 2-25 H | - | - | - | X | X | - | X | - | - | - |
| MLA 3-25 H | - | - | - | X | X | - | X | - | - | - |
| MLA 3-25 H-C | - | - | - | X | X | - | X | - | - | - |
| MLA 4-50 H | - | - | - | X | X | - | X | X | - | - |
| MLA 4-50 H-C | - | - | - | X | X | - | X | X | - | - |
| MLA 5-50 H | - | - | - | - | - | - | - | - | X | - |
| MLA 5-60 H-Z | - | - | - | - | - | - | - | - | X | - |
| R105 | - | - | - | - | - | X | - | - | - | X |
| RT105 | - | - | - | - | - | X | - | - | - | X |
| RT135 | - | - | - | - | - | X | - | - | - | X |
| MLA 1-25 H OLD | - | X | - | X | X | - | - | - | - | - |
| MLA 3-35 H OLD | - | - | - | - | X | - | X | - | - | - |
| MLA 4-50 H OLD | - | - | - | X | X | - | X | X | - | - |

| Capacities | | BLM 1400 / 680 (a) | BLM 1400 / 680 (b) | BLM 1400 / 680 (c) | BLM 1500 / 730 (a) | BLM 1500 / 730 (b) | BLM 1500 / 730 (c) | BLM 1520 / 480 | BLM 1650 / 1100 | BLM 1680 / 530 | BLM 1680 / 670 |
|-----------------------|-----|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|----------------|-----------------|----------------|----------------|
| Capacity (kg) | | 680 | 680 | 680 | 730 | 730 | 730 | 480 | 810 | 530 | 670 |
| Heaped capacity (l) | | 680 | 680 | 680 | 730 | 730 | 730 | 480 | 810 | 530 | 670 |
| Weight | | | | | | | | | | | |
| Overall weight (kg) | | 194 | 210 | 210 | 208 | 218 | 220 | - | 1100 | 160 | 242 |
| Weight and dimensions | | | | | | | | | | | |
| Overall height (mm) | h17 | 775 | 775 | 795 | 775 | 775 | 795 | 600 | 810 | 600 | 605 |
| Width (mm) | | 1400 | 1400 | 1400 | 1500 | 1500 | 1500 | 1520 | 1650 | 1680 | 1680 |
| Depth (mm) | p5 | 1025 | 988 | 967 | 1025 | 988 | 951 | 890 | 1224 | 890 | 1023 |
| Working Parameters | | | | | | | | | | | |
| Machine Equipment | | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ |
| Flexible tube | | - | - | - | - | - | - | - | - | - | - |

| Machines compatibility | BLM 1400 / 680 (a) | BLM 1400 / 680 (b) | BLM 1400 / 680 (c) | BLM 1500 / 730 (a) | BLM 1500 / 730 (b) | BLM 1500 / 730 (c) | BLM 1520 / 480 | BLM 1650 / 1100 | BLM 1680 / 530 | BLM 1680 / 670 |
|------------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|----------------|-----------------|----------------|----------------|
| All-Tach® Narrow | N004025 | - | - | N004026 | - | - | - | - | - | - |
| All-Tach® | - | N004089 | N004093 | - | N004090 | N004094 | N736014 | N51502537 | N736015 | N747011 |
| 4 point Carriage | N003025 | 52799520 | N003093 | N003026 | N003090 | N003094 | - | N51502603 | - | - |
| Euro Carriage | N002025 | N51502161 | N51502186 | N002026 | N51502162 | N51502187 | - | N51502562 | - | - |
| 1350R NXT2 | - | - | - | - | - | - | X | - | X | - |
| 1350RT | - | - | - | - | - | - | X | - | X | - |
| 1650R | - | - | - | - | - | - | - | - | - | X |
| 1650RT | - | - | - | - | - | - | - | - | - | X |
| 1900R | - | - | - | - | - | - | - | - | - | X |
| 1950RT | - | - | - | - | - | - | - | - | - | X |
| 1950RT | - | - | - | - | - | - | - | - | - | X |
| 1950RT | - | - | - | - | - | - | - | - | - | X |
| 1950RT | - | - | - | - | - | - | - | - | - | X |
| 2100V | - | - | - | - | - | - | - | - | - | X |
| 2100VT | - | - | - | - | - | - | - | - | - | X |
| AL320 | - | X | - | - | - | - | - | - | - | - |
| AL330 | - | X | - | - | - | - | - | - | - | - |
| AL420 | X | X | - | - | - | - | - | - | - | - |
| AL430 | X | X | - | - | - | - | - | - | - | - |
| AL530 | - | - | X | - | - | X | - | - | - | - |
| AL550 | - | - | X | - | - | X | - | - | - | - |
| AL650 | - | - | - | - | - | - | - | X | - | - |
| AL750 | - | - | - | - | - | - | - | X | - | - |
| ALT750 | - | - | - | - | - | - | - | X | - | - |
| MLA 3-25 H | - | X | - | - | - | - | - | - | - | - |
| MLA 3-25 H-C | - | X | - | - | - | - | - | - | - | - |
| MLA 4-50 H | X | X | - | - | - | - | - | - | - | - |
| MLA 4-50 H-C | X | X | - | - | - | - | - | - | - | - |
| MLA 5-50 H | - | - | X | - | - | X | - | - | - | - |
| MLA 5-60 H-Z | - | - | X | - | - | X | - | - | - | - |
| MLA 6-65 H-Z | - | - | - | - | - | - | - | X | - | - |
| MLA-T 516-75 H | - | - | - | - | - | - | - | X | - | - |
| R165 | - | - | - | - | - | - | - | - | - | X |
| RT135 | - | - | - | - | - | - | X | - | X | - |
| RT165 | - | - | - | - | - | - | - | - | - | X |
| RT195 - NEW | - | - | - | - | - | - | - | - | - | X |
| RT195 - NEW | - | - | - | - | - | - | - | - | - | X |
| RT195 - NEW | - | - | - | - | - | - | - | - | - | X |
| V210 - NEW | - | - | - | - | - | - | - | - | - | X |
| VT210 - NEW | - | - | - | - | - | - | - | - | - | X |
| AL440 OLD | - | X | - | - | - | - | - | - | - | - |
| ALT750 OLD | - | - | - | - | - | - | - | X | - | - |
| ALT750 OLD | - | - | - | - | - | - | - | X | - | - |
| MLA 3-35 H OLD | X | - | - | X | - | - | - | - | - | - |
| MLA 4-50 H OLD | X | X | - | - | X | - | - | - | - | - |

| Capacities | | BLM 1760 / 790 | BLM 1760 / 820 | BLM 1800 / 910 | BLM 1800 / 1200 | BLM 1850 / 830 | BLM 1850 / 860 | BLM 1850 / 1100 | BLM 1950 / 1300 | BLM 2000 / 1020 | BLM 2080 / 1250 |
|-----------------------|-----|----------------|----------------|----------------|-----------------|----------------|----------------|-----------------|-----------------|-----------------|-----------------|
| Capacity (kg) | | 820 | 790 | - | 810 | 860 | 830 | 1100 | 1300 | - | 1250 |
| Heaped capacity (l) | | 820 | 790 | 910 | 810 | 860 | 830 | 1100 | 1300 | 1020 | 1250 |
| Weight | | | | | | | | | | | |
| Overall weight (kg) | | 275 | 264 | 235 | 1200 | 290 | 275 | 350 | 354 | 250 | 370 |
| Weight and dimensions | | | | | | | | | | | |
| Overall height (mm) | h17 | 711 | 705 | 795 | 810 | 711 | 705 | 832 | 810 | 795 | 832 |
| Width (mm) | | 1760 | 1760 | 1800 | 1800 | 1850 | 1850 | 1850 | 1950 | 2000 | 2080 |
| Depth (mm) | p5 | 1020 | 1012 | 951 | 1224 | 1020 | 1012 | 1102 | 1224 | 951 | 1102 |
| Working Parameters | | | | | | | | | | | |
| Machine Equipment | | × | × | - | × | × | × | × | × | - | × |
| Flexible tube | | - | - | No | - | - | - | - | - | No | - |

| Machines compatibility | BLM 1760 / 790 | BLM 1760 / 820 | BLM 1800 / 910 | BLM 1800 / 1200 | BLM 1850 / 830 | BLM 1850 / 860 | BLM 1850 / 1100 | BLM 1950 / 1300 | BLM 2000 / 1020 | BLM 2080 / 1250 |
|----------------------------|----------------|----------------|----------------|-----------------|----------------|----------------|-----------------|-----------------|-----------------|-----------------|
| All-Tach® Narrow | - | - | - | - | - | - | - | - | - | - |
| All-Tach® 4 point Carriage | N757013 | N51502468 | N004027 | N51502536 | N757014 | N51502469 | N51502037 | N51502535 | N004028 | N51502076 |
| Euro Carriage | - | - | N003027 | N51502605 | - | - | - | N51502607 | N003028 | - |
| | - | - | N51502188 | N51502564 | - | - | - | N51502566 | N51502189 | - |
| 1850RT | - | - | - | - | - | - | X | - | - | - |
| 2100V | - | X | - | - | X | - | - | - | - | - |
| 2100VT | - | - | - | - | - | - | X | - | - | - |
| 2150RT | - | - | - | - | - | - | X | - | - | - |
| 2200R | - | X | - | - | - | X | - | - | - | - |
| 2300V | X | X | - | - | X | X | - | - | - | - |
| 2300VT | - | - | - | - | - | - | X | - | - | - |
| 2600R | - | - | - | - | - | X | - | - | - | X |
| 2700V NXT2 | X | - | - | - | X | - | - | - | - | - |
| 2750V | X | - | - | - | - | X | - | - | - | X |
| 2750VT | - | - | - | - | - | - | X | - | - | - |
| 3300V NXT2 | - | - | - | - | - | - | - | - | - | X |
| 4200V | - | - | - | - | - | - | - | - | - | X |
| AL650 | - | - | - | X | - | - | - | X | - | - |
| AL750 | - | - | - | X | - | - | - | X | - | - |
| ALT750 | - | - | - | X | - | - | - | X | - | - |
| MLA 6-65 H-Z | - | - | - | X | - | - | - | X | - | - |
| MLA-T 516-75 H | - | - | - | X | - | - | - | X | - | - |
| R220 | - | X | - | - | - | X | - | - | - | - |
| R260 | - | - | - | - | - | X | - | - | - | X |
| RT185 | - | - | - | - | - | - | X | - | - | - |
| RT215 | - | - | - | - | - | - | X | - | - | - |
| V210 - NEW | - | X | - | - | X | - | - | - | - | - |
| V230 - NEW | X | X | - | - | X | X | - | - | - | - |
| V275 - NEW | X | - | - | - | - | X | - | - | - | X |
| V330 GEN:2 | - | - | - | - | - | - | - | - | - | X |
| V330 GEN:2 | - | - | - | - | - | - | - | - | - | X |
| VT210 - NEW | - | - | - | - | - | - | X | - | - | - |
| VT230 - NEW | - | - | - | - | - | - | X | - | - | - |
| VT275 - NEW | - | - | - | - | - | - | X | - | - | - |
| VT275 - NEW | - | - | - | - | - | - | X | - | - | - |
| ALT750 OLD | - | - | - | X | - | - | - | X | - | - |
| ALT750 OLD | - | - | - | X | - | - | - | X | - | - |
| V270 OLD | X | - | - | - | X | - | - | - | - | - |

| Capacities | | BLM 2140 / 1290 | BLM 2150 / 1420 | BLM 2350 / 1370 (a) | BLM 2350 / 1370 (b) |
|-----------------------|-----|-----------------|-----------------|---------------------|---------------------|
| Capacity (kg) | | 1290 | 1420 | 1370 | 1370 |
| Heaped capacity (l) | | 1290 | 1420 | 1370 | 1370 |
| Weight | | | | | |
| Overall weight (kg) | | 381 | 380 | 405 | 405 |
| Weight and dimensions | | | | | |
| Overall height (mm) | h17 | 832 | 810 | 832 | 832 |
| Width (mm) | | 2140 | 2150 | 2350 | 2350 |
| Depth (mm) | p5 | 1102 | 1224 | 1102 | 1102 |
| Working Parameters | | | | | |
| Machine Equipment | | × | × | × | × |
| Flexible tube | | - | - | - | - |

| Machines compatibility | BLM 2140 / 1290 | BLM 2150 / 1420 | BLM 2350 / 1370 (a) | BLM 2350 / 1370 (b) |
|----------------------------|-----------------|-----------------|---------------------|---------------------|
| All-Tach® Narrow | - | - | - | - |
| All-Tach® 4 point Carriage | N700248 | N51502534 | N700249 | N51502038 |
| Euro Carriage | - | N51502609 | - | - |
| | - | N51502568 | - | - |
| 2150RT | - | - | - | X |
| 2750VT | - | - | - | X |
| 3300V NXT2 | X | - | - | - |
| 4200V | X | - | X | - |
| AL750 | - | X | - | - |
| ALT750 | - | X | - | - |
| MLA-T 516-75 H | - | X | - | - |
| RT215 | - | - | - | X |
| V330 GEN:2 | X | - | - | - |
| V330 GEN:2 | X | - | - | - |
| VT275 - NEW | - | - | - | X |
| ALT750 OLD | - | X | - | - |
| ALT750 OLD | - | X | - | - |

| TABLE SYMBOL | | | | | |
|---|----------------------------|---|-------------------------|---|---|
|  | No predisposition required |  | Hydraulic line |  | Return piping to hydraulic oil tank |
|  | Electric predisposition |  | Platform predisposition |  | Tyre handler, cylinder handler predisposition |



GEHL®

Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend