Technical sheet :

LIGHT MATERIAL BUCKET

Technical characteristics

- Suitable for low density products like powders, grains or even snow

Customer benefits

- A great choice for handling light materials such as grain, feed, and other cereals

		BLM 1080/510	BLM 1080/510 EU	BLM 1200/580	BLM 1200/580 EU	BLM 1220/330	BLM 1300/630	BLM 1300/630	BLM 1300/630
Reference number		N003022	N51502113	N003023	N51502114	N726011	N003024	N51502185	N003092
Heaped capacity (l)		510	510	580	580	330	630	630	640
Struck capacity (l)		460	460	510	510	270	560	530	530
Overall weight (kg)		193	180	215	176	97	230	196	203
Height (mm)		770	770	770	770	542	770	795	795
Length (mm)		1014	-	1014	-	819	1014	-	951
Width (mm)		1080	1080	1200	1200	1220	1300	1300	1300
Depth (mm)	p5	940	1025	940	1025	719	940	967	884
Required machine equipment									
Cutting edge		No	No	No	No	No	No	No	No
E-RECO		No	No	No	No	No	No	No	No
Connection system		4-point	Euro	4-point	Euro	Universal Quick-attach	4-point	Euro	4-point

Machines compatibility								
1050R	-	-	-	-	X	-	-	-
1050R	-	-	-	-	X	-	-	-
1050R	-	-	-	-	X	-	-	-
1050R	-	-	-	-	X	-	-	-
1050RT	-	-	-	-	X	-	-	-
1050RT	-	-	-	-	X	-	-	-
1050RT	-	-	-	-	X	-	-	-
1350R NXT2	-	-	-	-	X	-	-	-
1350R NXT2	-	-	-	-	X	-	-	-
1350R NXT2	-	-	-	-	X	-	-	-
1350R NXT2	-	-	-	-	X	-	-	-
1350RT	-	-	-	-	X	-	-	-
1350RT	-	-	-	-	X	-	-	-
1350RT	-	-	-	-	X	-	-	-
AL230	X	X	X	X	-	X	-	-
AL320	X	X	X	X	-	X	-	-
AL330	X	X	X	X	-	X	-	-
AL420	-	X	X	X	-	X	-	-
AL430	-	X	X	X	-	X	-	-
AL530	-	-	-	-	-	-	X	-
AL550	-	-	-	-	-	-	X	X
AL550	-	-	-	-	-	-	X	X
MLA 2-25 H	X	X	X	X	-	X	-	-
MLA 3-25 H	X	X	X	X	-	X	-	-
MLA 3-25 H-C	X	X	X	X	-	X	-	-
MLA 4-50 H	-	X	X	X	-	X	-	-
MLA 4-50 H-C	-	X	X	X	-	X	-	-
MLA 5-50 H	-	-	-	-	-	-	X	-
MLA 5-60 H-Z	-	-	-	-	-	-	X	X
R105	-	-	-	-	X	-	-	-
R105	-	-	-	-	X	-	-	-
R105	-	-	-	-	X	-	-	-
R135 GEN:2	-	-	-	-	X	-	-	-
R135 GEN:2	-	-	-	-	X	-	-	-
R135 GEN:2	-	-	-	-	X	-	-	-
RT105	-	-	-	-	X	-	-	-
RT105	-	-	-	-	X	-	-	-
RT105	-	-	-	-	X	-	-	-
RT105	-	-	-	-	X	-	-	-
RT135	-	-	-	-	X	-	-	-
RT135	-	-	-	-	X	-	-	-
RT135	-	-	-	-	X	-	-	-

		BLM 1300/630	BLM 1300/630 EU	BLM 1300/630 EU	BLM 1380/430	BLM 1400/680	BLM 1400/680	BLM 1400/680	BLM 1400/680
Reference number		N004092	N51502115	N51502160	N736013	52799520	N51502186	N004093	N003093
Heaped capacity (l)		640	630	630	430	680	680	700	700
Struck capacity (l)		530	560	520	370	560	570	570	570
Overall weight (kg)		217	190	235	150	240	196	210	210
Height (mm)		795	770	775	602	775	795	795	795
Length (mm)		967	-	-	889	-	-	967	951
Width (mm)		1300	1300	1300	1380	1400	1400	1400	1400
Depth (mm)	p5	884	1025	998	816	988	-	884	884
Required machine equipment		✕	✕	✕	✕	✕	✕	✕	✕
Cutting edge		No	No	No	No	No	No	No	No
E-RECO		No	No	No	No	No	No	No	No
Connection system		Universal Quick-attach	Euro	Euro	Universal Quick-attach	4-point	Euro	Universal Quick-attach	4-point

Machines compatibility								
1050R	-	-	-	X	-	-	-	-
1050R	-	-	-	X	-	-	-	-
1050R	-	-	-	X	-	-	-	-
1050R	-	-	-	X	-	-	-	-
1050RT	-	-	-	X	-	-	-	-
1050RT	-	-	-	X	-	-	-	-
1050RT	-	-	-	X	-	-	-	-
1350R NXT2	-	-	-	X	-	-	-	-
1350R NXT2	-	-	-	X	-	-	-	-
1350R NXT2	-	-	-	X	-	-	-	-
1350R NXT2	-	-	-	X	-	-	-	-
1350RT	-	-	-	X	-	-	-	-
1350RT	-	-	-	X	-	-	-	-
1350RT	-	-	-	X	-	-	-	-
AL230	-	X	-	-	-	-	-	-
AL320	-	X	-	-	X	-	-	-
AL330	-	X	-	-	X	-	-	-
AL420	-	X	X	-	X	-	-	-
AL430	-	X	X	-	X	-	-	-
AL530	-	-	-	-	-	X	-	X
AL550	X	-	-	-	-	X	X	X
AL550	X	-	-	-	-	X	X	X
MLA 2-25 H	-	X	-	-	-	-	-	-
MLA 3-25 H	-	X	-	-	X	-	-	-
MLA 3-25 H-C	-	X	-	-	X	-	-	-
MLA 4-50 H	-	X	X	-	X	-	-	-
MLA 4-50 H-C	-	X	X	-	X	-	-	-
MLA 5-50 H	-	-	-	-	-	X	-	X
MLA 5-60 H-Z	X	-	-	-	-	X	X	X
R105	-	-	-	X	-	-	-	-
R105	-	-	-	X	-	-	-	-
R105	-	-	-	X	-	-	-	-
R135 GEN:2	-	-	-	X	-	-	-	-
R135 GEN:2	-	-	-	X	-	-	-	-
R135 GEN:2	-	-	-	X	-	-	-	-
RT105	-	-	-	X	-	-	-	-
RT105	-	-	-	X	-	-	-	-
RT105	-	-	-	X	-	-	-	-
RT105	-	-	-	X	-	-	-	-
RT135	-	-	-	X	-	-	-	-
RT135	-	-	-	X	-	-	-	-
RT135	-	-	-	X	-	-	-	-

		BLM 1400/680 EU	BLM 1420/300 QA	BLM 1500/730	BLM 1500/730	BLM 1500/730	BLM 1520/480	BLM 1650/1100	BLM 1650/1100
Reference number		N51502161	50810025	N004094	N003094	N51502187	N736014	N51502603	N51502562
Heaped capacity (l)		680	300	750	750	730	480	1100	1100
Struck capacity (l)		560	-	610	610	610	420	910	910
Overall weight (kg)		240	106	211	220	253	168	348	343
Height (mm)		775	500	795	795	795	602	823	823
Length (mm)		-	-	967	951	-	889	-	-
Width (mm)		1400	1422	1500	1500	1500	1520	1650	1650
Depth (mm)	p5	-	810	884	884	951	816	1224	1224
Required machine equipment		✕	✕	✕	✕	✕	✕	✕	✕
Cutting edge		No	No	No	No	No	No	No	No
E-RECO		No	No	No	No	No	No	No	No
Connection system		Euro	Universal Quick-attach	Universal Quick-attach	4-point	Euro	Universal Quick-attach	4-point	Euro

Machines compatibility								
1350R NXT2	-	-	-	-	-	X	-	-
1350R NXT2	-	-	-	-	-	X	-	-
1350R NXT2	-	-	-	-	-	X	-	-
1350R NXT2	-	-	-	-	-	X	-	-
1350RT	-	-	-	-	-	X	-	-
1350RT	-	-	-	-	-	X	-	-
1350RT	-	-	-	-	-	X	-	-
AL320	X	-	-	-	-	-	-	-
AL330	X	-	-	-	-	-	-	-
AL420	X	-	-	-	-	-	-	-
AL430	X	-	-	-	-	-	-	-
AL530	-	-	-	X	X	-	-	-
AL550	-	-	X	X	X	-	-	-
AL550	-	-	X	X	X	-	-	-
AL650	-	-	-	-	-	-	X	X
AL650	-	-	-	-	-	-	X	X
AL750	-	-	-	-	-	-	X	X
AL750	-	-	-	-	-	-	X	X
AL750	-	-	-	-	-	-	X	X
MLA 3-25 H	X	-	-	-	-	-	-	-
MLA 3-25 H-C	X	-	-	-	-	-	-	-
MLA 4-50 H	X	-	-	-	-	-	-	-
MLA 4-50 H-C	X	-	-	-	-	-	-	-
MLA 5-50 H	-	-	-	X	X	-	-	-
MLA 5-60 H-Z	-	-	X	X	X	-	-	-
MLA 6-65 H-Z	-	-	-	-	-	-	X	X
MLA 7-75 H-Z	-	-	-	-	-	-	X	X
MLA 7-75 H-Z	-	-	-	-	-	-	X	X
R134	-	X	-	-	-	-	-	-
R135 GEN:2	-	-	-	-	-	X	-	-
R135 GEN:2	-	-	-	-	-	X	-	-
R135 GEN:2	-	-	-	-	-	X	-	-
RT135	-	-	-	-	-	X	-	-
RT135	-	-	-	-	-	X	-	-
RT135	-	-	-	-	-	X	-	-

		BLM 1650/1100	BLM 1650/1100 WP	BLM 1650/1100 WP	BLM 1650/1100 WP	BLM 1680/530	BLM 1680/670	BLM 1760/790	BLM 1760/820
Reference number		N51502537	N51502563	N51502604	N51502533	N736015	N747011	N757013	N51502468
Heaped capacity (l)		810	1100	1100	1100	530	670	790	820
Struck capacity (l)		910	910	910	-	460	550	650	680
Overall weight (kg)		385	373	373	342	175	242	313	320
Height (mm)		823	823	823	810	602	606	711	711
Length (mm)		-	-	-	-	889	1023	1012	-
Width (mm)		1650	1650	1650	1650	1680	1680	1760	1760
Depth (mm)	p5	1224	1271	1271	1271	816	956	946	1020
Required machine equipment		X	X	X	X	X	X	X	X
Cutting edge		No	Bolt-on	Bolt-on	Bolt-on	No	No	No	No
E-RECO		No	No	No	No	No	No	No	No
Connection system		Universal Quick-attach	Euro	4-point	Universal Quick-attach	Universal Quick-attach	Universal Quick-attach	Universal Quick-attach	Universal Quick-attach

Machines compatibility								
1350R NXT2	-	-	-	-	X	-	-	-
1350R NXT2	-	-	-	-	X	-	-	-
1350R NXT2	-	-	-	-	X	-	-	-
1350R NXT2	-	-	-	-	X	-	-	-
1350RT	-	-	-	-	X	-	-	-
1350RT	-	-	-	-	X	-	-	-
1350RT	-	-	-	-	X	-	-	-
1650R	-	-	-	-	-	X	-	-
1650R	-	-	-	-	-	X	-	-
1650RT	-	-	-	-	-	X	-	-
1650RT	-	-	-	-	-	X	-	-
1650RT	-	-	-	-	-	X	-	-
1650RT	-	-	-	-	-	X	-	-
1900R NXT2	-	-	-	-	-	X	-	-
1900R NXT2	-	-	-	-	-	X	-	-
1900R NXT2	-	-	-	-	-	X	-	-
1950RT	-	-	-	-	-	X	-	-
1950RT	-	-	-	-	-	X	-	-
1950RT	-	-	-	-	-	X	-	-
2100V	-	-	-	-	-	X	-	X
2100V	-	-	-	-	-	X	-	X
2100VT	-	-	-	-	-	X	-	-
2100VT	-	-	-	-	-	X	-	-
2300V	-	-	-	-	-	-	X	X
2300V	-	-	-	-	-	-	X	X
2750V	-	-	-	-	-	-	X	-
2750V	-	-	-	-	-	-	X	-
AL650	X	X	X	X	-	-	-	-
AL650	X	X	X	X	-	-	-	-
AL750	X	X	X	X	-	-	-	-
AL750	X	X	X	X	-	-	-	-
AL750	X	X	X	X	-	-	-	-
MLA 6-65 H-Z	X	X	X	X	-	-	-	-
MLA 7-75 H-Z	X	X	X	X	-	-	-	-
MLA 7-75 H-Z	X	X	X	X	-	-	-	-
R135 GEN:2	-	-	-	-	X	-	-	-
R135 GEN:2	-	-	-	-	X	-	-	-
R135 GEN:2	-	-	-	-	X	-	-	-
R165	-	-	-	-	-	X	-	-
R165	-	-	-	-	-	X	-	-
R190 GEN:2	-	-	-	-	-	X	-	-
R190 GEN:2	-	-	-	-	-	X	-	-
R190 GEN:2	-	-	-	-	-	X	-	-
RT135	-	-	-	-	X	-	-	-
RT135	-	-	-	-	X	-	-	-
RT135	-	-	-	-	X	-	-	-
RT165	-	-	-	-	-	X	-	-
RT165	-	-	-	-	-	X	-	-
RT165	-	-	-	-	-	X	-	-
RT195 - NEW	-	-	-	-	-	X	-	-
RT195 - NEW	-	-	-	-	-	X	-	-
RT195 - NEW	-	-	-	-	-	X	-	-
V210	-	-	-	-	-	X	-	X
V210	-	-	-	-	-	X	-	X
V230	-	-	-	-	-	-	X	X
V230	-	-	-	-	-	-	X	X
V275	-	-	-	-	-	-	X	-
V275	-	-	-	-	-	-	X	-
VT210	-	-	-	-	-	X	-	-
VT210	-	-	-	-	-	X	-	-
1900R OLD	-	-	-	-	-	X	-	-
2200R OLD	-	-	-	-	-	-	-	X
2700V NXT2 OLD	-	-	-	-	-	-	X	-
R220 OLD	-	-	-	-	-	-	-	X
R220 OLD	-	-	-	-	-	-	-	X

	BLM 1650/1100	BLM 1650/1100 WP	BLM 1650/1100 WP	BLM 1650/1100 WP	BLM 1680/530	BLM 1680/670	BLM 1760/790	BLM 1760/820
V270 OLD	-	-	-	-	-	-	X	-
V270 OLD	-	-	-	-	-	-	X	-

		BLM 1800/1200	BLM 1800/1200	BLM 1800/1200	BLM 1800/1200 WP	BLM 1800/1200 WP	BLM 1800/1200 WP	BLM 1850/1100	BLM 1850/830
Reference number		N51502605	N51502564	N51502536	N51502532	N51502565	N51502606	N51502037	N757014
Heaped capacity (l)		1200	1200	1200	1200	1200	1200	1100	830
Struck capacity (l)		1000	1000	1000	-	1000	1000	900	680
Overall weight (kg)		369	364	385	365	390	390	360	315
Height (mm)		823	823	823	810	823	823	827	711
Length (mm)		-	-	-	-	-	-	-	1012
Width (mm)		1800	1800	1800	1800	1800	1800	1850	1850
Depth (mm)	p5	1224	1224	1224	1271	1271	1271	1102	946
Required machine equipment		✕	✕	✕	✕	✕	✕	✕	✕
Cutting edge		No	No	No	Bolt-on	Bolt-on	Bolt-on	No	No
E-RECO		No	No	No	No	No	No	No	No
Connection system		4-point	Euro	Universal Quick-attach	Universal Quick-attach	Euro	4-point	Universal Quick-attach	Universal Quick-attach

Machines compatibility								
2100V	-	-	-	-	-	-	-	X
2100V	-	-	-	-	-	-	-	X
2100VT	-	-	-	-	-	-	X	-
2100VT	-	-	-	-	-	-	X	-
2300V	-	-	-	-	-	-	-	X
2300V	-	-	-	-	-	-	-	X
2300VT	-	-	-	-	-	-	X	-
2300VT	-	-	-	-	-	-	X	-
2750VT	-	-	-	-	-	-	X	-
2750VT	-	-	-	-	-	-	X	-
AL650	X	X	X	X	X	X	-	-
AL650	X	X	X	X	X	X	-	-
AL750	X	X	X	X	X	X	-	-
AL750	X	X	X	X	X	X	-	-
AL750	X	X	X	X	X	X	-	-
MLA 6-65 H-Z	X	X	X	X	X	X	-	-
MLA 7-75 H-Z	X	X	X	X	X	X	-	-
MLA 7-75 H-Z	X	X	X	X	X	X	-	-
V210	-	-	-	-	-	-	-	X
V210	-	-	-	-	-	-	-	X
V230	-	-	-	-	-	-	-	X
V230	-	-	-	-	-	-	-	X
VT210	-	-	-	-	-	-	X	-
VT210	-	-	-	-	-	-	X	-
VT230	-	-	-	-	-	-	X	-
VT230	-	-	-	-	-	-	X	-
VT275	-	-	-	-	-	-	X	-
VT275	-	-	-	-	-	-	X	-
2700V NXT2 OLD	-	-	-	-	-	-	-	X
RT185 OLD	-	-	-	-	-	-	X	-
RT185 OLD	-	-	-	-	-	-	X	-
RT215 OLD	-	-	-	-	-	-	X	-
V270 OLD	-	-	-	-	-	-	-	X
V270 OLD	-	-	-	-	-	-	-	X

		BLM 1850/860	BLM 1950/1300	BLM 1950/1300	BLM 1950/1300	BLM 1950/1300 WP	BLM 1950/1300 WP	BLM 1950/1300 WP	BLM 2080/1250
Reference number		N51502469	N51502566	N51502607	N51502535	N51502567	N51502608	N51502531	N51502076
Heaped capacity (l)		860	1300	1300	1300	1300	1300	1300	1250
Struck capacity (l)		710	1080	1080	1080	1080	1080	1080	1020
Overall weight (kg)		330	401	391	405	430	430	449	378
Height (mm)		711	823	823	823	823	823	823	827
Length (mm)		-	-	-	-	-	-	-	-
Width (mm)		1850	1950	1950	1950	1950	1950	1950	2080
Depth (mm)	p5	1020	1224	1224	1224	1271	1271	1271	1102
Required machine equipment		X	X	X	X	X	X	X	X
Cutting edge		No	No	No	No	Bolt-on	Bolt-on	Bolt-on	No
E-RECO		No	No	No	No	No	No	No	No
Connection system		Universal Quick-attach	Euro	4-point	Universal Quick-attach	Euro	4-point	Universal Quick-attach	Universal Quick-attach

Machines compatibility								
2300V	X	-	-	-	-	-	-	-
2300V	X	-	-	-	-	-	-	-
2750V	X	-	-	-	-	-	-	X
2750V	X	-	-	-	-	-	-	X
3300V NXT2	-	-	-	-	-	-	-	X
3300V NXT2	-	-	-	-	-	-	-	X
AL650	-	X	X	X	X	X	X	-
AL650	-	X	X	X	X	X	X	-
AL750	-	X	X	X	X	X	X	-
AL750	-	X	X	X	X	X	X	-
AL750	-	X	X	X	X	X	X	-
MLA 6-65 H-Z	-	X	X	X	X	X	X	-
MLA 7-75 H-Z	-	X	X	X	X	X	X	-
MLA 7-75 H-Z	-	X	X	X	X	X	X	-
V230	X	-	-	-	-	-	-	-
V230	X	-	-	-	-	-	-	-
V275	X	-	-	-	-	-	-	X
V275	X	-	-	-	-	-	-	X
2200R OLD	X	-	-	-	-	-	-	-
R220 OLD	X	-	-	-	-	-	-	-
R220 OLD	X	-	-	-	-	-	-	-
R260 OLD	X	-	-	-	-	-	-	X

		BLM 2140/1290	BLM 2150/1420	BLM 2150/1420	BLM 2150/1420	BLM 2150/1420 WP	BLM 2150/1420 WP	BLM 2150/1420 WP	BLM 2350/1370
Reference number		N700248	N51502609	N51502568	N51502534	N51502530	N51502610	N51502569	N51502038
Heaped capacity (l)		1290	1430	1430	1430	1430	1430	1430	1370
Struck capacity (l)		1040	1190	1190	1190	1190	1190	1190	1150
Overall weight (kg)		382	419	429	437	483	465	465	382
Height (mm)		827	823	823	823	823	823	823	827
Length (mm)		1102	-	-	-	-	-	-	-
Width (mm)		2140	2150	2150	2150	2150	2150	2150	2350
Depth (mm)	p5	1030	1224	-	1224	1271	1271	1271	1102
Required machine equipment		X	X	X	X	X	X	X	X
Cutting edge		No	No	No	No	Bolt-on	Bolt-on	Bolt-on	No
E-RECO		No	No	No	No	No	No	No	No
Connection system		Universal Quick-attach	4-point	Euro	Universal Quick-attach	Universal Quick-attach	4-point	Euro	Universal Quick-attach

Machines compatibility								
2750VT	-	-	-	-	-	-	-	X
2750VT	-	-	-	-	-	-	-	X
3300V NXT2	X	-	-	-	-	-	-	-
3300V NXT2	X	-	-	-	-	-	-	-
AL750	-	X	X	X	X	X	X	-
AL750	-	X	X	X	X	X	X	-
AL750	-	X	X	X	X	X	X	-
MLA 7-75 H-Z	-	X	X	X	X	X	X	-
MLA 7-75 H-Z	-	X	X	X	X	X	X	-
VT275	-	-	-	-	-	-	-	X
VT275	-	-	-	-	-	-	-	X
RT215 OLD	-	-	-	-	-	-	-	X

TABLE SYMBOL					
X	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition

MANITOU
HANDLING YOUR WORLD

Head Office
B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com

This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.
MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes