

Technical sheet :

# **LIGHT MATERIAL BUCKET**

---



---

## **Technical characteristics**

- Suited for bulk materials with a density <math>< 0.8 \text{ t/m}^3 / 50 \text{ lb/ft}^3</math>.
- 400 HB cutting edge for more resistance.

[The 3D picture at the top of this page is the reference BLM 1500 / 770 - 52706270].

## **Customer benefits**

- High capacity for efficient loading applications.

<b>Technical characteristics</b>		<b>BLM 1500 / 770</b>	
Distance to center of gravity (mm)		481	
<b>Capacities</b>			
Capacity (kg)		610	
Heaped capacity (l)		763	
Struck capacity (l)		613	
<b>Weight</b>			
Overall weight (kg)		209	
<b>Weight and dimensions</b>			
Overall height (mm)	h17	775	
Overall length (mm)	l1	1218	
Width (mm)		1500	
<b>Working Parameters</b>			
Required machine equipment		✕	

<b>Machines compatibility</b>		<b>BLM 1500 / 770</b>	
All-Tach®		52706270	
4 point Carriage		52723640	
Euro Carriage		52723641	
AL530		X	
MLA 5-50 H		X	
ULM 412 H		X	
ULM 415 H		X	

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



**Head Office**

B.P. 249 - 430 rue de l'Aubinière  
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes