

LIGHT MATERIAL BUCKET WITH WEAR PLATE (COMPACT MACHINES)

BUCKETS



GEHL®

Customer benefits

- Wide range of bucket capacities.
- High capacities for efficient loading applications.







Technical characteristics

- Suited for bulk materials with a density $< 1\text{t/m}^3$.
- 400HB cutting edge for more resistance.

MANITOU GROUP ATTACHMENTS

| Capacities | | BLM WP 1650 / 1100 | BLM WP 1800 / 1200 | BLM WP 1950 / 1300 | BLM WP 2150 / 1420 |
|-----------------------|-----|--------------------|--------------------|--------------------|--------------------|
| Capacity (kg) | | 1100 | 1200 | 1300 | 1420 |
| Heaped capacity (l) | | 1100 | 1200 | 1300 | 1420 |
| Weight | | | | | |
| Overall weight (kg) | | 342 | 365 | 387 | 417 |
| Weight and dimensions | | | | | |
| Overall height (mm) | h17 | 810 | 810 | 810 | 810 |
| Width (mm) | | 1650 | 1800 | 1950 | 2150 |
| Depth (mm) | p5 | 1271 | 1271 | 1271 | 1271 |
| Working Parameters | | | | | |
| Machine Equipment | | × | × | × | × |

| Machines compatibility | BLM WP 1650 / 1100 | BLM WP 1800 / 1200 | BLM WP 1950 / 1300 | BLM WP 2150 / 1420 |
|------------------------|--------------------|--------------------|--------------------|--------------------|
| All-Tach® | N51502533 | N51502532 | N51502531 | N51502530 |
| 4 point Carriage | N51502604 | N51502606 | N51502608 | N51502610 |
| Euro Carriage | N51502563 | N51502565 | N51502567 | N51502569 |
| AL650 | X | X | X | - |
| AL750 | X | X | X | X |
| ALT750 | X | X | X | X |
| MLA 6-65 H-Z | X | X | X | - |
| MLA-T 516-75 H | X | X | X | X |
| ALT750 OLD | X | X | X | X |
| ALT750 OLD | X | X | X | X |

| TABLE SYMBOL | | | | | |
|---|----------------------------|---|-------------------------|---|---|
|  | No predisposition required |  | Hydraulic line |  | Return piping to hydraulic oil tank |
|  | Electric predisposition |  | Platform predisposition |  | Tyre handler, cylinder handler predisposition |



GEHL®

Siège Social

P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095

Tel: (262) 334-9461 - Fax: (262) 338-7517

www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend