

Technical sheet :

# MATERIAL BASKET



## Customer benefits

- Transport and storage facilitated by its foldability.
- Efficient and inexpensive solution for the safe movement of materials in all types of application, environment and meteorology.
- Front opening facilitating pallet loading.

## Technical characteristics

- Reach of 1.2 m and capacity of 1000 kg / 2205 ft.

[The 3D photo at the top of this page is the reference MB 2000 / 1000 - 52596600].

Technical characteristics		MB 2000 / 1000
Distance to center of gravity (mm)		694
Capacities		
Capacity (kg)		1000
Weight		
Overall weight (kg)		400
Weight and dimensions		
Overall height (mm)	h17	1215
Overall length (mm)	l1	1632
Width (mm)		2056
Depth (mm)	p5	1120
Working Parameters		
Machine Equipment		✕

Machines compatibility		MB 2000 / 1000
Reference number		52596600
MLT 630-115		X
MLT 630-115 V		X
MLT 630-115 V CP		X
MLT 635-130 PS+		X
MLT 635-140 V+		X
MLT 730-115 V		X
MLT 730-115 V CP		X
MLT 733-115 LSU		X
MLT 737-130 PS+		X
MLT 741-130 PS+		X
MLT 741-140 V+		X
MLT 841-145 PS+		X
MLT 850-145 V+		X
MLT 937-115		X
MLT 940-140 V+		X
MLT 1041-145 PS+L		X
MLFX 625-75 H		X
MLFX 735 T LSU		X
MLFX 737-130 PS+		X
MLFX 741 T LSU		X
MLFX 841 - 145 PS+		X
MLFX 850-145 V+		X
MLFX 1041-145 PS+L		X
MT 625 e		X
MT 625 H		X
MT 625 H Comfort		X
MT 625 HA		X
MT 730 H		X
MT 735 75D ST5		X
MT 930 H		X
MT 930 HA		X
MT 935 75D ST5		X
MT 1135 75 D		X
MT 1135 H 100D		X
MT 1335 75D ST5		X
MT 1335 100D ST5		X
MT 1335 H 75D ST5		X
MT 1335 H 100D ST5		X
MT 1440 A ST5		X
MT 1440 easy ST5		X
MT 1440 HA ST5		X
MT 1440 ST5		X
MT 1840 A 100D ST5 S1		X
MT 1840 easy ST5		X
MT 1840 HA		X
MT 1840 ST5		X
MTFX 735		X
MTFX 1135		X
MTFX 1440		X
MTFX 1440 A		X
MTFX 1840		X
MTFX 1840 A		X
MLT 630-105 ST4 <span style="background-color: #cccccc; border: 1px solid #000; border-radius: 3px; padding: 0 2px;">OLD</span>		X
MLT 630-105 V CP ST4 <span style="background-color: #cccccc; border: 1px solid #000; border-radius: 3px; padding: 0 2px;">OLD</span>		X
MLT 630-105 V ST4 <span style="background-color: #cccccc; border: 1px solid #000; border-radius: 3px; padding: 0 2px;">OLD</span>		X
MLT 635-130 PS+ ST4 <span style="background-color: #cccccc; border: 1px solid #000; border-radius: 3px; padding: 0 2px;">OLD</span>		X
MLT 635-140 V+ ST4 <span style="background-color: #cccccc; border: 1px solid #000; border-radius: 3px; padding: 0 2px;">OLD</span>		X
MLT 730-115 V CP ST4 <span style="background-color: #cccccc; border: 1px solid #000; border-radius: 3px; padding: 0 2px;">OLD</span>		X
MLT 730-115 V ST4 <span style="background-color: #cccccc; border: 1px solid #000; border-radius: 3px; padding: 0 2px;">OLD</span>		X
MLT 733-115 <span style="background-color: #cccccc; border: 1px solid #000; border-radius: 3px; padding: 0 2px;">OLD</span>		X
MLT 733-115 LSU ST4 <span style="background-color: #cccccc; border: 1px solid #000; border-radius: 3px; padding: 0 2px;">OLD</span>		X
MLT 733-115 ST4 <span style="background-color: #cccccc; border: 1px solid #000; border-radius: 3px; padding: 0 2px;">OLD</span>		X
MLT 737-130 PS+ ST4 <span style="background-color: #cccccc; border: 1px solid #000; border-radius: 3px; padding: 0 2px;">OLD</span>		X
MLT 741-140 V+ ST4 <span style="background-color: #cccccc; border: 1px solid #000; border-radius: 3px; padding: 0 2px;">OLD</span>		X

Machines compatibility	MB 2000 / 1000
MLT 940-140 V+ ST4 <b>OLD</b>	X
MLFX 737-130 PS+ <b>OLD</b>	X
MLFX 741-140 V+ S1 <b>OLD</b>	X
MLFX 840-140 PS+ <b>OLD</b>	X
MLFX 1040-140 PS+ L <b>OLD</b>	X
MT 733 Easy <b>OLD</b>	X
MT 933 Easy <b>OLD</b>	X
MT 1033 easy <b>OLD</b>	X
MT 1135 easy ST5 <b>OLD</b>	X
MT 1135 H easy ST5 <b>OLD</b>	X
MT 1135 HA Easy ST5 <b>OLD</b>	X
MT 1135 ST5 <b>OLD</b>	X
MT 1335 <b>OLD</b>	X
MT 1335 easy ST5 <b>OLD</b>	X
MT 1335 H easy ST5 <b>OLD</b>	X
MT 1335 HA easy ST5 <b>OLD</b>	X
MT 1335 ST5 <b>OLD</b>	X
MT 1440 <b>OLD</b>	X
MT 1840 HA <b>OLD</b>	X
MT-X 733 <b>OLD</b>	X

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes