

PALLET FORKS CARRIAGE (COMPACT MACHINES)

ON FORK HANDLING SOLUTIONS



GEHL®

Customer benefits

- A universal attachment for pallet handling.

Technical characteristics

- Wide carriage with backrest for more stability during travel.
- Standardized FEM forks, side slidable.

MANITOU GROUP ATTACHMENTS

| Capacities | | CAT 915 / 800 | CAT 920 / 1000 | CAT 920 / 1100 | CAT 920 / 1200 | CAT 1200 / 1200 | CAT 1210 / 1200 (b) | CAT 1220 / 1000 (a) | CAT 1220 / 1100 (a) | CAT 1220 / 1200 (a) |
|-----------------------------------|-----|---------------|----------------|----------------|----------------|-----------------|---------------------|---------------------|---------------------|---------------------|
| Capacity (kg) | | 800 | 1000 | 1100 | 1200 | 1200 | 1200 | 1000 | 1100 | 1200 |
| Weight and dimensions | | | | | | | | | | |
| Overall height (mm) | h17 | 893 | 893 | 893 | 893 | 888 | 890 | 890 | 890 | 890 |
| Forks section X Forks length (mm) | s | 35.10 X 800 | 1000 | 1100 | 1200 | 1200 | 1200 | 1000 | 1100 | 1200 |
| Width (mm) | | 915 | 915 | 915 | 915 | 1212 | 1212 | 1212 | 1212 | 1212 |
| Depth (mm) | p5 | 1260 | 1160 | 1260 | 1360 | 1488 | 1350 | 1318 | 1318 | 1318 |
| Working Parameters | | | | | | | | | | |
| Machine Equipment | | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ |

| Maschinenkompatibilitäten | CAT 915 / 800 | CAT 920 / 1000 | CAT 920 / 1100 | CAT 920 / 1200 | CAT 1200 / 1200 | CAT 1210 / 1200 (b) | CAT 1220 / 1000 (a) | CAT 1220 / 1100 (a) | CAT 1220 / 1200 (a) |
|---------------------------|---------------|----------------|----------------|----------------|-----------------|---------------------|---------------------|---------------------|---------------------|
| All-Tach® Narrow | - | 52807868 | 52807867 | 52799512 | - | - | - | - | - |
| All-Tach® | - | N004019 | - | - | - | 52799516 | - | - | - |
| 4 point Carriage | - | 52813313 | 52796388 | 52799521 | - | 52799513 | - | - | - |
| Euro Carriage | - | 52807866 | 52799511 | - | - | 52799514 | - | - | - |
| 1050R | - | - | - | - | - | - | X | - | - |
| 1050RT | - | - | - | - | - | - | X | - | - |
| 1350R NXT2 | - | - | - | - | - | - | X | - | - |
| 1650R | - | - | - | - | - | - | - | X | X |
| 1650RT | - | - | - | - | - | - | - | X | X |
| 1950RT | - | - | - | - | - | - | - | X | X |
| 1950RT | - | - | - | - | - | - | - | X | X |
| 1950RT | - | - | - | - | - | - | - | X | X |
| 1950RT | - | - | - | - | - | - | - | X | X |
| 2700V NXT2 | - | - | - | - | - | - | - | X | X |
| 3300V NXT2 | - | - | - | - | - | - | - | X | X |
| 4200V | - | - | - | - | - | - | - | X | X |
| AL230 | - | X | X | - | - | - | - | - | - |
| AL320 | - | X | X | - | - | - | - | - | - |
| AL330 | - | X | X | - | - | - | - | - | - |
| AL420 | - | X | X | X | - | X | - | - | - |
| AL430 | - | X | X | X | - | X | - | - | - |
| AL530 | - | - | - | - | - | X | - | - | - |
| AL650 | - | - | - | - | X | - | - | - | - |
| AL750 | - | - | - | - | X | - | - | - | - |
| MLA 2-25 H | - | X | X | - | - | - | - | - | - |
| MLA 3-25 H | - | X | X | - | - | - | - | - | - |
| MLA 3-25 H-C | - | X | X | - | - | - | - | - | - |
| MLA 4-50 H | - | X | X | X | - | X | - | - | - |
| MLA 4-50 H-C | - | X | X | X | - | X | - | - | - |
| MLA 5-50 H | - | - | - | - | - | X | - | - | - |
| MLA 6-65 H-Z | - | - | - | - | X | - | - | - | - |
| R165 | - | - | - | - | - | - | - | X | X |
| RT105 | - | - | - | - | - | - | X | - | - |
| RT165 | - | - | - | - | - | - | - | X | X |
| RT195 - NEW | - | - | - | - | - | - | - | X | X |
| RT195 - NEW | - | - | - | - | - | - | - | X | X |
| RT195 - NEW | - | - | - | - | - | - | - | X | X |
| V330 GEN:2 | - | - | - | - | - | - | - | X | X |
| V330 GEN:2 | - | - | - | - | - | - | - | X | X |
| AL140 OLD | - | X | X | - | - | - | - | - | - |
| AL340 OLD | - | - | X | X | - | - | - | - | - |
| AL440 OLD | - | - | - | - | - | X | - | - | - |
| MLA 1-25 H OLD | - | X | X | - | - | - | - | - | - |
| MLA 3-35 H OLD | - | - | X | X | - | - | - | - | - |
| MLA 4-50 H OLD | - | X | - | - | - | X | - | - | - |

| TABELLE DER SYMBOLE | | | | | |
|---------------------|---------------------------------|--|----------------------------|--|---|
| | Keine Vorbereitung erforderlich | | Hydraulikleitung | | Rückföhrleitung zum Hydrauliköltank |
| | Elektrischer Anschluss | | Arbeitsböhnen-Vorbereitung | | Vorbereitung für Reifenklammer, Zylinderklammer |



GEHL®

Siège Social

P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095

Tel: (262) 334-9461 - Fax: (262) 338-7517

www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend