Technical sheet :

PLATFORM WITH DISMOUNTABLE FOPS ROOF



Customer benefits

- Full safety in people lifting.

- Solution designed for tunneling/mining applications where operator protection is required.

- Dismountable roof the platform can be used for standard applications when protection is not required.

- Fork sleeves for yard handing.

Technical characteristics

- Platform fitted with a protection roof designed according to FOPS-1 standard.
- Legally approved for 3 persons.
- Dismountable roof.
- 90°/90° rotation.
- 3 m / 10 ft wide basket, non extendable.
- Fork sleeves: 238 mm x 100 mm / 9 in x 4 in.
- Access: sliding bar.



PLATFORM WITH DISMOUNTABLE FOPS ROOF Created on July 24, 2025 at 2:21 AM UTC

Technical characteristics		PST 3000 / 1000
Capacity including people (kg)		1000
Number of people		3
Weight		
Overall weight (kg)		1105
Weight and dimensions		
Overall height (mm)	h17	2140
Overall length (mm)	11	2375
Width (mm)		3190
Working Parameters		
Required machine equipment		
Rotation 1 (°)		90
Rotation 2 (°)		90

Machines compatibility	PST 3000 / 1000
Reference number E-RECO	52719263
MRT 1645 75	x
MRT 1645 115	x
MRT 1845 75	x
MRT 1845 115	x
MRT 2145 115	x
MRT 2260	x
MRT 2260 e	x
MRT 2545 115	x
MRT 2570	x
MRT 2660	x
MRT 2660 e	x
MRT 3060	x
MRT 3570	x
MRT 3570 ES	x
MRT-X 1645	x
MRT-X 1845	x
MRT-X 2145	x
MRT-X 2260	x
MRT-X 2545	x
MRT-X 2570	x
MRT-X 2660	x
MRT-X 3060	x
MRT-X 3570	x
MRT-X 3570 ES	Х

TABLE SYMBOL								
\times	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank			
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition			



Head Office B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes