Technical sheet:

POT CLAMP (COMPACT MACHINES)



Customer benefits

- Makes the handling of pots and plants easy and efficient.
- Efficiently replaces forks, jibs or human strength.

Technical characteristics

- Articulated handles for a smooth pot clamping.
- Adjustable pressure limiter to prevent from damaging fragile pots (terracotta).



		, , , , , , , , , , , , , , , , , , ,
Technical characteristics		CLP 1000 / 800
Distance to center of gravity (mm)		350
Capacities		
Capacity (kg)		800
Weight		
Overall weight (kg)		109
Weight and dimensions		
Overall height (mm)	h17	507
Overall length (mm)	11	1106
Width (mm)		686
Minimum diameter / Maximum diameter (mm)		400 / 1050
Working Parameters		
Required machine equipment		
Minimum opening (mm)		400
Maximum opening (mm)		1000

Machines compatibility	CLP 1000 / 800
All-Tach® Narrow	N51502717
All-Tach®	N51502716
4 point Carriage	52742066
Euro Carriage	52742067
AL230	x
AL320	x
AL330	х
AL420	x
AL430	х
AL530	х
AL650	х
AL750	x
GCT 3-14	х
GCT 3-14 +	х
MLA 2-25 H	х
MLA 3-25 H	х
MLA 3-25 H-C	х
MLA 4-50 H	х
MLA 4-50 H-C	х
MLA 5-50 H	х
MLA 6-65 H-Z	х
ULM 412 H	х
ULM 412 H	x
ULM 415 H	x
ULM 415 H	x
MLA 1-25 H OLD	х
MLA 3-35 H OLD	х
MLA 4-50 H OLD	x

TABLE SYMBOL								
×	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank			
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition			





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes