

Technical sheet :

R-EVOLUTION TILTING FORK CARRIAGE




Customer benefits

- Easy handling of long loads in narrow spaces.
- Space saving: better pallet management= less storage space used.
- Reduce machine movements & maneuvers = Fuel consumption savings.
- Safety: constant monitoring of the load's weight, angle & position ; adaptive overload control according to the load's position; no forward tilting if rotation > 120° and boom lifted over 3m high.
- Cost saving: limits machine movements & maneuvers = lower fuel consumption.
- Space saving: better pallet management= less storage space used.

Technical characteristics

- Major increase of your MRT's functionality thanks to a continuous 360° fork rotation.
- 2 capacities: Up to 5000 kg frontal (+/- 15°) and up to 2500 kg rotated.
- Note: road circulation kit mandatory in Germany and Italy on MRT Vision+. Contact your dealer.
[The 3D picture at the top of this page is the reference CAT 1200 / 5000 R B - 52629990].

| Technical characteristics | | CAT 1200 / 5000 R B |
|---------------------------------------|-----|---|
| Distance to center of gravity (mm) | | 263 |
| Capacities | | |
| Max. capacity in front (15°/15°) (kg) | | 5000 |
| Max Capacity in Rotation (360°) (kg) | | 2500 |
| Weight | | |
| Overall weight (kg) | | 680 |
| Weight and dimensions | | |
| Overall height (mm) | h17 | 1130 |
| Overall length (mm) | l1 | 2208 |
| Overall width (mm) | b1 | 1420 |
| Working Parameters | | |
| Machine Equipment | |  |
| Rotation 1 (°) | | 360 |
| Fork spread minimum (mm) | b5 | 315 |
| Fork spread maximum (mm) | b5 | 1225 |
| Available fork dimensions | | |
| 125 x 50 x 1200 | | 52629990 |

| Machines compatibility | CAT 1200 / 5000 R B |
|-------------------------|---------------------|
| Reference number E-RECO | 52629990 |
| MRT 2260 | X |
| MRT 2260 e | X |
| MRT 2570 | X |
| MRT 2660 | X |
| MRT 2660 e | X |
| MRT 3060 | X |
| MRT 3570 | X |
| MRT 3570 ES | X |
| MRT-X 2260 | X |
| MRT-X 2570 | X |
| MRT-X 2660 | X |
| MRT-X 3060 | X |
| MRT-X 3570 | X |
| MRT-X 3570 ES | X |

| TABLE SYMBOL | | | | | |
|---|----------------------------|---|-------------------------|---|---|
|  | No predisposition required |  | Hydraulic line |  | Return piping to hydraulic oil tank |
|  | Electric predisposition |  | Platform predisposition |  | Tyre handler, cylinder handler predisposition |



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes