Technical sheet:

ROUND BALE CLAMP (COMPACT MACHINES)



Technical characteristics

- Can be used for square bales.
- Synchronized arms with 4 forged teeth each.

[The 3D picture at the top of this page is the reference CLBR 2x2 / 800 - N51502631].

Customer benefits

- Attachment designed for the handling of round bales.
- · Allows an easy and clean handling



Distance to center of gravity (mm) Capacities Capacity (kg) Weight Overall weight (kg) Soverall height (mm) Overall length (mm) If Soverall length (mm			
Capacities 800 Capacity (kg) 800 Weight 150 Overall weight (kg) 150 Weight and dimensions 69 Overall height (mm) 11 910 Width (mm) 1990 Working Parameters 869 Teeth / Fingers 2 / 2 Minimum opening (mm) 780 Maximum opening (mm) 1583	Technical characteristics		CLBR 2x2 / 800
Capacity (kg) 800 Weight 150 Overall weight (kg) 150 Weight and dimensions 50 Overall height (mm) h17 869 Overall length (mm) 11 910 Width (mm) 1990 Working Parameters 869 Teeth / Fingers 2 / 2 Minimum opening (mm) 780 Maximum opening (mm) 1583	Distance to center of gravity (mm)		341
Weight Overall weight (kg) 150 Weight and dimensions Userall height (mm) h17 669 Overall length (mm) 11 910 1900 Width (mm) 1990<	Capacities		
Overall weight (kg) 150 Weight and dimensions 50 Overall height (mm) h17 869 Overall length (mm) 11 910 Width (mm) 1900 Working Parameters 50 Required machine equipment 50 Teeth / Fingers 2 / 2 Minimum opening (mm) 780 Maximum opening (mm) 1583	Capacity (kg)		800
Weight and dimensions 69 Overall height (mm) 11 910 Working Parameters 60 60 Required machine equipment 60 60 Teeth / Fingers 2 / 2 Minimum opening (mm) 780 Maximum opening (mm) 1583	Weight		
Overall height (mm) h17 869 Overall length (mm) 11 910 Width (mm) 1090 Working Parameters Feequired machine equipment \$\frac{1}{2}\$	Overall weight (kg)		150
Overall length (mm) 11 910 Width (mm) 1090 Working Parameters Feequired machine equipment \$\begin{align*} \text{Pringers} \\	Weight and dimensions		
Width (mm) 1090 Working Parameters Required machine equipment \$\begin{array}{c} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\	Overall height (mm)	h17	869
Working Parameters Required machine equipment Teeth / Fingers 2 / 2 Minimum opening (mm) Maximum opening (mm) 1583	Overall length (mm)	l1	910
Required machine equipment Feeth / Fingers 2 / 2 Minimum opening (mm) Maximum opening (mm) 1583	Width (mm)		1090
Teeth / Fingers 2 / 2 Minimum opening (mm) 780 Maximum opening (mm) 1583	Working Parameters		
Minimum opening (mm) 780 Maximum opening (mm) 1583	Required machine equipment		
Maximum opening (mm) 1583	Teeth / Fingers		2/2
	Minimum opening (mm)		780
Minimum forks spread (mm) b5 150	Maximum opening (mm)		1583
	Minimum forks spread (mm)	b5	150

Machines compatibility	CLBR 2x2 / 800
All-Tach® Narrow	N51502696
All-Tach®	N51502631
4 point Carriage	N51502632
Euro Carriage	N51502633
AL420	х
AL430	х
AL530	х
AL550	х
AL650	х
AL750	х
AL750	х
GCT 3-14	x
GCT 3-14 +	x
MLA 4-50 H	x
MLA 4-50 H-C	x
MLA 5-50 H	x
MLA 5-60 H-Z	x
MLA 6-65 H-Z	x
MLA-T 516-75 H	х
MLA-T 516-75 H	х
ULM 412 H	х
ULM 412 H	х
ULM 415 H	х
ULM 415 H	х
AL750 OLD	x
ALT750 OLD	х
ALT750 OLD	х
MLA 1-25 H OLD	х
MLA 3-35 H OLD	х
MLA 4-50 H OLD	x

TABLE SYMBOL								
\times	No predisposition required	88	Hydraulic line		Retum piping to hydraulic oil tank			
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition			





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes