

Technical sheet :

# **ROUND BALE CLAMP (COMPACT MACHINES)**

---



---

## **Technical characteristics**


- Can be used for square bales.
- Synchronized arms with 4 forged teeth each.

[The 3D picture at the top of this page is the reference CLBR 2x2 / 800 - N51502631].







## **Customer benefits**

---

- Attachment designed for the handling of round bales.
- Allows an easy and clean handling

Technical characteristics		CLBR 2x2 / 800	
Distance to center of gravity (mm)		341	
Capacities			
Capacity (kg)		800	
Weight			
Overall weight (kg)		150	
Weight and dimensions			
Overall height (mm)	h17	869	
Overall length (mm)	l1	910	
Width (mm)		1090	
Working Parameters			
Required machine equipment			
Teeth / Fingers		2 / 2	
Minimum opening (mm)		780	
Maximum opening (mm)		1583	
Minimum forks spread (mm)	b5	150	

Machines compatibility	CLBR 2x2 / 800	
All-Tach® Narrow	N51502696	
All-Tach®	N51502631	
4 point Carriage	N51502632	
Euro Carriage	N51502633	
AL420	X	
AL430	X	
AL530	X	
AL550	X	
AL650	X	
AL750	X	
AL750	X	
GCT 3-14	X	
GCT 3-14 +	X	
MLA 4-50 H	X	
MLA 4-50 H-C	X	
MLA 5-50 H	X	
MLA 5-60 H-Z	X	
MLA 6-65 H-Z	X	
MLA-T 516-75 H	X	
MLA-T 516-75 H	X	
ULM 412 H	X	
ULM 412 H	X	
ULM 415 H	X	
ULM 415 H	X	
AL750 <b>OLD</b>	X	
ALT750 <b>OLD</b>	X	
ALT750 <b>OLD</b>	X	
MLA 1-25 H <b>OLD</b>	X	
MLA 3-35 H <b>OLD</b>	X	
MLA 4-50 H <b>OLD</b>	X	

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes