Technical sheet :

SILAGE FACING BUCKET

Technical characteristics

- Synchronized hydraulic movements.
- Hydraulic motor integrated within the rotor for complete protection & extended lifespan.
- Reverse rotor rotation for optimized bucket filling.

  [The 3D picture at the top of this page is the reference CRS 2550/2000 - 52612540].

Customer benefits

- Loads and aerates silages in a single pass.
- Provids ready-to-use feed for direct distribution or mixer wagon use
- Clean silage pit face, limits secondary fermentation.
- Time-saving, a single attachment for the handling of silage and bulk feed.
- For corn silage and grass silage (short wisps).
  Not suitable for long wisp silage (10 cm / 4 in max.).

		BSCR 2100/1130	CRS 2550/2000
Reference number		52728902	52612540
Heaped capacity (l)		1130	2000
Overall weight (kg)		540	950
Length (mm)		1434	1687
Width (mm)		2136	2550
Closed grapple height (mm)	h33	1049	-
Opened grapple height (mm)	h34	1681	-
Depth (mm)	p5	1146	-
Required machine equipment			
Cutting edge		No	No
E-RECO		No	No
Connection system		Manitou	Manitou

Machines compatibility		
MLT 625-75 H	X	-
MLT 625 e	X	-
MLT 635-130 PS+ (S1)	-	X
MLT 635-130 PS+ (S2)	-	X
MLT 635-140 V+ (S1)	-	X
MLT 635-140 V+ (S2)	-	X
MLT 733-115	-	X
MLT 733-115 (S2)	-	X
MLT 733-115 LSU (S1)	-	X
MLT 737-130 PS+ (S1)	-	X
MLT 738-130 PS+ (S1)	-	X
MLT 741-130 PS+ (S1)	-	X
MLT 741-140 V+ (S1)	-	X
MLT 742-130 PS+ (S1)	-	X
MLT 742-140 V+ (S1)	-	X
MLT 841-145 PS+	-	X
MLT 940-140 V+ (S1)	-	X
MLT 940-140 V+ (S2)	-	X
MLT 1041-145 PS+L	-	X
MLT-X 625-75 H	X	-
MLT-X 732	-	X
MLT-X 735 T LSU	-	X
MLT-X 741 T LSU	-	X
MLT-X 841 - 145 PS+	-	X
MLT-X 1041-145 PS+L	-	X
MLT-X 737-130 PS+ OLD	-	X
MLT-X 741-140 V+ OLD	-	X

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition

Head Office
B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com

This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.
MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes