Technical sheet:

# SNOW BLOWER (COMPACT MACHINES)



### **Technical characteristics**

- Double stage turbine for more snow clearing efficiency.
- Mechanical adjustable chute orientation.
- Chimney rotation = 240°.
- Minimum/maximum hydraulic requirements = 70-120 l/min / 18-32 gpm.
- Frontal height = 740 mm / 29 in.

### **Customer benefits**

• Efficient snow removal & perfect surface cleaning in one go.



## SNOW BLOWER (COMPACT MACHINES) Created on November 9, 2025 at 2:38 AM UTC

Weight		SBL 1800	SBL 2100		
Overall weight (kg)		480	540		
Weight and dimensions					
Overall height (mm) h17		1500	2100		
Width (mm)		1800	2100		
Diameter 1 (mm)		450	450		
Diameter 2 (mm)		420	420		
Working Parameters					
Required machine equipment		# FE	# F.		

Machines compatibility	SBL 1800	SBL 2100
All-Tach®	N51502228	N51502229
1650R	X	
1650RT	X	
1950RT	Х	
1950RT	Х	
1950RT	Х	
1950RT	X	
2100V	Х	X
2100VT	Х	X
2300V	Х	X
2300VT	Х	Х
2750V	X	X
2750VT	X	X
3300V NXT2	·	X
R165	X	
RT165	X	
RT195 - NEW	X	
RT195 - NEW	X	
RT195 - NEW	X	
V210	X	X
V230	X	X
V275	X	X
V330 GEN:2		X
V330 GEN:2	·	X
VT210	X	X
VT230	X	X
VT275	X	X
1850RT <b>OLD</b>	X	
1900R <b>OLD</b>	Х	
2150RT <b>OLD</b>		X
2200R OLD		X
2600R <b>OLD</b>		X
2700V NXT2 OLD	Х	
4200V <b>OLD</b>		X
R220 <b>OLD</b>		X
R260 <b>OLD</b>		X
RT185 OLD	Х	
RT215 OLD		Х
V270 <b>OLD</b>	Х	

TABLE SYMBOL							
×		No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank	
	•	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition	





#### **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes