Technical sheet:

SNOW BLOWER (COMPACT MACHINES)



Customer benefits

- Efficient snow removal & perfect surface cleaning in one go.

Technical characteristics

- Double stage turbine for more snow clearing efficiency.
- Mechanical adjustable chute orientation.
- Chimney rotation = 240°.
- Minimum/maximum hydraulic requirements = 70-120 l/min / 18-32 gpm.
- Frontal height = 740 mm / 29 in.



SNOW BLOWER (COMPACT MACHINES) Created on August 31, 2025 at 7:30 AM UTC

Weight		SBL 1800 SBL 2100			
Overall weight (kg)		480 540			
Weight and dimensions					
Overall height (mm)	h17	1500	2100		
Width (mm)		1800	2100		
Diameter 1 (mm)		450	450		
Diameter 2 (mm)		420	420		
Working Parameters					
Required machine equipment					

1658R x - 1959RT x - 2100V x - 2300V x - 2300V x - 2300V x - 2300V x - 2575V x - x x - x x - x x - x x - x x - x x - x x - x x - x x - x x - x x -	Machines compatibility	SBL 1800	SBL 2100
1508T	All-Tach®	N51502228	N51502229
1950RT	1650R	Х	
1950RT	1650RT	X	
1950RT	1950RT	Х	TW.
1950RT	1950RT	X	
X	1950RT	Х	*
2100VT	1950RT	Х	
X	2100V	Х	X
X	2100VT	Х	X
2750V X X 2750VT X X 2750VT X X R105 X - R1165 X - RT195 - NEW X - RT195 - NEW X - RT195 - NEW X - V210 X X V230 X X V275 X X V330 GEN:2 - X V7210 X X V7230 X X V7210 X X V7275 X X V7276 X X V7275 X X V7276 X X V7276 X X V7270 X X V2200F (01) X X V2200F (01) X X V2200F (01) X X V2200F (01) X X	2300V	χ	X
X	2300VT	Х	Х
RESTRICT RESTRICT	2750V	Х	X
R165 x - RT195 - NEW X - RT195 - NEW X - RT195 - NEW X - V210 X X V220 X X V275 X X V330 GEN:2 - X V330 GEN:2 - X V7210 X X V7230 X X V7275 X X V7276 X X V7275 X X 1900 000 X - 2150RT 010 X - 2200R 010 X X 2200R 010 X X 4200V 010 X X 4200V 010 X X	2750VT	Х	Х
RT165 X - RT195 - NEW X - RT195 - NEW X - RT195 - NEW X - V210 X X V230 X X V275 X X V330 GEN:2 - X V7210 X X V7230 X X V7275 X X 1880RT GLD X X 1900R GLD X - 2215GRT GLD X X 2220GR GLD X X 22700V NXT2 GLD X X 4200V GLD X X 4200V GLD X X 4200V GLD X X	3300V NXT2		X
RT195 - NEW X - RT195 - NEW X - V210 X X V230 X X V275 X X V330 GEN:2 - X V330 GEN:2 - X V7210 X X V7230 X X V7210 X X V7230 X X V7215 X X 1850RT OLD X X 1900R OLD X X 2200R OLD - X 2200R OLD - X 2200R OLD - X 2400V OLD - X 4200V OLD - X	R165	Х	
RT195 - NEW X - V210 X X V230 X X V275 X X V330 GEN:2 - X V330 GEN:2 - X V7210 X X V7230 X X V7275 X X V800 GLD X X V150 GLD X X V2200 GLD - X V2200 GLD X X V2200 GLD X - V220 GLD X <	RT165	Х	
RT195 - NEW X - V210 X X V230 X X V275 X X V330 GEN:2 - X V7210 X X V7230 X X V7275 X X 1850RT OLD X X 1900R OLD X X 2250RR OLD - X 2200R OLD - X 2270V NXT2 OLD X - 4200V OLD - X 4200V OLD - X 4200V OLD - X 4200V OLD - X	RT195 - NEW	Х	
V210 X X V230 X X V275 X X V330 GEN:2 - X V7210 X X V7230 X X V7275 X X 1850RT OLD X - 1900R OLD X - 2250RT OLD - X 2250R OLD - X 2700V NXT2 OLD X - 4200V OLD - X 4200V OLD - X 4200V OLD - X	RT195 - NEW	Х	· ·
V230 X X V275 X X V330 GEN:2 - X V7210 X X V7230 X X V7275 X X 1850RT OLD X - 1900R OLD X - 2250RT OLD X X 2250R OLD - X 270V NXT2 OLD X - 4200V OLD - X 4200V OLD - X 4200V OLD - X	RT195 - NEW	Х	
x2755 x x x330 GEN:2 - x x1210 x x x1230 x x x1275 x x x1850RT OLD x - x1900R OLD x - x200R OLD x x x200R OLD x x x200V NXT2 OLD x - x420V OLD x x x220 OLD x x x220 OLD x x x220 OLD x x	V210	Х	X
X X X X X X X X X X	V230	X	X
N	V275	X	X
XT210 X X XT230 X X XT275 X X 1850RT OLD X - 1900R OLD X - 2150RT OLD X - 2200R OLD - X 2600R OLD - X 2700V NXT2 OLD X - 4200V OLD - X R220 OLD - X	V330 GEN:2		X
XT230 X X XT275 X X 1850RT OLD X - 1900R OLD X - 2150RT OLD X - 2200R OLD - X 2600R OLD - X 2700V NXT2 OLD X - 4200V OLD - X R220 OLD - X	V330 GEN:2		X
XT230 X X XT275 X X 1850RT OLD X - 1900R OLD X - 2150RT OLD X - 2200R OLD - X 2700V NXT2 OLD X - 4200V OLD X - 4200V OLD X X R220 OLD - X	VT210	X	X
1850RT OLD	VT230		X
1850RT OLD	VT275	X	X
1900R OLD	1850RT OLD		
2150RT OLD		Х	
2200R OLD	2150RT OLD		X
2600R OLD	2200R OLD		X
2700V NXT2	2600R OLD		
4200V OLD - x R220 OLD - x	2700V NXT2 OLD	X	
R220 OLD x			X
	R260 OLD		X
	RT185 OLD		
	RT215 OLD		X
	V270 OLD		

TABLE SYMBOL							
\times	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank		
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition		





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes