

# SNOW BLOWER (COMPACT MACHINES)

# SNOW REMOVING SOLUTIONS



# GEHL®



## Customer benefits

- Efficient snow removal & perfect surface cleaning in one go.







## Technical characteristics

- Double stage turbine for more snow clearing efficiency.
- Mechanical adjustable chute orientation.
- Chimney rotation = 240°.
- Minimum/maximum hydraulic requirements = 70-120 l/min.
- Frontal height = 740 mm.

**MANITOU GROUP ATTACHMENTS**

| Weight                |     | SBL 1800  | SBL 2100  |
|-----------------------|-----|---|---|
| Overall weight (kg)   |     | 480   | 540   |
| Weight and dimensions |     | SBL 1800  | SBL 2100  |
| Overall height (mm)   | h17 | 1500  | 2100  |
| Width (mm)            |     | 1800  | 2100  |
| Diameter 1 (mm)       |     | 450   | 450   |
| Diameter 2 (mm)       |     | 420   | 420   |
| Working Parameters    |     | SBL 1800  | SBL 2100  |
| Machine Equipment     |     |  |  |

| Machines compatibility | SBL 1800   | SBL 2100   |
|------------------------|------------|------------|
| All-Tach®              | N515 02228 | N515 02229 |
| 1650R                  | X          | -          |
| 1650RT                 | X          | -          |
| 1850RT                 | X          | -          |
| 1900R                  | X          | -          |
| 1950RT                 | X          | -          |
| 1950RT                 | X          | -          |
| 1950RT                 | X          | -          |
| 1950RT                 | X          | -          |
| 2100V                  | X          | X          |
| 2100VT                 | X          | X          |
| 2150RT                 | -          | X          |
| 2200R                  | -          | X          |
| 2300V                  | X          | X          |
| 2300VT                 | X          | X          |
| 2600R                  | -          | X          |
| 2700V NXT2             | X          | -          |
| 2750V                  | X          | X          |
| 2750VT                 | X          | X          |
| 3300V NXT2             | -          | X          |
| 4200V                  | -          | X          |
| R165                   | X          | -          |
| R220                   | -          | X          |
| R260                   | -          | X          |
| RT165                  | X          | -          |
| RT185                  | X          | -          |
| RT195 - NEW            | X          | -          |
| RT195 - NEW            | X          | -          |
| RT195 - NEW            | X          | -          |
| RT215                  | -          | X          |
| V210 - NEW             | X          | X          |
| V230 - NEW             | X          | X          |
| V275 - NEW             | X          | X          |
| V330 GEN:2             | -          | X          |
| V330 GEN:2             | -          | X          |
| VT210 - NEW            | X          | X          |
| VT230 - NEW            | X          | X          |
| VT275 - NEW            | X          | X          |
| V270 <b>OLD</b>        | X          | -          |

| TABLE SYMBOL  |                            |   |                         |   |   |
|---|----------------------------|---|-------------------------|---|---|
|  | No predisposition required |  | Hydraulic line          |  | Return piping to hydraulic oil tank           |
|  | Electric predisposition    |  | Platform predisposition |  | Tyre handler, cylinder handler predisposition |



# GEHL®

Siège Social  
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095  
Tel: (262) 334-9461 - Fax: (262) 338-7517  
[www.gehl.com](http://www.gehl.com)



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend