Technical sheet:

SNOW BLOWER (COMPACT MACHINES)



Technical characteristics

- Double stage turbine for more snow clearing efficiency.
- Mechanical adjustable chute orientation.
- Chimney rotation = 240°.
- Minimum/maximum hydraulic requirements = 70-120 l/min / 18-32 gpm.
- Frontal height = 740 mm / 29 in.

Customer benefits

• Efficient snow removal & perfect surface cleaning in one go.



SNOW BLOWER (COMPACT MACHINES) Created on December 14, 2025 at 2:38 AM UTC

Weight		SBL 1800	SBL 2100		
Overall weight (kg)		480	540		
Weight and dimensions					
Overall height (mm)	h17	1500	2100		
Width (mm)		1800	2100		
Diameter 1 (mm)		450	450		
Diameter 2 (mm)		420	420		
Working Parameters					
Required machine equipment		## Fc			

1508	Machines compatibility	SBL 1800	SBL 2100
1568FT X . 1958FT X . 1958FT X . 1958FT X . 1958FT X . 2100V X X 2100V X X 2300V X X 2300V X X 2250VT X X 2250VT X X 2250VT X X 8165 X X 8165 X X 81795 - NEW X - 817195 - NEW X X 8200 - NEW X X 8210 - CONTON X X 8210 - CONTO X X 8220 - CONTO <td< th=""><th>All-Tach®</th><th>N51502228</th><th>N51502229</th></td<>	All-Tach®	N51502228	N51502229
1950FT	1650R	X	
1950RT	1650RT	X	
1950RT	1950RT	X	TW.
1950RT	1950RT	X	
X	1950RT	X.	· ·
2300VT	1950RT	Х	
2300V X X 2300VT X X 2750VT X X 2750VT X X 23300VNT2 X X RIS X - RIT165 X - RT195 - NEW X - RT195 - NEW X - RT195 - NEW X - V230 X X V230 X X V230 X X V230 X X V2300-RP12 X X V3300 GEN:2 X X V3300 GEN:2 X X V7230 X X V7230 X X V7275 X X V7276 X X V7277 X X V1904 GUB X X V2004 NXT2 GUB X X V2004 NXT2 GUB X X<	2100V	X.	X
2300VT X X 2750V X X 2300V NXT2 - X 2300V NXT2 - X R165 X - R1795 - NEW X - V210 X X V220 X X V230 GEN-2 X X V320 GEN-2 X X V7210 X X V7220 X X V7210 X X V72210 X X V7225 X X V7230 X X V7230 X X V7230 X X V725 X X 1850T 0.0 X X 2250T 0.0 X X 2250T 0.0 X X	2100VT	Х	X
2750V X X 2750VT X X 2750VT X X 28300V NXT2 X 2 RT165 X - RT195 NEW X - RT195 NEW X - V210 X X V210 X X V2275 X X V230 GEN:2 - X V7275 X X V7280 X X V7210 X X V7230 X X V2200 X X V220	2300V	X	X
2750VT X X 3300V NXTZ C X R165 X - RT195 NEW X - RT195 NEW X - V210 X X V230 X X V275 X X V330 GEN:2 X X V330 GEN:2 X X V7210 X X V7230 X X V7230 X X V7230 X X V7245 X X V7257 X X V7210 X X V72210 X X V2220 X X V2	2300VT	Х	X
3300V NXT2	2750V	Х	X
R165 X - RT165 X - RT195 - NEW X - RT195 - NEW X - V210 X X V230 X X V275 X X V330 GEN:2 - X V7210 X X V7220 X X V7275 X X 1850RT 0.10 X X 1900R 0.10 X X 2250RR 0.10 X X 2260R 0.10 X X 2270W NTZ 0.10 X X 2220 0.	2750VT	Х	X
RT165 x - RT195 - NEW x - RT195 - NEW x - Y210 x - Y230 x x Y230 - X x x Y230 - CR12 x x Y330 GEN:2 - x x Y7210 X x x Y7230 X x x Y7275 X X x Y850FT GLD X X X Y150FT GLD X X X Y250FT GLD X X X Y260FT GLD X X X Y270FT GLD X X X Y280FT GLD X X	3300V NXT2		X
RT195 - NEW x - RT195 - NEW x - V210 x x V230 x x V275 x x V330 GEN:2 - x V7210 x x V7220 x x V7230 x x V7225 x x 1850FT 010 x x 1900R 010 x - 22150FT 010 x x 2220R 010 x x 2200R 010<	R165	Х	
RT195 - NEW X - V210 X X V230 X X V275 X X V330 GEN:2 - X V330 GEN:2 - X V7210 X X V7230- X X V1210- X X	RT165	Х	
RT195 - NEW X - V210 X X V230 X X V275 X X V330 GEN:2 - X V7210 X X V7230 X X V7275 X X 1850RT OLD X X 1900R OLD X - 2200R OLD - X 2270V NXT2 OLD X - 4200V OLD - X R220 OLD - X	RT195 - NEW	Х	
V210 X X V230 X X V275 X X V330 GEN:2 - X V330 GEN:2 - X V7210 X X V7230 X X V7275 X X 1850RT OLD X X 1900R OLD X X 2200R OLD - X 2270VV NYZ OLD X X 4200V OLD - X 4200 OLD -	RT195 - NEW	Х	· ·
V230 X X V275 X X V330 GEN:2 - X V210 X X V1230 X X V1275 X X 1850RT OLD X - 1900R OLD X - 2250RT OLD X X 2250R OLD X X 2270V NXT2 OLD X - 4200V OLD X X R220 OLD X X R220 OLD X X R220 OLD X X R220 OLD X X	RT195 - NEW	Х	
x275 x x x330 GEN:2 - x x7210 x x x7230 x x x7275 x x x8850T GLD x x x990R GLD x - x220QR GLD - x x270V NXT2 GLD x - x420V GLD x - x820 GLD x -	V210	Х	X
x330 GEN:2 - x x330 GEN:2 x x x1210 x x x1230 x x x1257 x x x1858T OLD x - x1900R OLD x - x200R OLD - x x200R OLD x - x200V NXT2 OLD x - x420V OLD x - x820 OLD x x x820 OLD x x x820 OLD x x x820 OLD x x	V230	Х	X
x330 GEN:2 x x x1210 x x x1230 x x x1275 x x x1850RT OLD x - x1900R OLD x - x2200R OLD x - x2600R OLD x - x2700V NXT2 OLD x - x4200V OLD x - x220 OLD	V275	Х	X
XT210 X X XT230 X X XT275 X X 1850RT OLD X - 1900R OLD X - 2150RT OLD X - 2200R OLD - X 2600R OLD X - 4200V OLD X - 4200V OLD X X 8220 OLD - X 8260 OLD - X	V330 GEN:2		X
XT230 X X XT275 X X 1850RT OLD X - 1900R OLD X - 2150RT OLD X - 2200R OLD - X 2600R OLD X - 4200V NXT2 OLD X - 4200V OLD X - 8220 OLD - X 8260 OLD - X	V330 GEN:2		
XT230 X X XT275 X X 1850RT OLD X - 1900R OLD X - 2150RT OLD X - 2200R OLD - X 2600R OLD X - 2700V NXT2 OLD X - 4200V OLD X - 8220 OLD - X 8260 OLD - X	VT210	Х	X
1850RT OLD X - 1900R OLD X - 2150RT OLD - X 2200R OLD - X 2600R OLD - X 2700V NXT2 OLD X - 4200V OLD - X R220 OLD - X R260 OLD - X	VT230		X
1850RT OLD X - 1900R OLD X - 2150RT OLD - X 2200R OLD - X 2600R OLD - X 2700V NXT2 OLD X - 4200V OLD - X R220 OLD - X R260 OLD - X	VT275		X
1900R OLD X 2150RT OLD - 2200R OLD - 2600R OLD - 2700V NXT2 OLD X 4200V OLD - 8220 OLD - 823 OLD - 824 OLD - 825 OLD - 826 OLD - 827 OLD - 828 OLD - 829 OLD - 820 OLD <td>1850RT OLD</td> <td></td> <td></td>	1850RT OLD		
2150RT OLD		X	
22200R OLD - X 2600R OLD - X 2700V NXT2 OLD X - 4200V OLD - X R220 OLD - X R260 OLD - X	2150RT OLD		X
2200V NXT2 OLD X 4200V OLD X R220 OLD - R220 OLD - R260 OLD -	2200R OLD	·	X
2700V NXT2 OLD X - 4200V OLD - X R220 OLD - X R260 OLD - X	2600R OLD		
4200V OLD - X R220 OLD - X R260 OLD - X	2700V NXT2 OLD	X	
R220 OLD - X			X
R260 OLD · X			
RT185 (OLD) X -	RT185 OLD		
	RT215 OLD		X
	V270 OLD		

TABLE SYMBOL							
X	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank		
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition		





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes