
Technical sheet:

# SQUARE WRAPPED BALE CLAMP (COMPACT MACHINES)



## **Technical characteristics**

- Strong frame & components for intensive applications.
- Telescopic cinematics-smooth movement & strong clamping capacity.
- Massive use of Teflon® pad.
- Limited maintenance.
- Standard pressure limiter.

## **Customer benefits**

- Tubular structure- no risk of damaging the film when moving wrapped bales.
- Wide clamp opening for big or multiple bale handling.
- Superior component protection.
- Multi-task: designed for wrapped square bales, can also handle standard square bales or round bales.



#### SQUARE WRAPPED BALE CLAMP (COMPACT MACHINES) Created on December 14, 2025 at 5:45 PM UTC

Capacities		CLBSW 2000 / 1000				
Capacity (kg)		1000				
Weight						
Overall weight (kg)		477				
Weight and dimensions						
Overall height (mm)	h17	679				
Arm length (mm)		1811				
Working Parameters						
Required machine equipment		<b>喜喜</b>				
Minimum opening (mm)		740				
Maximum opening (mm)		2090				

Machines compatibility	CLBSW 2000 / 1000		
All-Tach®	N51502694		
4 point Carriage Euro Carriage	N51502693		
Euro Carriage	N51502692		
AL650	x		
MLA 6-65 H-Z	x		
MLA-T 516-75 H	x		
MLA-T 516-75 H	x		
AL750 OLD	x		
ALT750 OLD	x		
ALT750 OLD	x		

TABLE SYMBOL							
×	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank		
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition		





#### **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes