

Technical sheet :

# STUMP AUGER BIT



## Technical characteristics

- The center point engages with the tree stump, drawing the blades down to the surface of the stump.
- Hexagonal output shaft. Size varies by model: 50mm or 70mm.

## Customer benefits

- Auger bit designed to remove stumps. Extend the capabilities of your planetary auger, enabling seamless stump grinding.

| Weight                | APD 200/860 STP/HX | APD 300/860 STP/HX |
|-----------------------|--------------------|--------------------|
| Overall weight (kg)   | 21.50              | 36                 |
| Dimensions            |                    |                    |
| Shaft diameter (mm)   | 50                 | 70                 |
| Weight and dimensions |                    |                    |
| Bit diameter (mm)     | 200                | 300                |
| Overall length (mm)   | 860                | 860                |
| Working Parameters    |                    |                    |
| Head type             | Hex                | Hex                |

| Machines compatibility | APD 200/860 STP/HX | APD 300/860 STP/HX |
|------------------------|--------------------|--------------------|
| Reference number       | 52886820           | 52886821           |
| 2100V                  | X                  | -                  |
| 2100VT                 | X                  | -                  |
| 2300V                  | X                  | -                  |
| 2300VT                 | X                  | -                  |
| 2750V                  | -                  | X                  |
| 2750VT                 | -                  | X                  |
| V210                   | X                  | -                  |
| V230                   | X                  | -                  |
| V275                   | -                  | X                  |
| VT210                  | X                  | -                  |
| VT230                  | X                  | -                  |
| VT275                  | -                  | X                  |

## TABLE SYMBOL

|   |                            |   |                         |   |   |
|---|----------------------------|---|-------------------------|---|---|
|  | No predisposition required |  | Hydraulic line          |  | Return piping to hydraulic oil tank           |
|  | Electric predisposition    |  | Platform predisposition |  | Tyre handler, cylinder handler predisposition |



**Head Office**

B.P. 249 - 430 rue de l'Aubinière  
44150 Ancenis Cedex - France  
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97  
[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes