

Technical sheet :

# **TILTING FORK CARRIAGE (MRT - MHT)**

---



## **Customer benefits**

- Efficient handling solution.

## **Technical characteristics**

- Tilting forks.
- Forks compliant with FEM standard, forks' length according to model.
- Note: road circulation kit mandatory in Italy. Contact your dealer.
- Note: road circulation kit mandatory in Germany on MRT Vision/Vision+. Contact your dealer.

[The 3D picture at the top of this page is the reference CAT 1320 / 6 T (a) - 52718348].

Capacities		CAT 1320 / 6 T (a)	CAT 1320 / 7 T (a)	CAT 1750 / 5 T (a)	CAT 1750 / 7 T (a)	CAT 1750 / 2.5 T	CAT 2000 / 5 T (a)	CAT 2000 / 7 T (a)	PFB 1320 (c4.5)	PFB 1320 (c4.5b)	PFB 1320 (c5-a)
Capacity (lb)		13228	15432	11023	15432	5512	11023	15432	9921	9921	11023
<b>Weight and dimensions</b>											
Overall height (in)	h17	3' 2"	3' 2"	2' 8"	3' 1"	2' 8"	2' 8"	3' 2"	2' 8"	2' 8"	2' 8"
Width (in)		4' 7"	4' 7"	6'	6'	6'	6' 10"	6' 10"	4' 7"	4' 7"	4' 7"
<b>Working Parameters</b>											
Machine Equipment		✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
Fork spread minimum (in)	b5	1' 1"	1' 3"	1' 7"	1' 3"	1' 7"	1' 7"	1' 3"	1' 6"	1' 7"	1' 7"
Fork spread maximum (in)	b5	3' 11"	4' 1"	5' 7"	5' 7"	5' 7"	6' 1"	6' 4"	3' 8"	4' 1"	4' 1"
<b>Available fork dimensions</b>											
125 x 50 x 1200									924877		
150 x 50 x 1200				52721175			52721208				921245
100 x 60 x 1200		52718348									
150 x 60 x 1200			52655420		52655520			52655525			
150 x 50 x 1500				52721176			52721209				
100 x 60 x 1500		52718356									
150 x 60 x 1500			52718373		52718375			52718378			
150 x 50 x 1800										52601398	
100 x 60 x 1800		52718357									
150 x 60 x 1800			52718374		52718377			52718379			
150 x 50 x 2000						52721177	52721210				







Machines compatibility		CAT 1320 / 6 T (a)	CAT 1320 / 7 T (a)	CAT 1750 / 5 T (a)	CAT 1750 / 7 T (a)	CAT 1750 / 2.5 T	CAT 2000 / 5 T (a)	CAT 2000 / 7 T (a)	PFB 1320 (c4.5)	PFB 1320 (c4.5b)	PFB 1320 (c5-a)
MRT 1645 75		-	-	X	-	X	X	-	X	X	-
MRT 1645 115		-	-	X	-	X	X	-	X	X	-
MRT 1845 75		-	-	X	-	X	X	-	X	X	-
MRT 1845 115		-	-	X	-	X	X	-	X	X	-
MRT 2145 115		-	-	X	-	X	X	-	X	X	-
MRT 2260		X	-	-	X	-	-	X	-	-	-
MRT 2260 e		X	-	-	X	-	-	X	-	-	-
MRT 2545 115		-	-	X	-	X	X	-	X	X	-
MRT 2570		-	X	-	X	-	-	X	-	-	-
MRT 2660		X	-	-	X	-	-	X	-	-	-
MRT 2660 e		X	-	-	X	-	-	X	-	-	-
MRT 3060		X	-	-	X	-	-	X	-	-	-
MRT 3570		-	X	-	X	-	-	X	-	-	-
MRT 3570 ES		-	X	-	X	-	-	X	-	-	-
MRT-X 1645		-	-	X	-	X	X	-	X	X	-
MRT-X 1845		-	-	X	-	X	X	-	X	X	-
MRT-X 2145		-	-	X	-	X	X	-	X	X	-
MRT-X 2260		X	-	-	X	-	-	X	-	-	-
MRT-X 2545		-	-	X	-	X	X	-	X	X	-
MRT-X 2570		-	X	-	X	-	-	X	-	-	-
MRT-X 2660		X	-	-	X	-	-	X	-	-	-
MRT-X 3060		X	-	-	X	-	-	X	-	-	-
MRT-X 3570		-	X	-	X	-	-	X	-	-	-
MRT-X 3570 ES		-	X	-	X	-	-	X	-	-	-
MRT 1440 Easy T4 S2 400° <b>OLD</b>		-	-	-	-	-	-	-	X	-	X
MRT 1640 Easy T4 S2 360° <b>OLD</b>		-	-	-	-	-	-	-	X	-	X
MRT 1640 Easy T4 S2 400° <b>OLD</b>		-	-	-	-	-	-	-	X	-	X
MRT 1840 Easy T4 S2 360° <b>OLD</b>		-	-	-	-	-	-	-	X	-	X
MRT 1840 Easy T4 S2 400° <b>OLD</b>		-	-	-	-	-	-	-	X	-	X
MRT 2145 Easy T4 S2 360° <b>OLD</b>		-	-	-	-	-	-	-	X	-	X
MRT 2145 Easy T4 S2 400° <b>OLD</b>		-	-	-	-	-	-	-	X	-	X
MRT 2150 Privilege Plus <b>OLD</b>		X	-	-	X	-	-	X	-	-	X
MRT 2470 Privilege Plus <b>OLD</b>		-	X	-	X	-	-	X	-	-	X
MRT 2545 Easy T4 S2 360° <b>OLD</b>		-	-	-	-	-	-	-	X	-	X
MRT 2545 Easy T4 S2 400° <b>OLD</b>		-	-	-	-	-	-	-	X	-	X
MRT 2550 Privilege Plus <b>OLD</b>		X	-	-	X	-	-	X	-	-	X
MRT 3050 Privilege Plus <b>OLD</b>		X	-	-	X	-	-	X	-	-	X
MRT 3255 Privilege Plus <b>OLD</b>		-	X	-	X	-	-	X	-	-	-
MRT-X 1840 Easy 360° <b>OLD</b>		-	-	-	-	-	-	-	X	-	X
MRT-X 1840 Easy 400° <b>OLD</b>		-	-	-	-	-	-	-	X	-	X
MRT-X 2145 Easy 360° <b>OLD</b>		-	-	-	-	-	-	-	X	-	X
MRT-X 2145 Easy 400° <b>OLD</b>		-	-	-	-	-	-	-	X	-	X
MRT-X 2150 Privilege Plus <b>OLD</b>		X	-	-	X	-	-	X	-	-	X
MRT-X 2470 Privilege Plus <b>OLD</b>		-	X	-	X	-	-	X	-	-	X
MRT-X 2545 Easy 360° <b>OLD</b>		-	-	-	-	-	-	-	X	-	X
MRT-X 2545 Easy 400° <b>OLD</b>		-	-	-	-	-	-	-	X	-	X
MRT-X 2550 Privilege Plus <b>OLD</b>		X	-	-	X	-	-	X	-	-	X
MRT-X 3050 Privilege Plus <b>OLD</b>		X	-	-	X	-	-	X	-	-	X
MRT-X 3255 Privilege Plus <b>OLD</b>		-	X	-	X	-	-	X	-	-	-

Capacities		PFB 1320 (c5-b)	PFB 1320 (c5-c)	PFB 1320 (c5-d)	PFB 1320 (c7-a)	PFB 1320 (c7-b)	PFB 1750 (c5-a)	PFB 1750 (c5-b)	PFB 1750 (c5-c)	PFB 1750 (c7)	PFB 1750 (c9)
Capacity (lb)		11023	11023	11023	15432	15432	11023	11023	11023	15432	19842
<b>Weight and dimensions</b>											
Overall height (in)	h17	3' 1"	2' 8"	2' 8"	4' 8"	4' 8"	-	-	2' 8"	4' 8"	2' 9"
Width (in)		4' 7"	4' 7"	4' 7"	4' 8"	4' 8"	5' 9"	5' 9"	6'	6' 1"	6'
<b>Working Parameters</b>											
Machine Equipment		✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
Fork spread minimum (in)	b5	-	1' 7"	1' 7"	1' 3"	1' 3"	-	-	1' 7"	1' 3"	1' 5"
Fork spread maximum (in)	b5	-	4' 1"	4' 1"	4' 1"	4' 1"	-	-	5' 7"	5' 7"	5' 8"
<b>Available fork dimensions</b>											
150 x 50 x 1200		53009916	52576641	923864			921246	53010108	52579341		
150 x 60 x 1200					52585460	52587815					
200 x 60 x 1200											939056
150 x 50 x 1500							921529		52579342		
200 x 60 x 1500											53021960
150 x 60 x 1600										52581520	
150 x 50 x 1800				923865							
200 x 60 x 2000											53025302

Machines compatibility	PFB 1320 (c5-b)	PFB 1320 (c5-c)	PFB 1320 (c5-d)	PFB 1320 (c7-a)	PFB 1320 (c7-b)	PFB 1750 (c5-a)	PFB 1750 (c5-b)	PFB 1750 (c5-c)	PFB 1750 (c7)	PFB 1750 (c9)
MHT 790 Mining ST5	-	-	-	-	-	-	-	-	-	X
MHT 790 ST5	-	-	-	-	-	-	-	-	-	X
MHT-X 790 ST3A	-	-	-	-	-	-	-	-	-	X
MHT 790 <b>OLD</b>	-	-	-	-	-	-	-	-	-	X
MHT-X 790 <b>OLD</b>	-	-	-	-	-	-	-	-	-	X
MHT-X 790 Mining <b>OLD</b>	-	-	-	-	-	-	-	-	-	X
MRT 1440 Easy T4 S2 400° <b>OLD</b>	-	-	X	-	-	X	-	-	-	-
MRT 1640 Easy T4 S2 360° <b>OLD</b>	-	-	X	-	-	X	-	-	-	-
MRT 1640 Easy T4 S2 400° <b>OLD</b>	-	-	X	-	-	X	-	-	-	-
MRT 1840 Easy T4 S2 360° <b>OLD</b>	-	-	X	-	-	X	-	-	-	-
MRT 1840 Easy T4 S2 400° <b>OLD</b>	-	-	X	-	-	X	-	-	-	-
MRT 2145 Easy T4 S2 360° <b>OLD</b>	-	-	X	-	-	X	-	-	-	-
MRT 2145 Easy T4 S2 400° <b>OLD</b>	-	-	X	-	-	X	-	-	-	-
MRT 2150 Privilege Plus <b>OLD</b>	-	-	X	-	-	X	-	-	-	-
MRT 2470 Privilege Plus <b>OLD</b>	-	X	-	X	X	-	-	X	X	-
MRT 2545 Easy T4 S2 360° <b>OLD</b>	-	-	X	-	-	X	-	-	-	-
MRT 2545 Easy T4 S2 400° <b>OLD</b>	-	-	X	-	-	X	-	-	-	-
MRT 2550 Privilege Plus <b>OLD</b>	-	-	X	-	-	X	-	-	-	-
MRT 3050 Privilege Plus <b>OLD</b>	-	X	-	-	-	-	-	X	-	-
MRT 3255 Privilege Plus <b>OLD</b>	X	-	-	-	-	-	X	-	-	-
MRT-X 1840 Easy 360° <b>OLD</b>	-	-	X	-	-	X	-	-	-	-
MRT-X 1840 Easy 400° <b>OLD</b>	-	-	X	-	-	X	-	-	-	-
MRT-X 2145 Easy 360° <b>OLD</b>	-	-	X	-	-	X	-	-	-	-
MRT-X 2145 Easy 400° <b>OLD</b>	-	-	X	-	-	X	-	-	-	-
MRT-X 2150 Privilege Plus <b>OLD</b>	-	-	X	-	-	X	-	-	-	-
MRT-X 2470 Privilege Plus <b>OLD</b>	-	X	-	X	X	-	-	X	X	-
MRT-X 2545 Easy 360° <b>OLD</b>	-	-	X	-	-	X	-	-	-	-
MRT-X 2545 Easy 400° <b>OLD</b>	-	-	X	-	-	X	-	-	-	-
MRT-X 2550 Privilege Plus <b>OLD</b>	-	-	X	-	-	X	-	-	-	-
MRT-X 3050 Privilege Plus <b>OLD</b>	-	X	-	-	-	-	-	X	-	-
MRT-X 3255 Privilege Plus <b>OLD</b>	X	-	-	-	-	-	X	-	-	-

Capacities		PFB 2000 (c5-a)	PFB 2000 (c5-b)	PFB 2000 (c5-c)	PFB 2000 (c7)	PFB 2000 (c9)
Capacity (lb)		11023	11023	11023	15432	19842
<b>Weight and dimensions</b>						
Overall height (in)	h17	-	4' 9"	2' 8"	4' 8"	2' 9"
Width (in)		6' 7"	6' 11"	6' 10"	6' 11"	6' 10"
<b>Working Parameters</b>						
Machine Equipment		✗	✗	✗	✗	✗
Fork spread minimum (in)	b5	-	-	1' 7"	1' 3"	1' 5"
Fork spread maximum (in)	b5	-	-	6' 6"	6' 4"	6' 6"
<b>Available fork dimensions</b>						
150 x 50 x 1200		921247	53010112	52579343		
200 x 60 x 1200						939058
150 x 50 x 1500		921533		52579344		
200 x 60 x 1500						53022163
150 x 60 x 1600					52581550	
200 x 60 x 2000						53025305

Machines compatibility		PFB 2000 (c5-a)	PFB 2000 (c5-b)	PFB 2000 (c5-c)	PFB 2000 (c7)	PFB 2000 (c9)
MHT 790 Mining ST5		-	-	-	-	X
MHT 790 ST5		-	-	-	-	X
MHT-X 790 ST3A		-	-	-	-	X
MHT 790 <b>OLD</b>		-	-	-	-	X
MHT-X 790 <b>OLD</b>		-	-	-	-	X
MHT-X 790 Mining <b>OLD</b>		-	-	-	-	X
MRT 1440 Easy T4 S2 400° <b>OLD</b>		X	-	-	-	-
MRT 1640 Easy T4 S2 360° <b>OLD</b>		X	-	-	-	-
MRT 1640 Easy T4 S2 400° <b>OLD</b>		X	-	-	-	-
MRT 1840 Easy T4 S2 360° <b>OLD</b>		X	-	-	-	-
MRT 1840 Easy T4 S2 400° <b>OLD</b>		X	-	-	-	-
MRT 2145 Easy T4 S2 360° <b>OLD</b>		X	-	-	-	-
MRT 2145 Easy T4 S2 400° <b>OLD</b>		X	-	-	-	-
MRT 2150 Privilege Plus <b>OLD</b>		X	-	-	-	-
MRT 2470 Privilege Plus <b>OLD</b>		-	-	X	X	-
MRT 2545 Easy T4 S2 360° <b>OLD</b>		X	-	-	-	-
MRT 2545 Easy T4 S2 400° <b>OLD</b>		X	-	-	-	-
MRT 2550 Privilege Plus <b>OLD</b>		X	-	-	-	-
MRT 3050 Privilege Plus <b>OLD</b>		-	-	X	-	-
MRT 3255 Privilege Plus <b>OLD</b>		-	X	-	-	-
MRT-X 1840 Easy 360° <b>OLD</b>		X	-	-	-	-
MRT-X 1840 Easy 400° <b>OLD</b>		X	-	-	-	-
MRT-X 2145 Easy 360° <b>OLD</b>		X	-	-	-	-
MRT-X 2145 Easy 400° <b>OLD</b>		X	-	-	-	-
MRT-X 2150 Privilege Plus <b>OLD</b>		X	-	-	-	-
MRT-X 2470 Privilege Plus <b>OLD</b>		-	-	X	X	-
MRT-X 2545 Easy 360° <b>OLD</b>		X	-	-	-	-
MRT-X 2545 Easy 400° <b>OLD</b>		X	-	-	-	-
MRT-X 2550 Privilege Plus <b>OLD</b>		X	-	-	-	-
MRT-X 3050 Privilege Plus <b>OLD</b>		-	-	X	-	-
MRT-X 3255 Privilege Plus <b>OLD</b>		-	X	-	-	-

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes