

Technical sheet :

TILTING FORKS CARRIAGE WITH SIDE SHIFT - LOAD BACKREST (MLT - MT)






Customer benefits

- Tilting fork carriage with hydraulic side shift and load backrest for efficient high/bulky load placement.
- Guarantees an accurate and efficient positioning of the handled palets.







Technical characteristics


- Bolt-on load backrest for a higher load stability.
- Note: to be used with FEM forks.

| Capacities | | PBF 45N 1670 SS LB | PFB 25N 1020 SS LB | PFB 35N 1260 SS LB |
|---------------------------|-----|---|---|---|
| Capacity (kg) | | 4500 | 2500 | 3500 |
| Weight | | | | |
| Overall weight (kg) | | 595 | 170 | 210 |
| Weight and dimensions | | | | |
| Overall height (mm) | h17 | 1258 | 1222 | 1229 |
| Width (mm) | | 1810 | 1044 | 1284 |
| Working Parameters | | | | |
| Machine Equipment | |  |  |  |
| Side shift (mm) | | 100 | 100 | 100 |
| Available fork dimensions | | | | |
| 125 x 45 x 1200 | | | 52000204 | 52000205 |
| 125 x 50 x 1200 | | 52000206 | | |

| Machines compatibility | PBF 45N 1670 SS LB | PFB 25N 1020 SS LB | PFB 35N 1260 SS LB |
|--------------------------------|--------------------|--------------------|--------------------|
| ALT950 | - | - | X |
| MLA-T 533-145 V+ - ST5 | - | - | X |
| MLTX 741 T LSU | X | - | - |
| MT 625 e | - | X | - |
| MT 625 H | - | X | - |
| MT 625 H Comfort | - | X | - |
| MT 625 HA | - | X | - |
| MT 735 75D ST5 | - | - | X |
| MT 935 75D ST5 | - | - | X |
| MT 1135 75 D | - | - | X |
| MT 1135 H 100D | - | - | X |
| MT 1335 75D ST5 | - | - | X |
| MT 1335 100D ST5 | - | - | X |
| MT 1335 H 75D ST5 | - | - | X |
| MT 1335 H 100D ST5 | - | - | X |
| MT 1440 A ST5 | X | - | - |
| MT 1440 easy ST5 | X | - | - |
| MT 1440 HA ST5 | X | - | - |
| MT 1440 ST5 | X | - | - |
| MT 1840 A 100D ST5 S1 | X | - | - |
| MT 1840 easy ST5 | X | - | - |
| MT 1840 HA | X | - | - |
| MT 1840 ST5 | X | - | - |
| MT-X 733 | - | - | X |
| MT-X 1033 | - | - | X |
| MT-X 1440 | X | - | - |
| MT-X 1440 A | X | - | - |
| MT-X 1840 | X | - | - |
| MT-X 1840 A | X | - | - |
| MT 733 Easy OLD | - | - | X |
| MT 933 Easy OLD | - | - | X |
| MT 1033 easy OLD | - | - | X |
| MT 1135 H easy ST5 OLD | - | - | X |
| MT 1135 HA Easy ST5 OLD | - | - | X |
| MT 1135 ST5 OLD | - | - | X |
| MT 1335 OLD | - | - | X |
| MT 1335 easy ST5 OLD | - | - | X |
| MT 1335 H easy ST5 OLD | - | - | X |
| MT 1335 ST5 OLD | - | - | X |
| MT 1440 OLD | X | - | - |
| MT 1440 A OLD | X | - | - |
| MT 1440 HA OLD | X | - | - |
| MT 1840 OLD | X | - | - |
| MT 1840 A OLD | X | - | - |
| MT 1840 HA OLD | X | - | - |

TABLE SYMBOL

| | | | | | |
|---|----------------------------|---|-------------------------|---|---|
|  | No predisposition required |  | Hydraulic line |  | Return piping to hydraulic oil tank |
|  | Electric predisposition |  | Platform predisposition |  | Tyre handler, cylinder handler predisposition |



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes