

Technical sheet :

# WOOD CLAMP



## Technical characteristics

- High gripping power with two hydraulic cylinders.
- Special shape of retainer for safe wood handling.

[The 3D picture at the top of this page is the reference CLHW 1200/3 - 52797759].


## Customer benefits

- Must-have attachment for handling of wood logs and branches.
- Robust structure for heavy work.

<b>Capacities</b>		CLHW 1200/3
Capacity (kg)		3000
<b>Weight</b>		
Overall weight (kg)		461
<b>Weight and dimensions</b>		
Overall height (mm)	h17	1185
Overall length (mm)	l1	1091
Width (mm)		1248
Closed grapple height (mm)	h33	1185
Opened grapple height (mm)	h34	1429
Minimum diameter / Maximum diameter (mm)		460 / 900
<b>Working Parameters</b>		
Required machine equipment		

<b>Machines compatibility</b>	CLHW 1200/3
Reference number	52797759
ALT950	X
MLA-T 533-145 V+ - ST5	X
MLT 630-115 (S2)	X
MLT 630-115 V (S2)	X
MLT 630-115 V CP (S2)	X
MLT 635-130 PS+ (S2)	X
MLT 635-140 V+ (S2)	X
MLT 730-115 V (S2)	X
MLT 730-115 V CP (S2)	X
MLT 733-115 (S2)	X
MLT 738-130 PS+ (S1)	X
MLT 742-130 PS+ (S1)	X
MLT 742-140 V+ (S1)	X
MLT 850-145 V+	X
MLT 937-115 (S1)	X
MLT 961-160 V+ L	X
MLTX 738-130 PS+ (S1)	X
MLTX 850-145 V+	X
MLTX 961-160 V+ L	X

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



# **MANITOU** HANDLING YOUR WORLD

## Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes